

# An introduction to coding theory

Adrish Banerjee

Department of Electrical Engineering  
Indian Institute of Technology Kanpur  
Kanpur, Uttar Pradesh  
India

Feb. 20, 2017



## Lecture #12: Performance Bounds for Convolutional Codes

# Introduction

- We will analyze the performance of maximum likelihood decoding for a convolutional code over binary symmetric channel.

# Introduction

- We will analyze the performance of maximum likelihood decoding for a convolutional code over binary symmetric channel.
- Without loss of generality, we assume that the all zero codeword  $\mathbf{0}$  is transmitted from a  $(3, 1, 2)$  nonsystematic feedforward encoder with

$$\mathbf{G}(\mathbf{D}) = [1 + D \quad 1 + D^2 \quad 1 + D + D^2]$$

# Introduction

- We will analyze the performance of maximum likelihood decoding for a convolutional code over binary symmetric channel.
- Without loss of generality, we assume that the all zero codeword  $\mathbf{0}$  is transmitted from a  $(3, 1, 2)$  nonsystematic feedforward encoder with

$$\mathbf{G}(\mathbf{D}) = [1 + D \quad 1 + D^2 \quad 1 + D + D^2]$$


- The Input Output Weight Enumerating Function (IOWEF) of this encoder is given by

$$\begin{aligned} A(W, X, L) &= \frac{X^7 W L^3}{1 - X W L (1 + X^2 L)} \\ &= X^7 W L^3 + X^8 W^2 L^4 + X^9 W^3 L^5 + X^{10} (W^2 L^5 + W^4 L^6 + \dots) \end{aligned}$$

Navigation icons: back, forward, search, etc.

## First Error Event

- A first event error happens at an arbitrary time  $t$  if the all zero path is eliminated for the first time in favor of an incorrect path.



Navigation icons: back, forward, search, etc.

# First Error Event

- The incorrect path must have diverged from all zero state at some time and has now remerged at time  $t$  for the first time.

# First Error Event

- The incorrect path must have diverged from all zero state at some time and has now remerged at time  $t$  for the first time.
- So, it must be one of the path enumerated by the codeword weight enumerating function.

# First Error Event

- The incorrect path must have diverged from all zero state at some time and has now remerged at time  $t$  for the first time.
- So, it must be one of the path enumerated by the codeword weight enumerating function.
- Assuming that the incorrect path has weight  $d$ , a first event error happens with probability

$$P_d = \begin{cases} \sum_{e=\frac{d+1}{2}}^d \binom{d}{e} p^e (1-p)^{d-e} & \text{odd} \\ \frac{1}{2} \binom{d}{d/2} p^{d/2} (1-p)^{d/2} + \sum_{e=\frac{d}{2}+1}^d \binom{d}{e} p^e (1-p)^{d-e} & \text{even} \end{cases}$$

## Convolutional codes

- All incorrect paths of length  $t$  branches or less can cause a first event error at time  $t$ .

# Convolutional codes

- All incorrect paths of length  $t$  branches or less can cause a first event error at time  $t$ .
- Thus the first event error probability at time  $t$  can be bounded using union bound by the sum of the error probabilities of each of these paths.

# Convolutional codes

- All incorrect paths of length  $t$  branches or less can cause a first event error at time  $t$ .
- Thus the first event error probability at time  $t$  can be bounded using union bound by the sum of the error probabilities of each of these paths.
- If all incorrect paths of length greater than  $t$  are also included, then the first event error probability at any time  $t$  can be bounded by

$$P_f(E) < \sum_{d=d_{\text{free}}}^{\infty} A_d P_d$$

where  $A_d$  is the number of codewords of weight  $d$ .

## First Error Event

- For odd  $d$ , we can write

$$\begin{aligned} P_d &= \sum_{e=\frac{d+1}{2}}^d \binom{d}{e} p^e (1-p)^{d-e} \\ &< \sum_{e=\frac{d+1}{2}}^d \binom{d}{e} p^{d/2} (1-p)^{d/2} \\ &= p^{d/2} (1-p)^{d/2} \sum_{e=\frac{d+1}{2}}^d \binom{d}{e} \\ &< p^{d/2} (1-p)^{d/2} \sum_{e=0}^d \binom{d}{e} \\ &= 2^d p^{d/2} (1-p)^{d/2} \end{aligned}$$

## First Error Event

- Similarly, for even  $d$ , we have

$$\begin{aligned}
 P_d &= \frac{1}{2} \binom{d}{d/2} p^{d/2} (1-p)^{d/2} + \sum_{e=(d/2)+1}^d \binom{d}{e} p^e (1-p)^{d-e} \\
 &< \sum_{e=(d/2)}^d \binom{d}{e} p^e (1-p)^{d-e} \\
 &< \sum_{e=(d/2)}^d \binom{d}{e} p^{d/2} (1-p)^{d/2} \\
 &= p^{d/2} (1-p)^{d/2} \sum_{e=(d/2)}^d \binom{d}{e} \\
 &< p^{d/2} (1-p)^{d/2} \sum_{e=0}^d \binom{d}{e} = 2^d p^{d/2} (1-p)^{d/2}
 \end{aligned}$$

# Event error probability

- Hence,

$$\begin{aligned} P_f(E) &< \sum_{d=d_{\text{free}}}^{\infty} A_d [2\sqrt{p(1-p)}]^d \\ &= A(X)|_{X=2\sqrt{p(1-p)}} \end{aligned}$$

# Event error probability

- Hence,

$$\begin{aligned} P_f(E) &< \sum_{d=d_{\text{free}}}^{\infty} A_d [2\sqrt{p(1-p)}]^d \\ &= A(X)|_{X=2\sqrt{p(1-p)}} \end{aligned}$$

- We have event error probability at time time t upper bounded by first event error probability, hence

$$P(E) < A(X)|_{X=2\sqrt{p(1-p)}}$$



## Event error probability

- Hence,

$$P_f(E) < \sum_{d=d_{\text{free}}}^{\infty} A_d [2\sqrt{p(1-p)}]^d$$

$$= A(X)|_{X=2\sqrt{p(1-p)}}$$

- We have event error probability at time time  $t$  upper bounded by first event error probability, hence

$$P(E) < A(X)|_{X=2\sqrt{p(1-p)}}$$

- For small  $p$ , the bound is dominated by the first time, thus event error probability can be approximated as

$$P(E) \approx A_{d_{\text{free}}} [2\sqrt{p(1-p)}]^{d_{\text{free}}}$$

## Bit error probability

- The bit error probability can be bounded by

$$P_b(E) < \sum_{d=d_{\text{free}}}^{\infty} B_d P_d$$

where  $B_d$  is the total number of nonzero information bits on all weight-d paths, divided by the number of information bits  $k$  per unit time

## Bit error probability

- The bit error probability can be bounded by

$$P_b(E) < \sum_{d=d_{\text{free}}}^{\infty} B_d P_d$$


where  $B_d$  is the total number of nonzero information bits on all weight-d paths, divided by the number of information bits  $k$  per unit time

- Then we can write


$$P_b(E) < \sum_{d=d_{\text{free}}}^{\infty} B_d [2\sqrt{p(1-p)}]^d = B(X)|_{X=2\sqrt{p(1-p)}}$$

## Multiple error events


- Multiple error events




# Different error events configuration



# Different error events configuration



# Different error events configuration



## Example: Computation of Event error probability

- For the (3, 1, 2) encoder calculate the event error probability for crossover probability of  $p = 10^{-2}$  for binary symmetric channel.

## Example: Computation of Event error probability

- For the (3, 1, 2) encoder calculate the event error probability for crossover probability of  $p = 10^{-2}$  for binary symmetric channel.
- $d_{\text{free}} = 7$  and  $A_{d_{\text{free}}} = 1$ , then we have

$$P(E) \approx 2^7 p^{7/2} = 1.28 \times 10^{-5}$$

## Example: Computation of bit error probability

- Calculate the bit error probability for the same encoder for  $p = 10^{-2}$ .

## Example: Computation of bit error probability

- Calculate the bit error probability for the same encoder for  $p = 10^{-2}$ .
- The bit weight enumerating function is given by

$$\begin{aligned} B(X) &= (1/k) \frac{\partial A(W, X)}{\partial W} \Big|_{W=1} \\ &= \frac{\partial [X^7 W / (1 - XW - X^3 W)]}{\partial W} \Big|_{W=1} \\ &= \frac{X^7}{(1 - 2X + X^2 - 2X^3 + 2X^4 + X^6)} \end{aligned}$$

## Example: Computation of bit error probability

- Calculate the bit error probability for the same encoder for  $p = 10^{-2}$ .
- The bit weight enumerating function is given by

$$\begin{aligned} B(X) &= (1/k) \frac{\partial A(W, X)}{\partial W} \Big|_{W=1} \\ &= \frac{\partial [X^7 W / (1 - XW - X^3 W)]}{\partial W} \Big|_{W=1} \\ &= \frac{X^7}{(1 - 2X + X^2 - 2X^3 + 2X^4 + X^6)} \end{aligned}$$

- $d_{\text{free}} = 7$  and  $B_{d_{\text{free}}} = 1$ , then we have

$$P(E) \approx 2^7 p^{7/2} = 1.28 \times 10^{-5}$$