

# An introduction to coding theory

Adrish Banerjee

Department of Electrical Engineering  
Indian Institute of Technology Kanpur  
Kanpur, Uttar Pradesh  
India

Feb. 13, 2017



## Lecture #10: Decoding of convolutional codes-I: Viterbi algorithm



# Convolutional codes

Outline of the lecture:

- Viterbi decoding of  $(n, 1, m)$  code.



# Convolutional codes

Outline of the lecture:

- Viterbi decoding of  $(n, 1, m)$  code.
- Example: Viterbi decoding of  $(2, 1, 2)$  convolutional code on BSC.



## Viterbi decoding of $(n, 1, m)$ code

- A convolutional code can be represented by its trellis diagram.



## Viterbi decoding of $(n, 1, m)$ code

- A convolutional code can be represented by its trellis diagram.
- Usually, the initial state of a convolutional code is a all-zero state.



## Viterbi decoding of $(n, 1, m)$ code

- A convolutional code can be represented by its trellis diagram.
- Usually, the initial state of a convolutional code is a all-zero state.
- For time,  $l \leq m$ , as information bits are shifted into the encoder, the number of states are doubled.



## Viterbi decoding of $(n, 1, m)$ code

- A convolutional code can be represented by its trellis diagram.
- Usually, the initial state of a convolutional code is a all-zero state.
- For time,  $l \leq m$ , as information bits are shifted into the encoder, the number of states are doubled.
- At time  $l = m$ , the number of states reaches  $2^m$ .



## Viterbi decoding of $(n, 1, m)$ code

- A convolutional code can be represented by its trellis diagram.
- Usually, the initial state of a convolutional code is a all-zero state.
- For time,  $l \leq m$ , as information bits are shifted into the encoder, the number of states are doubled.
- At time  $l = m$ , the number of states reaches  $2^m$ .
- Since one information bit enters the encoder at each time instant, there are two branches leaving each state in the trellis diagram.



## Viterbi decoding of $(n, 1, m)$ code

- A convolutional code can be represented by its trellis diagram.
- Usually, the initial state of a convolutional code is a all-zero state.
- For time,  $l \leq m$ , as information bits are shifted into the encoder, the number of states are doubled.
- At time  $l = m$ , the number of states reaches  $2^m$ .
- Since one information bit enters the encoder at each time instant, there are two branches leaving each state in the trellis diagram.
- For time,  $l > m$ , there are also two branches merging into each state.




# Viterbi decoding of $(n, 1, m)$ code

- A convolutional code can be represented by its trellis diagram.
- Usually, the initial state of a convolutional code is a all-zero state.
- For time,  $l \leq m$ , as information bits are shifted into the encoder, the number of states are doubled.
- At time  $l = m$ , the number of states reaches  $2^m$ .
- Since one information bit enters the encoder at each time instant, there are two branches leaving each state in the trellis diagram.
- For time,  $l > m$ , there are also two branches merging into each state.
- The encoding of a information sequence is equivalent to tracing a path through a trellis.

Navigation icons: back, forward, search, etc.

## Viterbi Decoding



Navigation icons: back, forward, search, etc.

## Viterbi decoding of $(n, 1, m)$ code

- The encoder is returned to all zero sequence after an L bit information sequence,

$$\mathbf{u} = (u_0, u_1, u_2, \dots, u_{L-1})$$

## Viterbi decoding of $(n, 1, m)$ code

- The encoder is returned to all zero sequence after an L bit information sequence,

$$\mathbf{u} = (u_0, u_1, u_2, \dots, u_{L-1})$$

- During the termination process, the number of states are reduced by half until all trellis paths converge back to the all-zero state.

## Viterbi decoding of $(n, 1, m)$ code

- The encoder is returned to all zero sequence after an  $L$  bit information sequence,

$$\mathbf{u} = (u_0, u_1, u_2, \dots, u_{L-1})$$

- During the termination process, the number of states are reduced by half until all trellis paths converge back to the all-zero state.
- For  $l \leq m$ , there is exactly one path of length  $l$ , entering each node at level(time)  $l$ .



## Viterbi decoding of $(n, 1, m)$ code

- The encoder is returned to all zero sequence after an  $L$  bit information sequence,

$$\mathbf{u} = (u_0, u_1, u_2, \dots, u_{L-1})$$

- During the termination process, the number of states are reduced by half until all trellis paths converge back to the all-zero state.
- For  $l \leq m$ , there is exactly one path of length  $l$ , entering each node at level(time)  $l$ .
- For  $l > m$ , there are exactly  $2^{l-m}$  paths of length  $l$ , entering each node at level(time)  $l$ .





## Viterbi decoding of $(n, 1, m)$ code

- The encoder is returned to all zero sequence after an  $L$  bit information sequence,

$$\mathbf{u} = (u_0, u_1, u_2, \dots, u_{L-1})$$

- During the termination process, the number of states are reduced by half until all trellis paths converge back to the all-zero state.
- For  $l \leq m$ , there is exactly one path of length  $l$ , entering each node at level(time)  $l$ .
- For  $l > m$ , there are exactly  $2^{l-m}$  paths of length  $l$ , entering each node at level(time)  $l$ .
- There are total  $2^l$  paths of length  $l$ .



## Viterbi decoding of $(n, 1, m)$ code

On BSC:

- Let the information sequence of length  $L$

$$\mathbf{u} = (u_0, u_1, \dots, u_l, \dots, u_{L-1})$$

is encoded into code sequence of length  $N \triangleq (L + m)n$

$$\mathbf{v} = (\mathbf{v}_0, \mathbf{v}_1, \dots, \mathbf{v}_l, \dots, \mathbf{v}_{L+m-1})$$



## Viterbi decoding of $(n, 1, m)$ code

On BSC:

- Let the information sequence of length  $L$

$$\mathbf{u} = (u_0, u_1, \dots, u_l, \dots, u_{L-1})$$

is encoded into code sequence of length  $N \triangleq (L + m)n$

$$\mathbf{v} = (\mathbf{v}_0, \mathbf{v}_1, \dots, \mathbf{v}_l, \dots, \mathbf{v}_{L+m-1})$$

- If the code sequence  $\mathbf{v}$  is transmitted over a channel, let the received sequence is,

$$\mathbf{r} = (\mathbf{r}_0, \mathbf{r}_1, \dots, \mathbf{r}_l, \dots, \mathbf{r}_{L+m-1}),$$

where the  $l^{th}$  received block is

$$\mathbf{r}_l = (r_l^{(1)}, r_l^{(2)}, \dots, r_l^{(n)}).$$



## Viterbi decoding of $(n, 1, m)$ code

On BSC:

- A maximum likelihood decoder finds a path through the trellis that maximizes the path conditional probability

$$P(\mathbf{r}|\mathbf{v}) = \prod_{l=0}^{L+m-1} P(\mathbf{r}_l|\mathbf{v}_l)$$

where the branch conditional probability

$$P(\mathbf{r}_l|\mathbf{v}_l) = \prod_{i=1}^n P(r_l^{(i)}|v_l^{(i)})$$



## Viterbi decoding of $(n, 1, m)$ code

On BSC:

- A maximum likelihood decoder finds a path through the trellis that maximizes the path conditional probability

$$P(\mathbf{r}|\mathbf{v}) = \prod_{l=0}^{L+m-1} P(\mathbf{r}_l|\mathbf{v}_l)$$

where the branch conditional probability

$$P(\mathbf{r}_I|\mathbf{v}_I) = \prod_{l=1}^n P(r_l^{(i)}|v_l^{(i)})$$

- The bit conditional probabilities  $P(r_l^{(i)}|v_l^{(i)})$  are the channel transition probabilities.



## Viterbi decoding of $(n, 1, m)$ code

## On BSC:

- Maximizing  $P(\mathbf{r}|\mathbf{v})$  is equivalent to maximizing

$$M(\mathbf{r}|\mathbf{v}) \triangleq \log P(\mathbf{r}|\mathbf{v})$$



## Viterbi decoding of $(n, 1, m)$ code

- Maximizing  $P(\mathbf{r}|\mathbf{v})$  is equivalent to maximizing

- $M(\mathbf{r}|\mathbf{v})$  is called the path metric.  $M(\mathbf{r}|\mathbf{v}) \triangleq \log P(\mathbf{r}|\mathbf{v})$

$$\begin{aligned}
 M(\mathbf{r}|\mathbf{v}) &= \sum_{l=0}^{L+m-1} \log P(\mathbf{r}_l|\mathbf{v}_l) \\
 &= \sum_{l=0}^{L+m-1} M(\mathbf{r}_l|\mathbf{v}_l), \quad (\text{branch metrics}) \\
 M(\mathbf{r}_l|\mathbf{v}_l) &= \sum_{i=1}^n \log P(r_l^{(i)}|v_l^{(i)}) \\
 &= \sum_{i=1}^n M(r_l|v_l), \quad (\text{bit metrics})
 \end{aligned}$$

Navigation icons: back, forward, search, etc.

## Viterbi decoding of $(n, 1, m)$ code

- The partial path metric for the first  $j$  branches of a path  $\mathbf{v}$  is given by

$$M([\mathbf{r}|\mathbf{v}]_j) = \sum_{l=0}^{j-1} M(\mathbf{r}_l|\mathbf{v}_l)$$

Navigation icons: back, forward, search, etc.

## Viterbi decoding of $(n, 1, m)$ code

- The partial path metric for the first  $j$  branches of a path  $\mathbf{v}$  is given by

$$M([\mathbf{r}|\mathbf{v}]_j) = \sum_{l=0}^{j-1} M(\mathbf{r}_l|\mathbf{v}_l)$$

- For BSC, the maximum likelihood decoder decodes the received sequence  $\mathbf{r}$  into code sequence  $\mathbf{v}$  that minimizes the Hamming distance  $d(\mathbf{r}, \mathbf{v})$



## Viterbi decoding of $(n, 1, m)$ code

- The partial path metric for the first  $j$  branches of a path  $\mathbf{v}$  is given by

$$M([\mathbf{r}|\mathbf{v}]_j) = \sum_{l=0}^{j-1} M(\mathbf{r}_l|\mathbf{v}_l)$$

- For BSC, the maximum likelihood decoder decodes the received sequence  $\mathbf{r}$  into code sequence  $\mathbf{v}$  that minimizes the Hamming distance  $d(\mathbf{r}, \mathbf{v})$
- The Viterbi algorithm is a computationally efficient method of finding the path through the trellis with the best metric.



## Viterbi decoding of $(n, 1, m)$ code

- The Viterbi decoder proceeds through the trellis level by level in search of the path with the best metric.

## Viterbi decoding of $(n, 1, m)$ code

- The Viterbi decoder proceeds through the trellis level by level in search of the path with the best metric.
- At each level, the decoder compares the metric of all partial paths entering each state.

## Viterbi decoding of $(n, 1, m)$ code

- The Viterbi decoder proceeds through the trellis level by level in search of the path with the best metric.
- At each level, the decoder compares the metric of all partial paths entering each state.
- The decoder stores the partial path entering each state with the best metric (survivor path) and eliminates all other partial paths.



## Viterbi decoding of $(n, 1, m)$ code

- The Viterbi decoder proceeds through the trellis level by level in search of the path with the best metric.
- At each level, the decoder compares the metric of all partial paths entering each state.
- The decoder stores the partial path entering each state with the best metric (survivor path) and eliminates all other partial paths.
- For  $m \leq l \leq L$ , there are total  $2^m$  survivors.



## Viterbi decoding of $(n, 1, m)$ code

- The Viterbi decoder proceeds through the trellis level by level in search of the path with the best metric.
- At each level, the decoder compares the metric of all partial paths entering each state.
- The decoder stores the partial path entering each state with the best metric (survivor path) and eliminates all other partial paths.
- For  $m \leq l \leq L$ , there are total  $2^m$  survivors.
- The number of survivors decrease during the termination process, until at time  $l = L + m$  when there is only one survivor left.



## Viterbi decoding of $(n, 1, m)$ code

- The Viterbi decoder proceeds through the trellis level by level in search of the path with the best metric.
- At each level, the decoder compares the metric of all partial paths entering each state.
- The decoder stores the partial path entering each state with the best metric (survivor path) and eliminates all other partial paths.
- For  $m \leq l \leq L$ , there are total  $2^m$  survivors.
- The number of survivors decrease during the termination process, until at time  $l = L + m$  when there is only one survivor left.
- the surviving path is the maximum likelihood path.





# Viterbi decoding of $(n, 1, m)$ code

## Viterbi Algorithm:

- Step 1: Starting at level  $l = m$  in the trellis, compute the partial metric for the single path entering each  $m^{th}$  level state. Store the survivor path and its metric for each state.



# Viterbi decoding of $(n, 1, m)$ code

## Viterbi Algorithm:

- Step 1: Starting at level  $l = m$  in the trellis, compute the partial metric for the single path entering each  $m^{th}$  level state. Store the survivor path and its metric for each state.
- Step 2: Increase time  $l$  by one. Compute the partial metric for all the paths entering at the  $(l + 1)^{th}$  level state by adding the branch metric entering that state to the metric of the connecting survivor path at the previous  $l^{th}$  level state. Store the survivor path and its metric for each state.



# Viterbi decoding of $(n, 1, m)$ code


## Viterbi Algorithm:

- Step 1: Starting at level  $l = m$  in the trellis, compute the partial metric for the single path entering each  $m^{th}$  level state. Store the survivor path and its metric for each state.
- Step 2: Increase time  $l$  by one. Compute the partial metric for all the paths entering at the  $(l + 1)^{th}$  level state by adding the branch metric entering that state to the metric of the connecting survivor path at the previous  $l^{th}$  level state. Store the survivor path and its metric for each state.
- Step 3: Repeat Step 2 until you are at the end of the trellis ( $l = L + m$ ).

Navigation icons: back, forward, search, etc.

## Viterbi Decoding

Example:




- This  $(2, 1, 2)$  convolutional code with  $L = 5$  is used on a BSC. The received sequence is

$$\mathbf{r} = (01, 11, 10, 10, 00, 11, 10)$$


Navigation icons: back, forward, search, etc.

# Viterbi Decoding



Trellis diagram of (2, 1, 2) convolutional code with  $L = 5$ .

# Viterbi Decoding



# Viterbi Decoding

$$\mathbf{r} = (01, 11)$$

$\mathbf{v}_1 = (00, 00)$	$d(\mathbf{v}_1, \mathbf{r}) = 3$
$\mathbf{v}_2 = (00, 11)$	$d(\mathbf{v}_2, \mathbf{r}) = 1$
$\mathbf{v}_3 = (11, 01)$	$d(\mathbf{v}_3, \mathbf{r}) = 2$
$\mathbf{v}_4 = (11, 10)$	$d(\mathbf{v}_4, \mathbf{r}) = 2$


Navigation icons: back, forward, search, etc.

Adrish Banerjee

Department of Electrical Engineering Indian Institute of Technology Kanpur Kanpur, Uttar Pradesh India

An introduction to coding theory

# Viterbi Decoding




Navigation icons: back, forward, search, etc.

Adrish Banerjee

Department of Electrical Engineering Indian Institute of Technology Kanpur Kanpur, Uttar Pradesh India

An introduction to coding theory

# Viterbi Decoding




$\mathbf{r} = (01, 11, 10, 10)$

Level 4



# Viterbi Decoding




$\mathbf{r} = (01, 11, 10, 10, 00)$

Level 5



# Viterbi Decoding




Adrish Banerjee

Department of Electrical Engineering Indian Institute of Technology Kanpur Kanpur, Uttar Pradesh India

An introduction to coding theory

# Viterbi Decoding



Adrish Banerjee

Department of Electrical Engineering Indian Institute of Technology Kanpur Kanpur, Uttar Pradesh India

An introduction to coding theory

# Viterbi Decoding

