



Ocean Thermal Energy: Conversion (OTEC)

Learning objectives:

- 1) To describe the principle behind OTEC operation
- 2) To indicate challenges with OTEC
- 3) To state the limitations of OTEC

Principle of OTEC:

- Temperature difference between warm water at the surface and colder water approximately 1km below the surface is used to run a heat engine and energy is extracted from the same
- Temperature difference can be of the order of 15 °C to 25 °C

Thermal profile of sea water

First 20 m absorbs sunlight. Surface freezing at poles to 36 °C in the Persian Gulf



Water turbulent and mixed for a few hundred meters



Boundary of a few hundred meters between mixed layer and undisturbed water below. Called Thermocline


90% of sea water below thermocline, temperature around 3 °C

Challenges working under sea:

- 1) Marina Trench, 11 km deep, visited by 3 people
- 2) Moon, nearly 384,400 km, visited by 12 people










$$\eta = 1 - \frac{T_2}{T_1} = 1 - \frac{273 + 5}{273 + 25}$$

$$\eta = 6.7\%$$







Air-conditioning



1 km
15 to 25 °C





Electricity

Air-conditioning



1 km
15 to 25 °C




Electricity



Desalinated water

Drinking water
Irrigation

Air-conditioning

1 km
15 to 25 °C





Electricity

Desalinated water


Cold water


Drinking water
Irrigation

Mariculture

Air-conditioning

1 km
15 to 25 °C





Open Cycle: Warm sea water evaporates at low pressure, runs turbine, condensed by cold sea water. Desalinated water becomes available

Closed cycle: Low boiling point liquid, ammonia, -33°C . Warm water makes it evaporate and run turbine, cold water condenses it afterwards

Conclusions:

- 1) OTEC is available to tap in almost all coastal regions
- 2) Can be setup off-shore as well
- 3) Efficiencies are low
- 4) Stability of structures in the presence of water currents is a factor to address