

Module 3: Hydrostatic forces on submerged bodies

Lecture 7: Calculation of horizontal component, buoyancy

☰ Forces on submerged bodies (continued)

☰ Buoyancy

◀◀ Previous   Next ▶▶


## Module 3: Hydrostatic forces on submerged bodies

## Lecture 7: Calculation of horizontal component, buoyancy

## Forces on submerged bodies (continued)

## Horizontal component

Re-consider the submerged surface 'AB' in a liquid.




(Fig. 7a)

Pressure  $p$  acts normal to  $dA$ , the elemental surface of  $AB$ , at a distance  $Z$  from the origin or the depth ' $h$ ' from the top of the liquid surface.

$$\begin{aligned} d\vec{F}_x &\equiv \text{differential pressure-force acting in x-direction} \\ &= (\rho gh) \hat{n} dA \sin\theta \end{aligned}$$

$$|dF_x| = (\rho gh) dA_x$$

$dA_x$  is the projected area of the submerged surface  $dA$  on  $Z-Y$  plane.



(Fig. 7b)

$$F_x = \int_{A_x} \rho gh dA_x$$


------(i)

◀ Previous    Next ▶

## Module 3: Hydrostatic forces on submerged bodies

## Lecture 7: Calculation of horizontal component, buoyancy


Let us calculate this integral for simple geometries.



(Fig. 7c)

See the figure presented above. All four surfaces marked as 'AB' have the same projected area, marked as A'B', on Y-Z plane because the depths ( $h_1$  and  $h_2$ ) of A and B are the same for all four geometries. Therefore,  $F_x$  will assume identical values for all cases as follows:

$$F_x = \int_{A_x} \rho g h dA_x = \int_{h_1}^{h_2} \rho g h dh \cdot 1 \quad (\text{Assuming unit width of the surface})$$



(Fig. 7d)

$$F_x = \rho g \frac{h_2^2 - h_1^2}{2}$$


Let us re-arrange the right hand Side of the expression

$$= \underbrace{\rho g \left( \frac{h_2 + h_1}{2} \right)}_{\text{pressure acting on the centroid of the the A'B' surface}} \underbrace{(h_2 - h_1)}_{\text{area of the projected surface A'B'}}$$

## Module 3: Hydrostatic forces on submerged bodies

## Lecture 7: Calculation of horizontal component, buoyancy

- Therefore, it may be said that the horizontal component of the hydrostatic pressure-force on a submerged surface is the hydrostatic pressure on the centroid of the projected surface on y-z plane, multiplied by the area of the projection. Alert: line of action of the force does not pass through the centroid! One will have to determine it.
- This can be shown that this is true for all submerged surfaces. Let us consider an object whose projection on y-z plane is a triangular surface. Therefore, for such object,  $F_x$  may be calculated as follows:



(Fig. 7e)

$|F_x| = (\rho g h_c) \times \text{Area of triangle ABC}$  where,  $h_c$  is the depth of the centroid of

$ABC = h + \frac{2}{3} AD$ , where AD is the altitude of the triangle ABC.

Area of the triangle  $ABC = \frac{1}{2} BC AD$

$$\therefore |F_x| = \rho g \left( h + \frac{2}{3} AD \right) \frac{1}{2} BC AD$$

To this end,  $\vec{F} = \vec{F}_x + \vec{F}_z$

$$\text{Or } |F| = \sqrt{F_x^2 + F_z^2}$$

◀ Previous    Next ▶

## Module 3: Hydrostatic forces on submerged bodies


## Lecture 7: Calculation of horizontal component, buoyancy

## Buoyancy

It is a net vertical force acting on the submerged body in a fluid, due to the hydrostatic pressure distribution. It is not a fundamental or physical force. It is an artifact of net pressure distribution in the vertical direction

**Buoyancy force =  $\rho g V$** , where  $V$  is the volume of displaced fluid. The force acts vertically upward.


Consider a cylinder of length ' $\ell$ ' and diameter ' $d$ ' immersed in the fluid:



(Fig. 7f)

- Vertical force acting on the vertical side is zero.
- Vertical force acting on the top circular surface  
 $= (p_{\text{atm}} + (\rho g h_1)) A$ , where  $A = \pi d^2/4$

Note that this is the weight of the fluid trapped between the free surface of the fluid and the top surface of the object, and acts vertically downward)




(Fig. 7g)

## Module 3: Hydrostatic forces on submerged bodies

## Lecture 7: Calculation of horizontal component, buoyancy

Vertical force on the bottom surface

$= (p_{\text{atm}} + (\rho g h_2))A$ , which acts vertically upward. Note that this is the weight of the fluid trapped in the column of height  $(h_1 + l)$  over the bottom surface of the cylinder.



(Fig. 7h)

Net force (vertical) on the cylinder  $= \rho g(h_2 - h_1)A$  or  $\rho g l A$ , which is the same as  $\rho g V$ , where  $V$  is the volume of the cylinder. Thus, buoyancy is the weight of the displaced fluid by the cylinder, acting upward.

◀ Previous    Next ▶