

# An introduction to coding theory

Adrish Banerjee

Department of Electrical Engineering  
Indian Institute of Technology Kanpur  
Kanpur, Uttar Pradesh  
India

Feb. 20, 2017



## Lecture #11C: Problem solving session-V



# Convolutional codes

- **Problem # 1:** Feedforward encoder inverse: How do we find an estimate of the information sequence from the received sequence without decoding?

# Convolutional codes

- **Problem # 1:** Feedforward encoder inverse: How do we find an estimate of the information sequence from the received sequence without decoding?
- **Solution:** Since  $\mathbf{v}(\mathbf{D}) = \mathbf{u}(\mathbf{D})\mathbf{G}(\mathbf{D})$ , we need an inverse matrix  $\mathbf{G}^{-1}(\mathbf{D})$  such that  $\mathbf{G}(\mathbf{D})\mathbf{G}^{-1}(\mathbf{D}) = \mathbf{D}^l$  for some positive  $l$ .

## Convolutional codes

- **Problem # 1:** Feedforward encoder inverse: How do we find an estimate of the information sequence from the received sequence without decoding?
- **Solution:** Since  $\mathbf{v}(\mathbf{D}) = \mathbf{u}(\mathbf{D})\mathbf{G}(\mathbf{D})$ , we need an inverse matrix  $\mathbf{G}^{-1}(\mathbf{D})$  such that  $\mathbf{G}(\mathbf{D})\mathbf{G}^{-1}(\mathbf{D}) = D^l$  for some positive  $l$ .
- Then  $\mathbf{v}(\mathbf{D})\mathbf{G}^{-1}(\mathbf{D}) = \mathbf{u}(\mathbf{D})\mathbf{G}(\mathbf{D})\mathbf{G}^{-1}(\mathbf{D}) = \mathbf{u}(\mathbf{D})\mathbf{I}D^l = \mathbf{u}(\mathbf{D})D^l$



## Convolutional codes

- **Problem # 1:** Feedforward encoder inverse: How do we find an estimate of the information sequence from the received sequence without decoding?
- **Solution:** Since  $\mathbf{v}(\mathbf{D}) = \mathbf{u}(\mathbf{D})\mathbf{G}(\mathbf{D})$ , we need an inverse matrix  $\mathbf{G}^{-1}(\mathbf{D})$  such that  $\mathbf{G}(\mathbf{D})\mathbf{G}^{-1}(\mathbf{D}) = D^l$  for some positive  $l$ .
- Then  $\mathbf{v}(\mathbf{D})\mathbf{G}^{-1}(\mathbf{D}) = \mathbf{u}(\mathbf{D})\mathbf{G}(\mathbf{D})\mathbf{G}^{-1}(\mathbf{D}) = \mathbf{u}(\mathbf{D})\mathbf{I}D^l = \mathbf{u}(\mathbf{D})D^l$
- For a rate  $R=1/n$  code, a feedforward inverse exists if and only if

$$\text{GCD}\{\mathbf{g}^0(\mathbf{D}), \mathbf{g}^1(\mathbf{D}), \dots, \mathbf{g}^{n-1}(\mathbf{D})\} = D^l$$



## Convolutional codes

- **Problem # 1:** Feedforward encoder inverse: How do we find an estimate of the information sequence from the received sequence without decoding?
- **Solution:** Since  $\mathbf{v}(\mathbf{D}) = \mathbf{u}(\mathbf{D})\mathbf{G}(\mathbf{D})$ , we need an inverse matrix  $\mathbf{G}^{-1}(\mathbf{D})$  such that  $\mathbf{G}(\mathbf{D})\mathbf{G}^{-1}(\mathbf{D}) = D^l$  for some positive  $l$ .
- Then  $\mathbf{v}(\mathbf{D})\mathbf{G}^{-1}(\mathbf{D}) = \mathbf{u}(\mathbf{D})\mathbf{G}(\mathbf{D})\mathbf{G}^{-1}(\mathbf{D}) = \mathbf{u}(\mathbf{D})\mathbf{I}D^l = \mathbf{u}(\mathbf{D})D^l$
- For a rate  $R=1/n$  code, a feedforward inverse exists if and only if

$$\text{GCD}\{\mathbf{g}^0(\mathbf{D}), \mathbf{g}^1(\mathbf{D}), \dots, \mathbf{g}^{n-1}(\mathbf{D})\} = D^l$$

- For a rate  $k/n$  code, a feedforward inverse exists if and only if

$$\text{GCD}\{\Delta_i(\mathbf{D}) = D^l\}$$

where  $\{\Delta_i(\mathbf{D})\}$  is the set of all determinants of  $k \times k$  submatrices.

◀ ◻ ▶ ◀ ◻ ▶ ◀ ≡ ▶ ◀ ≡ ▶ ≡ ≡ ↺ ↻

## Convolutional codes

- Let  $\mathbf{G}(\mathbf{D}) = [1 + D^2 + D^3 \quad 1 + D + D^2 + D^3]$ .

◀ ◻ ▶ ◀ ◻ ▶ ◀ ≡ ▶ ◀ ≡ ▶ ≡ ≡ ↺ ↻

## Convolutional codes

- Let  $\mathbf{G}(\mathbf{D}) = [1 + D^2 + D^3 \quad 1 + D + D^2 + D^3]$ .
- $\text{GCD} \{1 + D^2 + D^3, 1 + D + D^2 + D^3\} = 1$ . Hence feedforward inverse exists.



## Convolutional codes

- Let  $\mathbf{G}(\mathbf{D}) = [1 + D^2 + D^3 \quad 1 + D + D^2 + D^3]$ .
- $\text{GCD} \{1 + D^2 + D^3, 1 + D + D^2 + D^3\} = 1$ . Hence feedforward inverse exists.
- In this case,

$$\mathbf{G}^{-1}(\mathbf{D}) = \begin{pmatrix} 1 + D + D^2 \\ D + D^2 \end{pmatrix}$$



# Convolutional codes

- Let

$$\mathbf{G}(\mathbf{D}) = \begin{pmatrix} 1 + D & D & 1 + D \\ D & 1 & 1 \end{pmatrix}$$

# Convolutional codes

- Let

$$\mathbf{G}(\mathbf{D}) = \begin{pmatrix} 1 + D & D & 1 + D \\ D & 1 & 1 \end{pmatrix}$$

- $2 \times 2$  determinants are given by  $\{1 + D + D^2, 1 + D^2, 1\}$

## Convolutional codes

- Let

$$\mathbf{G}(\mathbf{D}) = \begin{pmatrix} 1+D & D & 1+D \\ D & 1 & 1 \end{pmatrix}$$

- $2 \times 2$  determinants are given by  $\{1+D+D^2, 1+D^2, 1\}$
- $\text{GCD} \{1+D+D^2, 1+D^2, 1\} = 1$



## Convolutional codes

- Let

$$\mathbf{G}(\mathbf{D}) = \begin{pmatrix} 1+D & D & 1+D \\ D & 1 & 1 \end{pmatrix}$$

- $2 \times 2$  determinants are given by  $\{1+D+D^2, 1+D^2, 1\}$
- $\text{GCD} \{1+D+D^2, 1+D^2, 1\} = 1$
- Hence, feedforward inverse exists and is given by

$$\mathbf{G}^{-1}(\mathbf{D}) = \begin{pmatrix} 0 & 0 \\ 1 & 1+D \\ 1 & D \end{pmatrix}$$



# Convolutional codes

- Catastrophic encoders do not have a feedforward inverse.

# Convolutional codes

- Catastrophic encoders do not have a feedforward inverse.
- Example. Consider a convolutional encoder with  $G(D) = [1 + D \quad 1 + D^2]$ .



# Convolutional codes

- Catastrophic encoders do not have a feedforward inverse.
- Example. Consider a convolutional encoder with  $G(D) = [1 + D \quad 1 + D^2]$ .
- $\text{GCD} \{1 + D, 1 + D^2\} = 1 + D$ .

# Convolutional codes

- Catastrophic encoders do not have a feedforward inverse.
- Example. Consider a convolutional encoder with  $G(D) = [1 + D \quad 1 + D^2]$ .
- $\text{GCD} \{1 + D, 1 + D^2\} = 1 + D$ .
- There doesn't exist any feedforward inverse.

## Convolutional codes

- Catastrophic encoders do not have a feedforward inverse.
- Example. Consider a convolutional encoder with  $G(D) = [1 + D \quad 1 + D^2]$ .
- $\text{GCD} \{1 + D, 1 + D^2\} = 1 + D$ .
- There doesn't exist any feedforward inverse.
- Let  $\mathbf{u}(D) = 1(1 + D) = 1 + D + D^2 + \dots$ , then

$$\mathbf{v}(D) = \mathbf{u}(D)\mathbf{G}(D) = 1/(1 + D)[1 + D \quad 1 + D^2] = [1 \quad 1 + D]$$

◀ ◻ ▶ ◀ ◻ ▶ ◀ ≡ ▶ ◀ ≡ ▶ ≡ ≡ ≡ ≡ ≡ ≡

## Convolutional codes

- Catastrophic encoders do not have a feedforward inverse.
- Example. Consider a convolutional encoder with  $G(D) = [1 + D \quad 1 + D^2]$ .
- $\text{GCD} \{1 + D, 1 + D^2\} = 1 + D$ .
- There doesn't exist any feedforward inverse.
- Let  $\mathbf{u}(D) = 1(1 + D) = 1 + D + D^2 + \dots$ , then

$$\mathbf{v}(D) = \mathbf{u}(D)\mathbf{G}(D) = 1/(1 + D)[1 + D \quad 1 + D^2] = [1 \quad 1 + D]$$

- This is a catastrophic encoder since infinite input weight sequence will result in finite weight output sequence.

◀ ◻ ▶ ◀ ◻ ▶ ◀ ≡ ▶ ◀ ≡ ▶ ≡ ≡ ≡ ≡ ≡ ≡

## Convolutional codes

- **Problem # 2:** If a class of rate  $1/2$  nonsystematic feedforward convolutional encoders with  $\mathbf{G}(\mathbf{D}) = [\mathbf{g}^0(\mathbf{D}) \quad \mathbf{g}^1(\mathbf{D})]$  satisfy

$$\mathbf{g}^0(\mathbf{D}) + D^\beta \mathbf{g}^1(\mathbf{D}) = D^\alpha$$

They are known as quick-look in (QLI) encoders. Show that QLI encoders are noncatastrophic encoders.



## Convolutional codes

- **Problem # 2:** If a class of rate  $1/2$  nonsystematic feedforward convolutional encoders with  $\mathbf{G}(\mathbf{D}) = [\mathbf{g}^0(\mathbf{D}) \quad \mathbf{g}^1(\mathbf{D})]$  satisfy

$$\mathbf{g}^0(\mathbf{D}) + D^\beta \mathbf{g}^1(\mathbf{D}) = D^\alpha$$

They are known as quick-look in (QLI) encoders. Show that QLI encoders are noncatastrophic encoders.

- **Solution:** QLI encoders have a simple feedforward inverse

$$\mathbf{G}^{-1}(\mathbf{D}) = \begin{pmatrix} 1 \\ D^\beta \end{pmatrix}$$

hence are noncatastrophic



# Convolutional codes

- Problem # 2:** If a class of rate  $1/2$  nonsystematic feedforward convolutional encoders with  $\mathbf{G}(\mathbf{D}) = [\mathbf{g}^0(\mathbf{D}) \quad \mathbf{g}^1(\mathbf{D})]$  satisfy

$$\mathbf{g}^0(\mathbf{D}) + D^\beta \mathbf{g}^1(\mathbf{D}) = D^\alpha$$

They are known as quick-look in (QLI) encoders. Show that QLI encoders are noncatastrophic encoders.

- **Solution:** QLI encoders have a simple feedforward inverse

$$\mathbf{G}^{-1}(\mathbf{D}) = \begin{pmatrix} 1 \\ D^\beta \end{pmatrix}$$

hence are noncatastrophic

- Further, the information sequence  $\mathbf{u}(\mathbf{D})$  can be recovered directly from  $\mathbf{v}(\mathbf{D}) = [\mathbf{v}^0(\mathbf{D}) \ \mathbf{v}^1(\mathbf{D})]$  using an encoder inverse with only two taps.

$$\mathbf{v}(\mathbf{D})\mathbf{G}^{-1}(\mathbf{D}) = \mathbf{v}^0(\mathbf{D}) + D^\beta \mathbf{v}^1(\mathbf{D}) = D^\alpha \mathbf{u}(\mathbf{D})$$



# Convolutional codes

- Problem # 3:** An important distance measure for convolutional codes is the column distance function. Let

$$[\mathbf{v}]_l = (v_0^{(0)} v_0^{(1)} \cdots v_1^{(n-1)}, v_1^{(0)} v_1^{(1)} \cdots v_1^{(n-1)}, \dots, v_l^{(0)} v_l^{(1)} \cdots v_l^{(n-1)})$$

denote the  $l$ -th truncation of the codeword  $\mathbf{v}$  and let

$$[\mathbf{u}]_I = (u_0^{(0)} u_0^{(1)} \cdots u_1^{(n-1)}, u_1^{(0)} u_1^{(1)} \cdots u_1^{(n-1)}, \dots, u_l^{(0)} u_l^{(1)} \cdots u_l^{(n-1)})$$

denote the  $l$ th truncation of the information sequence  $\mathbf{u}$ . The column distance function of order  $l$ ,  $d_l$  is defined as

$$\begin{aligned} d_I &= \min_{[\mathbf{u}']_I, [\mathbf{u}'']_I} \{d([\mathbf{v}']_I, [\mathbf{v}'']_I) : [\mathbf{u}']_0 \neq [\mathbf{u}'']_0\} \\ &= \min_{[\mathbf{u}]_I} \{w[\mathbf{v}]_I : [\mathbf{u}]_0 \neq 0\} \end{aligned}$$

where  $\mathbf{v}$  is the codeword corresponding to the information sequence  $\mathbf{u}$ . Prove that for noncatastrophic encoders

$$\lim_{l \rightarrow \infty} d_l = d_{\text{free}}$$



## Convolutional codes

- **Solution:** By definition,  $d_{\text{free}}$  is the minimum weight path that has diverged from and remerged with the all-zero state.



## Convolutional codes

- **Solution:** By definition,  $d_{\text{free}}$  is the minimum weight path that has diverged from and remerged with the all-zero state.
- Assume that  $[\mathbf{v}]_j$  represents the shortest remerged path through the state diagram with weight  $d_{\text{free}}$ .



## Convolutional codes

- **Solution:** By definition,  $d_{\text{free}}$  is the minimum weight path that has diverged from and remerged with the all-zero state.
- Assume that  $[\mathbf{v}]_j$  represents the shortest remerged path through the state diagram with weight  $d_{\text{free}}$ .
- Let  $[d_l]_{\text{re}}$  be the minimum weight of all remerged paths of length  $l$ , it follows that  $[d_l]_{\text{re}} = d_{\text{free}}$  for all  $l \geq j$ .



## Convolutional codes

- **Solution:** By definition,  $d_{\text{free}}$  is the minimum weight path that has diverged from and remerged with the all-zero state.
- Assume that  $[\mathbf{v}]_j$  represents the shortest remerged path through the state diagram with weight  $d_{\text{free}}$ .
- Let  $[d_l]_{\text{re}}$  be the minimum weight of all remerged paths of length  $l$ , it follows that  $[d_l]_{\text{re}} = d_{\text{free}}$  for all  $l \geq j$ .
- Also, for a noncatastrophic encoder, any path that remains unmerged must accumulate weight.



