

An introduction to coding theory

Adrish Banerjee

Department of Electrical Engineering
Indian Institute of Technology Kanpur
Kanpur, Uttar Pradesh
India

Mar. 13, 2017



Lecture #17: Distance Properties of turbo codes



Outline of the lecture

- Introduction



Outline of the lecture

- Introduction
- Weight distribution of turbo codes



Outline of the lecture

- Introduction
- Weight distribution of turbo codes
- Spectral thinning



Outline of the lecture

- Introduction
- Weight distribution of turbo codes
- Spectral thinning
- Distance properties of turbo codes



Introduction

- Turbo codes give very good performance at moderate BERs. This is due to random-like weight distribution of the codewords produced by the pseudorandom interleaver when systematic feedback encoders are used as constituent encoders.

Introduction

- Turbo codes give very good performance at moderate BERs. This is due to random-like weight distribution of the codewords produced by the pseudorandom interleaver when systematic feedback encoders are used as constituent encoders.
- Let us consider some examples to understand this feature.

Introduction

- Turbo codes give very good performance at moderate BERs. This is due to random-like weight distribution of the codewords produced by the pseudorandom interleaver when systematic feedback encoders are used as constituent encoders.
- Let us consider some examples to understand this feature.
- Consider the conventional (2,1,4) convolutional code with generation matrix

$$G_{ff}(D) = [D^4 + D^3 + D^2 + D^1 \quad D^4 + 1]$$



Introduction

- Turbo codes give very good performance at moderate BERs. This is due to random-like weight distribution of the codewords produced by the pseudorandom interleaver when systematic feedback encoders are used as constituent encoders.
- Let us consider some examples to understand this feature.
- Consider the conventional (2,1,4) convolutional code with generation matrix

$$G_{ff}(D) = [D^4 + D^3 + D^2 + D^1 \quad D^4 + 1]$$

- This code has $d_{free} = 6$, obtained from the information sequence $u(D) = 1 + D$.



Introduction

- Turbo codes give very good performance at moderate BERs. This is due to random-like weight distribution of the codewords produced by the pseudorandom interleaver when systematic feedback encoders are used as constituent encoders.
- Let us consider some examples to understand this feature.
- Consider the conventional (2,1,4) convolutional code with generation matrix

$$G_{ff}(D) = \begin{bmatrix} D^4 + D^3 + D^2 + D^1 & D^4 + 1 \end{bmatrix}$$

- This code has $d_{free} = 6$, obtained from the information sequence $u(D) = 1 + D$.
- Now consider the equivalent (2,1,4) systematic recursive convolutional code (SRCC) with generator matrix

$$G_{fb}(D) = \left[1 \quad \frac{D^4 + 1}{D^4 + D^3 + D^2 + D + 1} \right]$$

◀ ◻ ▶ ◀ ◻ ◻ ▶ ◀ ≡ ≡ ≡ ▶ ◀ ≡ ≡ ≡ ▶ ≡ ≡ ≡ ↺ 🔍 ↻

Adrish Banerjee

Department of Electrical Engineering Indian Institute of Technology Kanpur Kanpur, Uttar Pradesh India

An introduction to coding theory

Introduction

- In this case, the (minimum) weight 6 codeword is produced by the information sequence $u(D) = 1 + D^5$.

◀ ◻ ▶ ◀ ◻ ▶ ◀ ≡ ▶ ◀ ≡ ▶ ≡

Adrish Banerjee

Department of Electrical Engineering Indian Institute of Technology Kanpur Kanpur, Uttar Pradesh India

An introduction to coding theory

Introduction

- In this case, the (minimum) weight 6 codeword is produced by the information sequence $u(D) = 1 + D^5$.
- These two encoders have the same set of codewords, but a different mapping between information sequence and codeword.

Introduction

- In this case, the (minimum) weight 6 codeword is produced by the information sequence $u(D) = 1 + D^5$.
- These two encoders have the same set of codewords, but a different mapping between information sequence and codeword.
- Now consider termination the codes by appending four bits to an information block of length $N - 4$ to return the encoder to all zero state.

Introduction

- In this case, the (minimum) weight 6 codeword is produced by the information sequence $u(D) = 1 + D^5$.
- These two encoders have the same set of codewords, but a different mapping between information sequence and codeword.
- Now consider termination the codes by appending four bits to an information block of length $N - 4$ to return the encoder to all zero state.
- This result in s $(2N, N - 4)$ block code with rate

$$R = \frac{N - 4}{2N} \approx \frac{1}{2} \quad (\text{large } N)$$



Introduction

- In this case, the (minimum) weight 6 codeword is produced by the information sequence $u(D) = 1 + D^5$.
- These two encoders have the same set of codewords, but a different mapping between information sequence and codeword.
- Now consider termination the codes by appending four bits to an information block of length $N - 4$ to return the encoder to all zero state.
- This result in s $(2N, N - 4)$ block code with rate

$$R = \frac{N - 4}{2N} \approx \frac{1}{2} \quad (\text{large } N)$$

- The termination bits differ in the two cases.



Introduction

Weight	Multiplicity	Weight	Multiplicity
0	1	17	520
1	0	18	491
2	0	19	346
3	0	20	212
4	0	21	132
5	0	22	68
6	11	23	38
7	12	24	11
8	23	25	2
9	38	26	0
10	61	27	0
11	126	28	0
12	200	29	0
13	332	30	0
14	425	31	0
15	502	32	0
16	545	-	-

Table: Weight spectra of (32,12) terminated convolutional code

Introduction

- The weight spectrum of the terminated convolutional code is dense at the low weight.

Introduction

- The weight spectrum of the terminated convolutional code is dense at the low weight.
- If a convolutional code has A_d codewords of weight d caused by a set of information sequences $\{u(D)\}$ starting at time 0, it also has A_d codewords of weight d caused by the set of information sequence $\{Du(D)\}$ starting at time 1, A_d codewords of weight d caused by the set $\{D^2u(D)\}$ starting at time 2, and so on.



Introduction

- The weight spectrum of the terminated convolutional code is dense at the low weight.
- If a convolutional code has A_d codewords of weight d caused by a set of information sequences $\{u(D)\}$ starting at time 0, it also has A_d codewords of weight d caused by the set of information sequence $\{Du(D)\}$ starting at time 1, A_d codewords of weight d caused by the set $\{D^2u(D)\}$ starting at time 2, and so on.
- This time invariant property of convolutional encoder accounts for the relatively large number of low weight codewords.



Weight Distribution of Turbo Codes

- Consider Now consider the (2,1,4) systematic recursive convolutional code (SRCC) with generator matrix

$$G_{fb}(D) = \begin{bmatrix} 1 & \frac{D^4 + 1}{D^4 + D^3 + D^2 + D + 1} \end{bmatrix}$$

◀ ◻ ▶ ◀ ◻ ▶ ◀ ≡ ▶ ◀ ≡ ▶ ≡ ≡ ≡ ≡ ≡ ≡ ≡ ≡

Weight Distribution of Turbo Codes

- Consider Now consider the (2,1,4) systematic recursive convolutional code (SRCC) with generator matrix

$$G_{fb}(D) = \begin{bmatrix} 1 & \frac{D^4 + 1}{D^4 + D^3 + D^2 + D + 1} \end{bmatrix}$$

- Now consider the (32, 12) block code that result from the parallel concatenation of two of the above SRCC's along with pseudorandom interleaving and after rate puncturing of parity bit.

◀ ◻ ▶ ◀ ◻ ▶ ◀ ≡ ▶ ◀ ≡ ▶ ≡ ≡ ≡ ≡ ≡ ≡ ≡ ≡

Weight Distribution of Turbo Codes

- The interleaved information sequence is fed to the second constituent encoder that produces a new set of parity sequences.



Weight Distribution of Turbo Codes

- The interleaved information sequence is fed to the second constituent encoder that produces a new set of parity sequences.
- Overall rate of this code is $R = 1/3$. To make it a $R = 1/2$ code, we need to puncture every other parity sequence.



Weight Distribution of Turbo Codes

- The interleaved information sequence is fed to the second constituent encoder that produces a new set of parity sequences.
- Overall rate of this code is $R = 1/3$. To make it a $R = 1/2$ code, we need to puncture every other parity sequence.
- The puncturing matrix is given by

$$P = \begin{bmatrix} 0 & 1 \\ 1 & 0 \end{bmatrix}$$

◀ ◻ ▶ ◀ ◻ ▶ ◀ ≡ ▶ ◀ ≡ ▶ ≡ ≡ ≡ ≡ ≡ ≡

Adrish Banerjee

Department of Electrical Engineering Indian Institute of Technology Kanpur Kanpur, Uttar Pradesh India

An introduction to coding theory

Weight Distribution of Turbo Codes

Weight	Multiplicity	Weight	Multiplicity
0	1	17	558
1	0	18	478
2	0	19	352
3	0	20	222
4	0	21	123
5	1	22	64
6	4	23	24
7	8	24	4
8	16	25	4
9	30	26	1
10	73	27	0
11	144	28	0
12	210	29	0
13	308	30	0
14	404	31	0
15	496	32	0
16	571	-	-

Table: Weight spectra of (32,12) parallel concatenated code

◀ ◻ ▶ ◀ ◻ ▶ ◀ ≡ ▶ ◀ ≡ ▶ ≡ ≡ ≡ ≡ ≡ ≡

Adrish Banerjee

Department of Electrical Engineering Indian Institute of Technology Kanpur Kanpur, Uttar Pradesh India

An introduction to coding theory

Spectral Thinning

- The parallel concatenated code (turbo) has the spectrum which is not as dense as the terminated convolutional code.

Spectral Thinning

- The parallel concatenated code (turbo) has the spectrum which is not as dense as the terminated convolutional code.
- This effect of parallel concatenation is called spectral thinning.

Spectral Thinning

- The parallel concatenated code (turbo) has the spectrum which is not as dense as the terminated convolutional code.
- This effect of parallel concatenation is called spectral thinning.
- The interleaves causes most of the low weight parity sequence from first constituent encoder to be able to match with the high weight parity sequence from second constituent encoder.

Spectral Thinning

- The parallel concatenated code (turbo) has the spectrum which is not as dense as the terminated convolutional code.
- This effect of parallel concatenation is called spectral thinning.
- The interleaves causes most of the low weight parity sequence from first constituent encoder to be able to match with the high weight parity sequence from second constituent encoder.
- Effect of spectral thinning is more pronounced for large interleaver sizes.

Spectral Thinning

- The parallel concatenated code (turbo) has the spectrum which is not as dense as the terminated convolutional code.
- This effect of parallel concatenation is called spectral thinning.
- The interleaves causes most of the low weight parity sequence from first constituent encoder to be able to match with the high weight parity sequence from second constituent encoder.
- Effect of spectral thinning is more pronounced for large interleaver sizes.
- Different interleavers and puncturing matrices would give different weight spectra, but the above result are typical.

Spectral Thinning

- Spectral thinning has little effect on the minimum distances, but it greatly reduces the multiplicities of low weight codewords.

Spectral Thinning

- Spectral thinning has little effect on the minimum distances, but it greatly reduces the multiplicities of low weight codewords.
- As the block length (interleaves size) increases, the weight spectrum of PCCC's begin to approximate a random like distribution i.e., the distribution that would result if each bit in every codeword were selected randomly from an i.i.d. probability distribution.

Spectral Thinning

- Spectral thinning has little effect on the minimum distances, but it greatly reduces the multiplicities of low weight codewords.
- As the block length (interleaves size) increases, the weight spectrum of PCCC's begin to approximate a random like distribution i.e., the distribution that would result if each bit in every codeword were selected randomly from an i.i.d. probability distribution.
- There is only a minor spectral thinning effect if non-recursive feedforward encoder are used, due to the fact that they are FIR rather than IIR filter.

Spectral Thinning

- Spectral thinning has little effect on the minimum distances, but it greatly reduces the multiplicities of low weight codewords.
- As the block length (interleaves size) increases, the weight spectrum of PCCC's begin to approximate a random like distribution i.e., the distribution that would result if each bit in every codeword were selected randomly from an i.i.d. probability distribution.
- There is only a minor spectral thinning effect if non-recursive feedforward encoder are used, due to the fact that they are FIR rather than IIR filter.
- One can explain the superiority of feedback encoders in parallel concatenation as a consequence of the fact that they are IIR, rather than FIR filters, i.e., their response to single input 1s is not localized to the constraint length of the code but extends over the entire block length.



Spectral Thinning

- Spectral thinning has little effect on the minimum distances, but it greatly reduces the multiplicities of low weight codewords.
- As the block length (interleaves size) increases, the weight spectrum of PCCC's begin to approximate a random like distribution i.e., the distribution that would result if each bit in every codeword were selected randomly from an i.i.d. probability distribution.
- There is only a minor spectral thinning effect if non-recursive feedforward encoder are used, due to the fact that they are FIR rather than IIR filter.
- One can explain the superiority of feedback encoders in parallel concatenation as a consequence of the fact that they are IIR, rather than FIR filters, i.e., their response to single input 1s is not localized to the constraint length of the code but extends over the entire block length.
- This property of feedback encoders is exploited by a pseudorandom interleaver to produce the spectral thinning effect.



Distance properties of turbo code

- The exact weight spectrum of a turbo code depends on the particular interleaver chosen.

Distance properties of turbo code

- The exact weight spectrum of a turbo code depends on the particular interleaver chosen.
- A uniform interleaver of length N is a probabilistic device which maps a given input block of weight w into all its distinct $\binom{N}{w}$ permutations with equal probability $\frac{1}{\binom{N}{w}}$.

Distance properties of turbo code

- The exact weight spectrum of a turbo code depends on the particular interleaver chosen.
- A uniform interleaver of length N is a probabilistic device which maps a given input block of weight w into all its distinct $\binom{N}{w}$ permutations with equal probability $\frac{1}{\binom{N}{w}}$.
- Using the concept of a uniform interleaver allows us to calculate the average weight spectrum of a PCC over all possible interleavers.



Distance properties of turbo code

- Let us consider a parallel concatenated block code (PCBC) with systematic $(7, 4, 3)$ Hamming code as a constituent code.



Distance properties of turbo code

- Let us consider a parallel concatenated block code (PCBC) with systematic (7, 4, 3) Hamming code as a constituent code.
- The weight enumerating function (WEF) of this code is given by

$$A(X) = \sum_d A_d X^d = 7X^3 + 7X^4 + X^7$$

◀ ◻ ▶ ◀ ◻ ▶ ◀ ≡ ▶ ◀ ≡ ▶ ≡ ≡ ≡ ≡ ≡ ≡

Distance properties of turbo code

- Let us consider a parallel concatenated block code (PCBC) with systematic (7, 4, 3) Hamming code as a constituent code.
- The weight enumerating function (WEF) of this code is given by

$$A(X) = \sum_d A_d X^d = 7X^3 + 7X^4 + X^7$$

- The input redundancy weight enumerating function (IRWEF) of this systematic code is given by

$$A(W, Z) = W(3Z^2 + Z^3) + W^2(3Z + 3Z^2) + W^3(1 + 3Z) + W^4 Z^3.$$

◀ ◻ ▶ ◀ ◻ ▶ ◀ ≡ ▶ ◀ ≡ ▶ ≡ ≡ ≡ ≡ ≡ ≡

Distance properties of turbo code

- Let us consider a parallel concatenated block code (PCBC) with systematic (7, 4, 3) Hamming code as a constituent code.
- The weight enumerating function (WEF) of this code is given by

$$A(X) = \sum_d A_d X^d = 7X^3 + 7X^4 + X^7$$

- The input redundancy weight enumerating function (IRWEF) of this systematic code is given by

$$A(W, Z) = W(3Z^2 + Z^3) + W^2(3Z + 3Z^2) + W^3(1 + 3Z) + W^4Z^3.$$

- The Conditional WEF (CWEF) for each input weight is given by

$$A_1(Z) = 3Z^2 + Z^3,$$

$$A_2(Z) = 3Z + 3Z^2,$$

$$A_3(Z) = 1 + 3Z,$$

$$A_4(Z) = Z^3.$$



Distance properties of turbo code

- Now consider a PCBC with two systematic (n,k) constituent codes C_1 and C_2 with CWEF's $A_w^{C_1}(Z)$ and $A_w^{C_2}(Z)$ separated by a uniform interleaves of size $N = k$.



Distance properties of turbo code

- Now consider a PCBC with two systematic (n,k) constituent codes C_1 and C_2 with CWEF's $A_w^{C_1}(Z)$ and $A_w^{C_2}(Z)$ separated by a uniform interleaves of size $N = k$.
- The average CWEF of the PCBC is given by

$$A_w^{PC}(Z) = \frac{A_w^{C_1}(Z)A_w^{C_2}(Z)}{\binom{N}{w}}.$$



Distance properties of turbo code

- Now consider a PCBC with two systematic (n,k) constituent codes C_1 and C_2 with CWEF's $A_w^{C_1}(Z)$ and $A_w^{C_2}(Z)$ separated by a uniform interleaves of size $N = k$.
- The average CWEF of the PCBC is given by

$$A_w^{PC}(Z) = \frac{A_w^{C_1}(Z)A_w^{C_2}(Z)}{\binom{N}{w}}.$$

- The average IRWEF is given by

$$A_w^{PC}(W, Z) = \sum_{(1 \leq w \leq N)} W^w A_w^{PC}(Z)$$



Distance properties of turbo code

- Now consider a PCBC with two systematic (n,k) constituent codes C_1 and C_2 with CWEF's $A_w^{C_1}(Z)$ and $A_w^{C_2}(Z)$ separated by a uniform interleaves of size $N = k$.

- The average CWEF of the PCBC is given by

$$A_w^{PC}(Z) = \frac{A_w^{C_1}(Z)A_w^{C_2}(Z)}{\binom{N}{w}}.$$

- The average IRWEF is given by

$$A_w^{PC}(W, Z) = \sum_{(1 \leq w \leq N)} W^w A_w^{PC}(Z)$$

- The average bit CWEF is

$$B_w^{PC}(Z) = \frac{w}{N} A_w^{PC}(Z)$$



Distance properties of turbo code

- The average bit IRWEF is

$$B^{PC}(W, Z) = \sum_{(1 \leq w \leq N)} W^w B_w^{PC}(Z)$$



Distance properties of turbo code

- The average bit IRWEF is

$$B^{PC}(W, Z) = \sum_{(1 \leq w \leq N)} W^w B_w^{PC}(Z)$$

- The average codeword WEF is

$$A_w^{PC}(X) = \sum_{d_{min} \leq d} A_d X^d = \sum_{1 \leq w \leq N} W^w A_w^{PC}(Z)|_{W=Z=X}$$



Distance properties of turbo code

- The average bit IRWEF is

$$B^{PC}(W, Z) = \sum_{(1 \leq w \leq N)} W^w B_w^{PC}(Z)$$

- The average codeword WEF is

$$A_w^{PC}(X) = \sum_{d_{min} \leq d} A_d X^d = \sum_{1 \leq w \leq N} W^w A_w^{PC}(Z)|_{W=Z=X}$$

- The average bit WEF is

$$B_w^{PC}(X) = \sum_{d_{min} \leq d} B_d X^d = \sum_{1 \leq w \leq N} W^w B_w^{PC}(Z)|_{W=Z=X}$$



Distance properties of turbo code

- For the (10, 4) PCBC with identical (7,4,3) Hamming constituent codes

$$A_1^{PC}(Z) = \frac{(3Z^2 + Z^3)^2}{\binom{4}{1}} = 2.23Z^4 + 1.5Z^5 + 0.25Z^6$$

$$A_2^{PC}(Z) = \frac{(3Z + 3Z^2)^2}{\binom{4}{2}} = 1.5Z^2 + 3Z^3 + 1.5Z^4$$

$$A_3^{PC}(Z) = \frac{(1 + 3Z)^2}{\binom{4}{3}} = 0.25 + 1.5Z + 2.25Z^2$$

$$A_4^{PC}(Z) = \frac{(Z^3)^2}{\binom{4}{4}} = Z^6$$

Navigation icons: back, forward, search, etc.

Distance properties of turbo code

- Similarly, the IRWEF's are given by

$$A^{PC}(W, Z) = W(2.25Z^4 + 1.5Z^5 + 0.25Z^6) + W^2(1.5Z^2 + 3Z^3 + 1.5Z^4) \\ + W^3(0.25 + 1.5Z + 2.25Z^2) + W^4Z^6$$

$$B^{PC}(W, Z) = W(0.56Z^4 + 0.37Z^5 + 0.06Z^6) + W^2(0.75Z^2 + 1.5Z^3 + 0.75Z^4) \\ + W^3(0.19 + 1.12Z + 1.69Z^2) + W^4Z^6$$

Navigation icons: back, forward, search, etc.

Distance properties of turbo code

- Similarly, the IRWEF's are given by

$$\begin{aligned} A^{PC}(W, Z) &= W(2.25Z^4 + 1.5Z^5 + 0.25Z^6) + W^2(1.5Z^2 + 3Z^3 + 1.5Z^4) \\ &\quad + W^3(0.25 + 1.5Z + 2.25Z^2) + W^4Z^6 \\ B^{PC}(W, Z) &= W(0.56Z^4 + 0.37Z^5 + 0.06Z^6) + W^2(0.75Z^2 + 1.5Z^3 + 0.75Z^4) \\ &\quad + W^3(0.19 + 1.12 + 1.69Z^2) + W^4Z^6 \end{aligned}$$

- Also, WEF's are given by

$$\begin{aligned} A^{PC}(X) &= 0.25X^3 + 3X^4 + 7.5X^5 + 3X^6 + 0.25X^7 + X^{10} \\ B^{PC}(X) &= 0.19X^3 + 1.87X^4 + 3.75X^5 + 1.12X^6 + 0.06X^7 + X^{10} \end{aligned}$$



Distance properties of turbo code

- The coefficients of the codeword WEF's for the PCBC are fractional due to averaging effect over all interleavers.



Distance properties of turbo code

- The coefficients of the codeword WEF's for the PCBC are fractional due to averaging effect over all interleavers.
- Sum of all the coefficients in $A^{PC}(X)$ is equal to total number of nonzero codewords in PCBC (15).



Distance properties of turbo code

- The coefficients of the codeword WEF's for the PCBC are fractional due to averaging effect over all interleavers.
- Sum of all the coefficients in $A^{PC}(X)$ is equal to total number of nonzero codewords in PCBC (15).
- The average codeword multiplicities of the low-weight codewords are given by $A_3 = 0.25$ and $A_4 = 3.0$.



Distance properties of turbo code

- The coefficients of the codeword WEF's for the PCBC are fractional due to averaging effect over all interleavers.
- Sum of all the coefficients in $A^{PC}(X)$ is equal to total number of nonzero codewords in PCBC (15).
- The average codeword multiplicities of the low-weight codewords are given by $A_3 = 0.25$ and $A_4 = 3.0$.
- The average bit multiplicities of the low-weight codewords are given by $B_3 = 0.19$ and $B_4 = 1.87$.