

An introduction to coding theory

Adrish Banerjee

Department of Electrical Engineering
Indian Institute of Technology Kanpur
Kanpur, Uttar Pradesh
India

Jan. 23, 2017



Lecture #3B: Problem solving session-I



Linear block code

- **Problem # 1:** Consider a linear block code, C with parity check matrix given by

$$\mathbf{H} = \begin{bmatrix} 1 & 0 & 0 & 1 & 0 & 1 & 1 \\ 0 & 1 & 0 & 1 & 1 & 1 & 0 \\ 0 & 0 & 1 & 0 & 1 & 1 & 1 \\ 1 & 1 & 1 & 0 & 0 & 1 & 0 \end{bmatrix}$$

What is (n, k) of C ?



Linear block code

- **Problem # 1:** Consider a linear block code, C with parity check matrix given by

$$\mathbf{H} = \begin{bmatrix} 1 & 0 & 0 & 1 & 0 & 1 & 1 \\ 0 & 1 & 0 & 1 & 1 & 1 & 0 \\ 0 & 0 & 1 & 0 & 1 & 1 & 1 \\ 1 & 1 & 1 & 0 & 0 & 1 & 0 \end{bmatrix}$$

What is (n, k) of C ?

- **Solutions:** Rank of \mathbf{H} matrix is 3. So, $n = 7$, $k = 7 - 3 = 4$.



Linear block code

- **Problem # 2:** Consider the following binary block code, C ,

$$C = \{000000, 110011, 011101, 111111\}$$

Is C a linear block code? Justify your answer.



Linear block code

- **Problem # 2:** Consider the following binary block code, C ,

$$C = \{000000, 110011, 011101, 111111\}$$

Is C a linear block code? Justify your answer.

- **Solutions:** No.



Linear block code

- **Problem # 2:** Consider the following binary block code, C ,

$$C = \{000000, 110011, 011101, 111111\}$$

Is C a linear block code? Justify your answer.

- **Solutions:** No.
- Sum of two codewords for a linear block code is a valid codeword.



Linear block code

- **Problem # 2:** Consider the following binary block code, C ,

$$C = \{000000, 110011, 011101, 111111\}$$

Is C a linear block code? Justify your answer.

- **Solutions:** No.
- Sum of two codewords for a linear block code is a valid codeword.
- Let $v_0 = 000000$, $v_1 = 110011$, $v_2 = 011101$, and $v_3 = 111111$, then $v_1 + v_2$, $v_1 + v_3$, $v_2 + v_3$, and $v_1 + v_2 + v_3$ must also be a valid codeword.

$$v_1 + v_2 = 101110$$

$$v_1 + v_3 = 001100$$

$$v_2 + v_3 = 100010$$

$$v_1 + v_2 + v_3 = 010001$$



Problem # 2 (contd.)

- Thus a linear block code should have the following codewords

$$C = \{000000, 110011, 011101, 111111, 101110, 001100, 100010, 010001\}$$



Problem # 2 (contd.)

- Thus a linear block code should have the following codewords

$$C = \{000000, 110011, 011101, 111111, 101110, 001100, 100010, 010001\}$$

- This is a (6,3) linear binary code.



Problem # 2 (contd.): Generator matrix in systematic form

- How to write the generator matrix in systematic form?

$$\mathbf{G} = \begin{bmatrix} 1 & 1 & 0 & 0 & 1 & 1 \\ 0 & 1 & 1 & 1 & 0 & 1 \\ 1 & 1 & 1 & 1 & 1 & 1 \end{bmatrix}$$

- Row 3 \rightarrow Row 3 + Row 1

$$\mathbf{G} = \begin{bmatrix} 1 & 1 & 0 & 0 & 1 & 1 \\ 0 & 1 & 1 & 1 & 0 & 1 \\ 0 & 0 & 1 & 1 & 0 & 0 \end{bmatrix}$$



Problem # 2 (contd.): Generator matrix in systematic form

- How to write the generator matrix in systematic form?

$$\mathbf{G} = \begin{bmatrix} 1 & 1 & 0 & 0 & 1 & 1 \\ 0 & 1 & 1 & 1 & 0 & 1 \\ 1 & 1 & 1 & 1 & 1 & 1 \end{bmatrix}$$

- Row 3 \rightarrow Row 3 + Row 1

$$\mathbf{G} = \begin{bmatrix} 1 & 1 & 0 & 0 & 1 & 1 \\ 0 & 1 & 1 & 1 & 0 & 1 \\ 0 & 0 & 1 & 1 & 0 & 0 \end{bmatrix}$$

- Row 2 \rightarrow Row 3 + Row 2

$$\mathbf{G} = \begin{bmatrix} 1 & 1 & 0 & 0 & 1 & 1 \\ 0 & 1 & 0 & 0 & 0 & 1 \\ 0 & 0 & 1 & 1 & 0 & 0 \end{bmatrix}$$



Problem # 2 (contd.): Generator matrix in systematic form

- Row 1 \rightarrow Row 1 + Row 2

$$\mathbf{G} = \begin{bmatrix} 1 & 0 & 0 & 0 & 1 & 0 \\ 0 & 1 & 0 & 0 & 0 & 1 \\ 0 & 0 & 1 & 1 & 0 & 0 \end{bmatrix}$$



Problem # 2 (contd.): Generator matrix in systematic form

- Row 1 \rightarrow Row 1 + Row 2

$$\mathbf{G} = \begin{bmatrix} 1 & 0 & 0 & 0 & 1 & 0 \\ 0 & 1 & 0 & 0 & 0 & 1 \\ 0 & 0 & 1 & 1 & 0 & 0 \end{bmatrix}$$

- Similarly parity check matrix in systematic form can be written as

$$\mathbf{H} = \begin{bmatrix} 0 & 0 & 1 & 1 & 0 & 0 \\ 1 & 0 & 0 & 0 & 1 & 0 \\ 0 & 1 & 0 & 0 & 0 & 1 \end{bmatrix}$$



Linear block code

- **Problem # 3:** Let \mathbf{H} be the parity check matrix of an (n,k) linear code C that has both odd and even-weight codewords. Construct a new linear code C_1 with the following parity-check matrix

$$\mathbf{H}_1 = \left[\begin{array}{c|c} \begin{matrix} 0 \\ 0 \\ \vdots \\ 0 \\ \dots \\ 1 \end{matrix} & \begin{matrix} \mathbf{H} \\ \dots \\ 11\dots 1 \end{matrix} \end{array} \right]$$



Linear block code

- **Problem # 3:** Let \mathbf{H} be the parity check matrix of an (n,k) linear code C that has both odd and even-weight codewords. Construct a new linear code C_1 with the following parity-check matrix

$$\mathbf{H}_1 = \left[\begin{array}{c|c} \begin{matrix} 0 \\ 0 \\ \vdots \\ 0 \\ \dots \\ 1 \end{matrix} & \begin{matrix} \mathbf{H} \\ \dots \\ 11\dots 1 \end{matrix} \end{array} \right]$$

- 1 Show that C_1 is an $(n+1, k)$ linear code.



Linear block code

- Problem # 3:** Let \mathbf{H} be the parity check matrix of an (n,k) linear code C that has both odd and even-weight codewords. Construct a new linear code C_1 with the following parity-check matrix

$$\mathbf{H}_1 = \left[\begin{array}{c|c} 0 & \\ 0 & \\ \vdots & \mathbf{H} \\ 0 & \\ \dots & \dots \\ 1 & 11\dots 1 \end{array} \right]$$

- ➊ Show that C_1 is an $(n+1, k)$ linear code.
- ➋ Show that every codeword of C_1 has even weight.

Linear block code

- Problem # 3:** Let \mathbf{H} be the parity check matrix of an (n,k) linear code C that has both odd and even-weight codewords. Construct a new linear code C_1 with the following parity-check matrix

$$\mathbf{H}_1 = \left[\begin{array}{c|c} 0 & \\ 0 & \\ \vdots & \mathbf{H} \\ 0 & \\ \dots & \dots \\ 1 & 11\dots 1 \end{array} \right]$$

- ➊ Show that C_1 is an $(n + 1, k)$ linear code.
- ➋ Show that every codeword of C_1 has even weight.
- ➌ Show that C_1 can be obtained from C by adding an extra parity check digit, denoted by v_∞ to the left of each codeword \mathbf{v} as follows

Linear block code

- **Problem # 3:** Let \mathbf{H} be the parity check matrix of an (n,k) linear code C that has both odd and even-weight codewords. Construct a new linear code C_1 with the following parity-check matrix

$$\mathbf{H}_1 = \left[\begin{array}{c|c} \begin{matrix} 0 \\ 0 \\ \vdots \\ 0 \\ \dots \\ 1 \end{matrix} & \begin{matrix} \mathbf{H} \\ \dots \\ 11\dots 1 \end{matrix} \end{array} \right]$$

- 1 Show that C_1 is an $(n+1, k)$ linear code.
- 2 Show that every codeword of C_1 has even weight.
- 3 Show that C_1 can be obtained from C by adding an extra parity check digit, denoted by v_∞ to the left of each codeword \mathbf{v} as follows
 - 1) if \mathbf{v} has odd weight, then $v_\infty = 1$, and



Linear block code

- **Problem # 3:** Let \mathbf{H} be the parity check matrix of an (n,k) linear code C that has both odd and even-weight codewords. Construct a new linear code C_1 with the following parity-check matrix

$$\mathbf{H}_1 = \left[\begin{array}{c|c} \begin{matrix} 0 \\ 0 \\ \vdots \\ 0 \\ \dots \\ 1 \end{matrix} & \begin{matrix} \mathbf{H} \\ \dots \\ 11\dots 1 \end{matrix} \end{array} \right]$$

- 1 Show that C_1 is an $(n+1, k)$ linear code.
- 2 Show that every codeword of C_1 has even weight.
- 3 Show that C_1 can be obtained from C by adding an extra parity check digit, denoted by v_∞ to the left of each codeword \mathbf{v} as follows
 - 1) if \mathbf{v} has odd weight, then $v_\infty = 1$, and
 - 2) if \mathbf{v} has even weight, then $v_\infty = 0$



Problem # 3 (contd.)

- The matrix \mathbf{H}_1 is an $(n - k + 1) \times (n + 1)$ matrix.

Problem # 3 (contd.)

- The matrix \mathbf{H}_1 is an $(n - k + 1) \times (n + 1)$ matrix.
- First we note that the $n - k$ rows of \mathbf{H} are linearly independent. It is clear that the first $(n - k)$ rows of \mathbf{H}_1 are also linearly independent.

Problem # 3 (contd.)

- The matrix \mathbf{H}_1 is an $(n - k + 1) \times (n + 1)$ matrix.
- First we note that the $n - k$ rows of \mathbf{H} are linearly independent. It is clear that the first $(n - k)$ rows of \mathbf{H}_1 are also linearly independent.
- The last row of \mathbf{H}_1 has a “1” at its first position but other rows of \mathbf{H}_1 have a “0” at their first position. Any linear combination including the last row of \mathbf{H}_1 will never yield a zero vector.



Problem # 3 (contd.)

- The matrix \mathbf{H}_1 is an $(n - k + 1) \times (n + 1)$ matrix.
- First we note that the $n - k$ rows of \mathbf{H} are linearly independent. It is clear that the first $(n - k)$ rows of \mathbf{H}_1 are also linearly independent.
- The last row of \mathbf{H}_1 has a “1” at its first position but other rows of \mathbf{H}_1 have a “0” at their first position. Any linear combination including the last row of \mathbf{H}_1 will never yield a zero vector.
- Thus all the rows of \mathbf{H}_1 are linearly independent. Hence the row space of \mathbf{H}_1 has dimension $n - k + 1$.



Problem # 3 (contd.)

- The matrix \mathbf{H}_1 is an $(n - k + 1) \times (n + 1)$ matrix.
- First we note that the $n - k$ rows of \mathbf{H} are linearly independent. It is clear that the first $(n - k)$ rows of \mathbf{H}_1 are also linearly independent.
- The last row of \mathbf{H}_1 has a “1” at its first position but other rows of \mathbf{H}_1 have a “0” at their first position. Any linear combination including the last row of \mathbf{H}_1 will never yield a zero vector.
- Thus all the rows of \mathbf{H}_1 are linearly independent. Hence the row space of \mathbf{H}_1 has dimension $n-k+1$.
- The dimension of its null space, C_1 , is then equal to

$$\dim(C_1) = (n + 1) - (n - k + 1) = k$$

◀ ◻ ▶ ◀ ◻ ▶ ◀ ≡ ▶ ◀ ≡ ▶ ≡ ≡ ≡ ≡ ≡ ≡ ≡ ≡ ≡

Problem # 3 (contd.)

- The matrix \mathbf{H}_1 is an $(n - k + 1) \times (n + 1)$ matrix.
- First we note that the $n - k$ rows of \mathbf{H} are linearly independent. It is clear that the first $(n - k)$ rows of \mathbf{H}_1 are also linearly independent.
- The last row of \mathbf{H}_1 has a “1” at its first position but other rows of \mathbf{H}_1 have a “0” at their first position. Any linear combination including the last row of \mathbf{H}_1 will never yield a zero vector.
- Thus all the rows of \mathbf{H}_1 are linearly independent. Hence the row space of \mathbf{H}_1 has dimension $n-k+1$.
- The dimension of its null space, C_1 , is then equal to

$$\dim(C_1) = (n + 1) - (n - k + 1) = k$$

- Hence C_1 is an $(n + 1, k)$ linear code.

◀ ◻ ▶ ◀ ◻ ▶ ◀ ≡ ▶ ◀ ≡ ▶ ≡ ≡ ≡ ≡ ≡ ≡ ≡ ≡ ≡

Problem # 3 (contd.)

- Show that every codeword of C_1 has even weight.



Problem # 3 (contd.)

- Show that every codeword of C_1 has even weight.
- **Solution:** The last row of \mathbf{H}_1 is an all-one vector.



Problem # 3 (contd.)

- Show that every codeword of C_1 has even weight.
- **Solution:** The last row of \mathbf{H}_1 is an all-one vector.
- The inner product of a vector with odd weight and the all-one vector is “1”. Hence, for any odd weight vector \mathbf{v} ,

$$\mathbf{v}\mathbf{H}_1^T \neq 0$$

and \mathbf{v} cannot be a code word in C_1 .



Problem # 3 (contd.)

- Show that every codeword of C_1 has even weight.
- **Solution:** The last row of \mathbf{H}_1 is an all-one vector.
- The inner product of a vector with odd weight and the all-one vector is “1”. Hence, for any odd weight vector \mathbf{v} ,

$$\mathbf{v}\mathbf{H}_1^T \neq 0$$

and \mathbf{v} cannot be a code word in C_1 .

- Therefore, C_1 consists of only even-weight code words.



Problem # 3 (contd.)

- Show that C_1 can be obtained from C by adding an extra parity check digit, denoted by v_∞ to the left of each codeword \mathbf{v} as follows



Problem # 3 (contd.)

- Show that C_1 can be obtained from C by adding an extra parity check digit, denoted by v_∞ to the left of each codeword \mathbf{v} as follows
 - 1) if \mathbf{v} has odd weight, then $v_\infty = 1$, and



Problem # 3 (contd.)

- Show that C_1 can be obtained from C by adding an extra parity check digit, denoted by v_∞ to the left of each codeword \mathbf{v} as follows
 - 1) if \mathbf{v} has odd weight, then $v_\infty = 1$, and
 - 2) if \mathbf{v} has even weight, then $v_\infty = 0$



Problem # 3 (contd.)

- Show that C_1 can be obtained from C by adding an extra parity check digit, denoted by v_∞ to the left of each codeword \mathbf{v} as follows
 - 1) if \mathbf{v} has odd weight, then $v_\infty = 1$, and
 - 2) if \mathbf{v} has even weight, then $v_\infty = 0$
- **Solution:** Let \mathbf{v} be a code word in C . Then $\mathbf{v}H^T = 0$. Extend \mathbf{v} by adding a digit v_∞ to its left.



Problem # 3 (contd.)

- Show that C_1 can be obtained from C by adding an extra parity check digit, denoted by v_∞ to the left of each codeword \mathbf{v} as follows
 - 1) if \mathbf{v} has odd weight, then $v_\infty = 1$, and
 - 2) if \mathbf{v} has even weight, then $v_\infty = 0$
- **Solution:** Let \mathbf{v} be a code word in C . Then $\mathbf{v}H^T = 0$. Extend \mathbf{v} by adding a digit v_∞ to its left.
- This results in a vector of $n+1$ digits,

$$\mathbf{v}_1 = (v_\infty, \mathbf{v}) = (v_\infty, v_0, v_1, \dots, v_{n-1}).$$



Problem # 3 (contd.)

- Show that C_1 can be obtained from C by adding an extra parity check digit, denoted by v_∞ to the left of each codeword \mathbf{v} as follows
 - 1) if \mathbf{v} has odd weight, then $v_\infty = 1$, and
 - 2) if \mathbf{v} has even weight, then $v_\infty = 0$
- **Solution:** Let \mathbf{v} be a code word in C . Then $\mathbf{v}H^T = 0$. Extend \mathbf{v} by adding a digit v_∞ to its left.
- This results in a vector of $n+1$ digits,

$$\mathbf{v}_1 = (v_\infty, \mathbf{v}) = (v_\infty, v_0, v_1, \dots, v_{n-1}).$$

- For \mathbf{v}_1 to be a vector in C_1 , we must require that

$$\mathbf{v}_1 \mathbf{H}_1^T = \mathbf{0}$$



Problem # 3 (contd.)

- Note that the inner product of v_1 with any of the first $n-k$ rows of \mathbf{H}_1 is 0.



Problem # 3 (contd.)

- Note that the inner product of v_1 with any of the first $n-k$ rows of \mathbf{H}_1 is 0.
- The inner product of \mathbf{v}_1 with the last row of \mathbf{H}_1 is

$$v_\infty + v_0 + v_1 + \cdots + v_{n-1}$$



Problem # 3 (contd.)

- Note that the inner product of v_1 with any of the first $n-k$ rows of \mathbf{H}_1 is 0.
- The inner product of \mathbf{v}_1 with the last row of \mathbf{H}_1 is

$$v_\infty + v_0 + v_1 + \cdots + v_{n-1}$$

- For this sum to be zero, we must require that $v_\infty = 1$ if the vector \mathbf{v} has odd weight and $v_\infty = 0$ if the vector \mathbf{v} has even weight.



Problem # 3 (contd.)

- Note that the inner product of v_1 with any of the first $n-k$ rows of \mathbf{H}_1 is 0.
- The inner product of \mathbf{v}_1 with the last row of \mathbf{H}_1 is

$$v_\infty + v_0 + v_1 + \cdots + v_{n-1}$$

- For this sum to be zero, we must require that $v_\infty = 1$ if the vector \mathbf{v} has odd weight and $v_\infty = 0$ if the vector \mathbf{v} has even weight.
- Therefore, any vector v_1 formed as above is a codeword in C_1 , there are 2^k such codewords.



Problem # 3 (contd.)

- Note that the inner product of v_1 with any of the first $n-k$ rows of \mathbf{H}_1 is 0.
- The inner product of \mathbf{v}_1 with the last row of \mathbf{H}_1 is

$$v_\infty + v_0 + v_1 + \cdots + v_{n-1}$$

- For this sum to be zero, we must require that $v_\infty = 1$ if the vector \mathbf{v} has odd weight and $v_\infty = 0$ if the vector \mathbf{v} has even weight.
- Therefore, any vector v_1 formed as above is a codeword in C_1 , there are 2^k such codewords.
- The dimension of C_1 is k , these 2^k codewords are all the code words of C_1 .