

An introduction to coding theory

Adrish Banerjee

Department of Electrical Engineering
Indian Institute of Technology Kanpur
Kanpur, Uttar Pradesh
India

Mar. 13, 2017



Lecture #18: Convergence of turbo codes



Outline of the lecture

- Introduction



Adrish Banerjee

Department of Electrical Engineering Indian Institute of Technology Kanpur Kanpur, Uttar Pradesh India

An introduction to coding theory

Outline of the lecture

- Introduction
- Measures for convergence analysis of turbo codes



Adrish Banerjee

Department of Electrical Engineering Indian Institute of Technology Kanpur Kanpur, Uttar Pradesh India

An introduction to coding theory

Outline of the lecture

- Introduction
- Measures for convergence analysis of turbo codes
 - El Gamal's method



Outline of the lecture

- Introduction
- Measures for convergence analysis of turbo codes
 - El Gamal's method
 - Density evolution



Outline of the lecture

- Introduction
- Measures for convergence analysis of turbo codes
 - El Gamal's method
 - Density evolution
 - EXIT charts



Outline of the lecture

- Introduction
- Measures for convergence analysis of turbo codes
 - El Gamal's method
 - Density evolution
 - EXIT charts
- Transfer Characteristics of the turbo decoder



Outline of the lecture

- Introduction
- Measures for convergence analysis of turbo codes
 - El Gamal's method
 - Density evolution
 - EXIT charts
- Transfer Characteristics of the turbo decoder
- Threshold Calculation




Outline of the lecture

- Introduction
- Measures for convergence analysis of turbo codes
 - El Gamal's method
 - Density evolution
 - EXIT charts
- Transfer Characteristics of the turbo decoder
- Threshold Calculation
- Limitations of the threshold calculation methods.




Introduction



- Convergence analysis is used to explain the performance of the turbo code in the waterfall region.

Navigation icons: back, forward, search, etc.

Introduction




Inputs and Outputs of a soft-input, soft-output (SISO) turbo decoder

- For turbo iterative decoding, the extrinsic information from one decoder is fed as a-priori information to the other decoder.

Navigation icons: back, forward, search, etc.


Introduction



Inputs and Outputs of a soft-input, soft-output (SISO) turbo decoder

- For turbo iterative decoding, the extrinsic information from one decoder is fed as a-priori information to the other decoder.
- Initially, the decoder has no a-priori information about the information bits.

Introduction



Inputs and Outputs of a soft-input, soft-output (SISO) turbo decoder

- For turbo iterative decoding, the extrinsic information from one decoder is fed as a-priori information to the other decoder.
- Initially, the decoder has no a-priori information about the information bits.
- With increasing iterations, only input to the decoder that is changing is the a-priori information.

Introduction

- Basic idea of convergence analysis is to track how extrinsic information evolve with increasing iterations.

Introduction

- Basic idea of convergence analysis is to track how extrinsic information evolve with increasing iterations.
- For a given E_b/N_0 , convergence analysis methods relate a parameter related to the extrinsic information of the turbo decoder to a parameter related to the a-priori information of the turbo decoder.

Introduction

- Basic idea of convergence analysis is to track how extrinsics information evolve with increasing iterations.
- For a given E_b/N_0 , convergence analysis methods relate a parameter related to the extrinsic information of the turbo decoder to a parameter related to the a-priori information of the turbo decoder.
- For asymptotically large block lengths, the smallest channel SNR for which iterative decoding converges is known as the *iterative decoding threshold*.

Introduction

- Basic idea of convergence analysis is to track how extrinsics information evolve with increasing iterations.
- For a given E_b/N_0 , convergence analysis methods relate a parameter related to the extrinsic information of the turbo decoder to a parameter related to the a-priori information of the turbo decoder.
- For asymptotically large block lengths, the smallest channel SNR for which iterative decoding converges is known as the *iterative decoding threshold*.
- Convergence analysis methods provide a tool to compute convergence thresholds for concatenated coding schemes using iterative decoding.

Introduction

- Basic idea of convergence analysis is to track how extrinsic information evolve with increasing iterations.
- For a given E_b/N_0 , convergence analysis methods relate a parameter related to the extrinsic information of the turbo decoder to a parameter related to the a-priori information of the turbo decoder.
- For asymptotically large block lengths, the smallest channel SNR for which iterative decoding converges is known as the *iterative decoding threshold*.
- Convergence analysis methods provide a tool to compute convergence thresholds for concatenated coding schemes using iterative decoding.
- They also help in the selection of constituent codes and puncturing patterns for turbo coding schemes for good performance in the waterfall region.




Measures for convergence analysis of turbo codes

- SNR [1].
 - Density evolution [2].
 - EXIT charts [3].
1. H. E. Gamal et. al., "Analyzing the turbo decoder using the Gaussian approximation," IEEE Trans. Inform. Theory, vol. 47, pp. 671-686, Feb 2001.
 2. D. Divsalar et. al, "Iterative Turbo Decoder Analysis Based on Density Evolution," IEEE JSAC, vol. 19, pp. 891-907, May 2001
 3. S. ten Brink, "Convergence behaviour of iteratively decoded parallel concatenated codes," IEEE Trans. Comm., vol. 49, Oct 2001.




El-Gamal's approach




- This method is based on Gaussian approximation of the output extrinsic information.

El-Gamal's approach



- This method is based on Gaussian approximation of the output extrinsic information.
- The Gaussian approximation allows characterization of the turbo decoder by its SNR.

El-Gamal's approach



- This method is based on Gaussian approximation of the output extrinsic information.
- The Gaussian approximation allows characterization of the turbo decoder by its SNR.
- For an AWGN channel,

$$z = x + n$$

where z is the received channel value, x is the transmitted bit ($= \pm 1$), and n is Gaussian distributed with zero mean and variance $N_0/2$.

El-Gamal's approach

- The log-likelihood or L-values are calculated as:

$$Z = \ln \frac{p(z|x = +1)}{p(z|x = -1)} \quad A = \ln \frac{p(u = +1)}{p(u = -1)},$$

where $u(= \pm 1)$ represents an information bit.

El-Gamal's approach

- The log-likelihood or L-values are calculated as:

$$Z = \ln \frac{p(z|x = +1)}{p(z|x = -1)} \quad A = \ln \frac{p(u = +1)}{p(u = -1)},$$

where $u(=\pm 1)$ represents an information bit.

- For large blocksizes, the probability distribution of the a-priori L-values p_A , are assumed to be Gaussian. In particular, the a-priori L-value A can be modeled as

$$A = \mu_A \cdot u + n_A$$

where the n_A is a zero mean Gaussian random variable with variance σ_A^2 that satisfies the following condition

$$\mu_A = \frac{\sigma_A^2}{2}. \quad (\text{consistency condition})$$



El-Gamal's approach

- The a-priori information at the input of the decoder can be characterized by input SNR,

$$\text{SNR}_i = \frac{\mu_A^2}{\sigma_A^2} = \frac{\mu_A}{2}$$



El-Gamal's approach

- The a-priori information at the input of the decoder can be characterized by input SNR,

$$\text{SNR}_i = \frac{\mu_A^2}{\sigma_A^2} = \frac{\mu_A}{2}$$

- The extrinsic information at the output of the decoder can be characterized by output SNR calculated as follows

$$P_e = Q(\sqrt{(2\text{SNR}_0)})$$

where P_e is the bit error probability of the extrinsic information at the output of SISO decoder.



El-Gamal's approach

- The a-priori information at the input of the decoder can be characterized by input SNR,

$$\text{SNR}_i = \frac{\mu_A^2}{\sigma_A^2} = \frac{\mu_A}{2}$$

- The extrinsic information at the output of the decoder can be characterized by output SNR calculated as follows

$$P_e = Q(\sqrt{(2\text{SNR}_0)})$$

where P_e is the bit error probability of the extrinsic information at the output of SISO decoder.

- Viewing SNR_0 as a function of E_b/N_0 , and SNR_i , the transfer characteristics of the decoder can be written as,

$$\text{SNR}_0 = T(\text{SNR}_i, E_b/N_0)$$



Transfer characteristics of a SISO decoder

Step 1 : For a given SNR E_b/N_0 , the distribution of a-priori L-value is generated for a particular mean μ_A , and transmitted bits u .



Transfer characteristics of a SISO decoder

Step 1 : For a given SNR E_b/N_0 , the distribution of a-priori L-value is generated for a particular mean μ_A , and transmitted bits u .

Step 2 : A SISO MAP decoder module is simulated. The inputs to the SISO module are the channel L-values, and the a-priori L-value generated in Step 1.



Transfer characteristics of a SISO decoder

- Step 1** : For a given SNR E_b/N_0 , the distribution of a-priori L-value is generated for a particular mean μ_A , and transmitted bits u .
- Step 2** : A SISO MAP decoder module is simulated. The inputs to the SISO module are the channel L-values, and the a-priori L-value generated in Step 1.
- Step 3** : The mean, μ_E , of the extrinsic information generated in step 2 is calculated.



Transfer characteristics of a SISO decoder

- Step 1** : For a given SNR E_b/N_0 , the distribution of a-priori L-value is generated for a particular mean μ_A , and transmitted bits u .
- Step 2** : A SISO MAP decoder module is simulated. The inputs to the SISO module are the channel L-values, and the a-priori L-value generated in Step 1.
- Step 3** : The mean, μ_E , of the extrinsic information generated in step 2 is calculated.
- Step 4** : The mean μ_A is varied from zero to a large number and the steps 1-3 are repeated.




Transfer characteristics of a SISO decoder

- Step 1** : For a given SNR E_b/N_0 , the distribution of a-priori L-value is generated for a particular mean μ_A , and transmitted bits u .
- Step 2** : A SISO MAP decoder module is simulated. The inputs to the SISO module are the channel L-values, and the a-priori L-value generated in Step 1.
- Step 3** : The mean, μ_E , of the extrinsic information generated in step 2 is calculated.
- Step 4** : The mean μ_A is varied from zero to a large number and the steps 1-3 are repeated.
- Step 5** : The set of $(\text{SNR}_i, \text{SNR}_0)$ for different values of μ_a is plotted. This is then used as the transfer characteristics for the SISO module for that particular code, and channel SNR E_b/N_0 .

Navigation icons: back, forward, search, etc.

Transfer characteristics of a SISO decoder



Navigation icons: back, forward, search, etc.

Threshold Calculation

Step 1 : For a particular E_b/N_0 , plot the transfer characteristics of SISO decoder for two constituent encoders on a reverse set of axes.



Threshold Calculation

Step 1 : For a particular E_b/N_0 , plot the transfer characteristics of SISO decoder for two constituent encoders on a reverse set of axes.

Step 2 : If a tunnel exists, the channel SNR E_b/N_0 is reduced until the transfer characteristics touch or cross each other.



Threshold Calculation

- Step 1** : For a particular E_b/N_0 , plot the transfer characteristics of SISO decoder for two constituent encoders on a reverse set of axes.
- Step 2** : If a tunnel exists, the channel SNR E_b/N_0 is reduced until the transfer characteristics touch or cross each other.
- Step 3** : If the transfer characteristics touch or cross each other, the channel SNR E_b/N_0 is increased until a tunnel exists.




Threshold Calculation

- Step 1** : For a particular E_b/N_0 , plot the transfer characteristics of SISO decoder for two constituent encoders on a reverse set of axes.
- Step 2** : If a tunnel exists, the channel SNR E_b/N_0 is reduced until the transfer characteristics touch or cross each other.
- Step 3** : If the transfer characteristics touch or cross each other, the channel SNR E_b/N_0 is increased until a tunnel exists.
- Step 4** : The smallest channel SNR E_b/N_0 for which the transfer characteristics do not touch and a tunnel exists is the convergence threshold for that particular code.



Threshold Calculation




Adrish Banerjee

Department of Electrical Engineering Indian Institute of Technology Kanpur Kanpur, Uttar Pradesh India

An introduction to coding theory

Threshold Calculation



Adrish Banerjee

Department of Electrical Engineering Indian Institute of Technology Kanpur Kanpur, Uttar Pradesh India

An introduction to coding theory

Decoding trajectory of a Turbo decoder

Step 1 : For a particular E_b/N_0 , plot the transfer characteristics of SISO decoder for two constituent encoders on a reverse set of axes.



Decoding trajectory of a Turbo decoder

Step 1 : For a particular E_b/N_0 , plot the transfer characteristics of SISO decoder for two constituent encoders on a reverse set of axes.

Step 2 : For a given E_b/N_0 , initially $\text{SNR}_i = 0$ corresponding to the first iteration of decoder 1, we determine the resulting SNR_0 (vertically) using the transfer characteristics for decoder 1.



Decoding trajectory of a Turbo decoder

- Step 1** : For a particular E_b/N_0 , plot the transfer characteristics of SISO decoder for two constituent encoders on a reverse set of axes.
- Step 2** : For a given E_b/N_0 , initially $\text{SNR}_i = 0$ corresponding to the first iteration of decoder 1, we determine the resulting SNR_0 (vertically) using the transfer characteristics for decoder 1.
- Step 3** : Since the extrinsic information at the output of decoder 1 becomes the a-priori information at the input of decoder 2, the value of SNR_0 from decoder 1 becomes SNR_i for the first iteration of decoder 2, and the resulting SNR_0 for decoder 2 is determined (horizontally) using the transfer characteristics for decoder 2.



Decoding trajectory of a Turbo decoder

- Step 1** : For a particular E_b/N_0 , plot the transfer characteristics of SISO decoder for two constituent encoders on a reverse set of axes.
- Step 2** : For a given E_b/N_0 , initially $\text{SNR}_i = 0$ corresponding to the first iteration of decoder 1, we determine the resulting SNR_0 (vertically) using the transfer characteristics for decoder 1.
- Step 3** : Since the extrinsic information at the output of decoder 1 becomes the a-priori information at the input of decoder 2, the value of SNR_0 from decoder 1 becomes SNR_i for the first iteration of decoder 2, and the resulting SNR_0 for decoder 2 is determined (horizontally) using the transfer characteristics for decoder 2.
- Step 4** : This procedure is repeated to trace the trajectory of iterative decoding.




Decoding trajectory of a Turbo decoder

- Step 1** : For a particular E_b/N_0 , plot the transfer characteristics of SISO decoder for two constituent encoders on a reverse set of axes.
- Step 2** : For a given E_b/N_0 , initially $\text{SNR}_i = 0$ corresponding to the first iteration of decoder 1, we determine the resulting SNR_0 (vertically) using the transfer characteristics for decoder 1.
- Step 3** : Since the extrinsic information at the output of decoder 1 becomes the a-priori information at the input of decoder 2, the value of SNR_0 from decoder 1 becomes SNR_i for the first iteration of decoder 2, and the resulting SNR_0 for decoder 2 is determined (horizontally) using the transfer characteristics for decoder 2.
- Step 4** : This procedure is repeated to trace the trajectory of iterative decoding.
- Step 5** : If a tunnel exists between the two transfer characteristics, iterative decoding converges.

Navigation icons: back, forward, search, etc.

Decoding trajectory of a Turbo decoder



Navigation icons: back, forward, search, etc.

Density Evolution

- This method is based on tracking the actual densities of the extrinsic information during each half iteration.

Density Evolution

- This method is based on tracking the actual densities of the extrinsic information during each half iteration.
- Generate input a-priori distribution based on the observed extrinsic information distribution.


Density Evolution

- This method is based on tracking the actual densities of the extrinsic information during each half iteration.
- Generate input a-priori distribution based on the observed extrinsic information distribution.
- Simulate SISO decoder, and from the generated extrinsic information find the distribution of the extrinsic information.

Density Evolution


- This method is based on tracking the actual densities of the extrinsic information during each half iteration.
- Generate input a-priori distribution based on the observed extrinsic information distribution.
- Simulate SISO decoder, and from the generated extrinsic information find the distribution of the extrinsic information.
- The a-priori/extrinsic information can be characterized by the $\text{SNR}_i/\text{SNR}_0$, where mean and variance of the a-priori/extrinsic information is calculated empirically.

Extrinsic Information Transfer Charts




- Mutual Information is used to describe the flow of extrinsic information through soft in/soft out decoders.

Extrinsic Information Transfer Charts



- Mutual Information is used to describe the flow of extrinsic information through soft in/soft out decoders.
- The information content of the a-priori probabilities is measured by the mutual information $I_A = I(U; A)$ between the information bits U and the a-priori L-values A .

Extrinsic Information Transfer Charts



- Mutual Information is used to describe the flow of extrinsic information through soft in/soft out decoders.
- The information content of the a-priori probabilities is measured by the mutual information $I_A = I(U; A)$ between the information bits U and the a-priori L-values A .
- The input mutual Information $I(U; A)$ is calculated as:

$$I(U; A) \triangleq \frac{1}{2} \sum_{U=-1,1} \int_{-\infty}^{\infty} p_A(\xi|U=u) \log \frac{p_A(\xi|U=u)}{p_A(\xi)} d\xi$$

Extrinsic Information Transfer Charts

- The information content of the extrinsic a-posteriori probabilities is measured by the mutual information $I_E = I(U; E)$ between the information bits U and the extrinsic L-values E .

Extrinsic Information Transfer Charts

- The information content of the extrinsic a-posteriori probabilities is measured by the mutual information $I_E = I(U; E)$ between the information bits U and the extrinsic L-values E .
- The probability distribution of the extrinsic L-values p_E , is computed experimentally from Monte Carlo simulations. p_E is then used to calculate the output mutual information $I(U; E)$.

$$I(U; E) \triangleq \frac{1}{2} \sum_{U=-1.1} \int_{-\infty}^{\infty} p_E(\xi|U=u) \log \frac{p_E(\xi|U=u)}{p_E(\xi)} d\xi$$

◀ ◻ ▶ ◀ ◻ ◻ ▶ ◀ ≡ ≡ ≡ ▶ ◀ ≡ ≡ ≡ ▶ ≡ ≡ ≡ ↺ 🔍 ↻

Adrish Banerjee

Department of Electrical Engineering Indian Institute of Technology Kanpur Kanpur, Uttar Pradesh India

An introduction to coding theory

Extrinsic Information Transfer Charts

- The information content of the extrinsic a-posteriori probabilities is measured by the mutual information $I_E = I(U; E)$ between the information bits U and the extrinsic L-values E .
- The probability distribution of the extrinsic L-values p_E , is computed experimentally from Monte Carlo simulations. p_E is then used to calculate the output mutual information $I(U; E)$.

$$I(U; E) \triangleq \frac{1}{2} \sum_{U=-1.1} \int_{-\infty}^{\infty} p_E(\xi|U=u) \log \frac{p_E(\xi|U=u)}{p_E(\xi)} d\xi$$

- Viewing I_E as a function of I_A and E_b/N_o , the extrinsic information transfer characteristic of an encoder is defined as

$$I_F = T(I_A, E_b/N_o).$$

◀ ◻ ▶ ◀ ◻ ▶ ◀ ≡ ▶ ◀ ≡ ▶ ≡

Adrish Banerjee

Department of Electrical Engineering Indian Institute of Technology Kanpur Kanpur, Uttar Pradesh India

An introduction to coding theory

Extrinsic Information Transfer Charts

- An EXIT chart for a particular channel SNR E_b/N_0 can be formed by plotting the transfer characteristics of the two constituent encoders on reverse axes.

Extrinsic Information Transfer Charts

- An EXIT chart for a particular channel SNR E_b/N_0 can be formed by plotting the transfer characteristics of the two constituent encoders on reverse axes.
- The EXIT chart can then be used to trace the trajectory of iterative decoding and to determine the convergence behavior of the constituent decoders.

Extrinsic Information Transfer Charts

- An EXIT chart for a particular channel SNR E_b/N_0 can be formed by plotting the transfer characteristics of the two constituent encoders on reverse axes.
- The EXIT chart can then be used to trace the trajectory of iterative decoding and to determine the convergence behavior of the constituent decoders.
- The existence of a “tunnel” implies convergence of iterative decoding.



Extrinsic Information Transfer Charts

- An EXIT chart for a particular channel SNR E_b/N_0 can be formed by plotting the transfer characteristics of the two constituent encoders on reverse axes.
- The EXIT chart can then be used to trace the trajectory of iterative decoding and to determine the convergence behavior of the constituent decoders.
- The existence of a “tunnel” implies convergence of iterative decoding.
- As the channel SNR E_b/N_0 is lowered, the two transfer characteristics come closer together (the “tunnel” narrows) until the two curves meet.



Limitations of the convergence analysis methods

- Convergence analysis is based on asymptotically large block sizes. Practical systems use a finite block size.

Limitations of the convergence analysis methods

- Convergence analysis is based on asymptotically large block sizes. Practical systems use a finite block size.
- Some of the methods are based on Gaussian approximation of the distribution of the extrinsic information. This approximation may not hold.