

*

AVERAGE CODE

LENGTH

How to achieve progressively lower code lengths?

Recall, optimal codeword length
for i th symbol s_i

$$l_i = \log_2\left(\frac{1}{P_i}\right)$$

Need not be
an integer

Choose $l_i = \lceil \log_2\left(\frac{1}{P_i}\right) \rceil$

integer ceiling
Function

✓ Gives the next
highest integer
Ex: $\lceil 4.7 \rceil = 5$

$$\log_2\left(\frac{1}{p_i}\right) \leq \frac{\left\lceil \log_2\left(\frac{1}{p_i}\right) \right\rceil}{l_i} \leq \log_2\left(\frac{1}{p_i}\right) + 1$$

$$\text{Ex: } 4.7 \leq \lceil 4.7 \rceil = 5 \leq 4.7 + 1$$

$$x \leq \lceil x \rceil \leq x + 1$$

$$\underbrace{\sum_{i=1}^{M-1} p_i \log_2\left(\frac{1}{p_i}\right)}_{H(X)} \leq \underbrace{\sum_{i=1}^{M-1} p_i \frac{\left\lceil \log_2\left(\frac{1}{p_i}\right) \right\rceil}{l_i}}_L$$

$$\begin{aligned}
 &\leq \sum_{i=0}^{M-1} P_i \left(\log_2 \left(\frac{1}{P_i} \right) + 1 \right) \\
 &= \sum_{i=0}^{M-1} P_i \log_2 \left(\frac{1}{P_i} \right) + \underbrace{\sum_{i=0}^{M-1} P_i}_{1} \\
 &= H(X) + 1
 \end{aligned}$$

We obtain,

$$H(X) \leq L \leq H(X) + 1$$

is within 1
bit of entropy

How to achieve
a code length arbitrarily
close to the Entropy?

Consider the sequence,

$$\bar{X} = X_1, X_2, \dots, X_n$$


n symbols together

Encode the block of n
symbols.

Discrete Memoryless Source
 $\Rightarrow$ Symbols are IID.

Let average code length
be $\bar{L}_n$ $\leftarrow$ when encoding
blocks of size n .

$H(\bar{X}) =$ entropy of
block source.



↓ Since symbols are IID

$$H(\bar{X}) = n H(X)$$

Intuitive: Since average information in block of n symbols = $n \times$ Average information in single symbol

Key Assumption:

IID, arising from Discrete Memoryless Source.

Theory: $P(X_1 = s_{i1}, X_2 = s_{i2}, \dots, X_n = s_{in})$

$$= P_{i1} P_{i2} \dots P_{in}$$

$$H(X) \leq L_n \leq H(X) + 1$$

$$nH(X) \leq L_n \leq nH(X) + 1$$

$$H(X) \leq \frac{L_n}{n} \leq H(X) + \frac{1}{n}$$

within $\frac{1}{n}$ of Entropy.

#bits per n symbols
 n

= Average number of bits per symbol.

✓ By increasing n , one can make average code length, arbitrarily close to Entropy.

Coding over larger & larger blocks.

i.e. within $\frac{1}{n}$ bits
and $\lim_{n \rightarrow \infty} \frac{1}{n} \rightarrow 0$

⇒ Gap between L_n and $H(X)$ approaches 0.