

Linear Dynamical Systems

Week 2 - Stability

Outline of Week 2

- 1 Introduction and Origin of Stability Analysis
- 2 Brief review of norms and definite matrices
- 3 Definitions of Stability
- 4 Lyapunov stability
- 5 Eigenvalue condition for Lyapunov stability
- 6 Bounded Input Bounded Output Stability
- 7 BIBO vs Lyapunov stability

Origin of Stability Analysis

One of the first significant feedback control systems in modern Europe




Figure: The flyball governor invented by James Watt in 1788. (a) The original design, and (b) the improved design.¹

¹C. G. Kang, "Origin of Stability Analysis: "On Governors" by J.C. Maxwell [Historical Perspectives]," in IEEE Control Systems, 36(5), pp. 77-88, 2016.

Origin of Stability Analysis

- At the height of industrial revolution around 1868, many governors were installed.
- The governor system was soon discovered to be plagued by problems of *instability* and *inaccuracy* that could apparently not be overcome by either theoretical or practical approaches

Origin of Stability Analysis

- At the height of industrial revolution around 1868, many governors were installed.
- The governor system was soon discovered to be plagued by problems of *instability* and *inaccuracy* that could apparently not be overcome by either theoretical or practical approaches
- Maxwell's 1868 paper²:
 - Stability concept
 - Simple mathematical models
 - Importance of integral actions
 - Linearization
 - Stability is an algebraic problem
 - Criteria for 1st, 2nd, and 3rd order systems
 - Posed stability problem in competition

²J. C. Maxwell, "On governors," Proc. R. Soc. London, 16, 270–283, 1868.

The equation of motion of the machine itself is

$$M \frac{d^2 x}{dt^2} = P - R - F \left(\frac{dx}{dt} - V_1 \right) - Gy. \quad \dots \quad (10)$$

This must be combined with equation (7) to determine the motion of the whole apparatus. The solution is of the form

$$x = A_1 e^{n_1 t} + A_2 e^{n_2 t} + A_3 e^{n_3 t} + Vt, \quad \dots \quad (11)$$

where n_1, n_2, n_3 are the roots of the cubic equation

$$MBn^3 + (MY + FB)n^2 + FYn + FG = 0. \quad \dots \quad (12)$$

If n be a pair of roots of this equation of the form $a \pm \sqrt{-1}b$, then the part of x corresponding to these roots will be of the form

$$e^{at} \cos (bt + \beta).$$

If a is a negative quantity, this will indicate an oscillation the amplitude of which continually decreases. If a is zero, the amplitude will remain constant, and if a is positive, the amplitude will continually increase.

One root of the equation (12) is evidently a real negative quantity. The condition that the real part of the other roots should be negative is

$$\left(\frac{F}{M} + \frac{Y}{B} \right) \frac{Y}{B} - \frac{G}{B} = \text{a positive quantity.}$$

This is the condition of stability of the motion. If it is not fulfilled there will be a dancing motion of the governor, which will increase till it is as great as the limits of motion of the governor. To ensure this stability, the value of Y must be made sufficiently great, as compared with G , by placing the weight W in a viscous liquid if the viscosity of the lubri-

Taxonomy - Stability Concept³

“the motion of a machine with its governor consist in general of a uniform motion, combined with a disturbance that may be expressed as the sum of several component motions. These components may be of four different kinds:

- ① continually increase,
- ② continually diminish,
- ③ be an oscillation of continually increasing amplitude, and
- ④ be an oscillation of continually decreasing amplitude.”

³J. C. Maxwell, “On governors,” Proc. R. Soc. London, 16, 270–283, 1868.

Taxonomy - Stability Concept³

“the motion of a machine with its governor consist in general of a uniform motion, combined with a disturbance that may be expressed as the sum of several component motions. These components may be of four different kinds:

- ① continually increase,
- ② continually diminish,
- ③ be an oscillation of continually increasing amplitude, and
- ④ be an oscillation of continually decreasing amplitude.”

The **second** and **fourth** kinds are admissible in a good governor, and are mathematically equivalent to the condition that all the possible roots, and all the possible parts of the impossible roots of a characteristic equation shall be negative.

³J. C. Maxwell, “On governors,” Proc. R. Soc. London, 16, 270–283, 1868.

Matrix Norms (Review)

A matrix norm is a norm on the vector space $K^{m \times n}$.

Matrix Norms (Review)

A matrix norm is a norm on the vector space $K^{m \times n}$.

Thus, the matrix norm is a function $\|\cdot\| : K^{m \times n} \rightarrow \mathbb{R}$ that must satisfy the following properties:

For all scalars $\alpha \in K$ and for all matrices $A, B \in K^{m \times n}$,

$$\|\alpha A\| = |\alpha| \|A\| \quad (\text{homogeneity})$$

$$\|A + B\| \leq \|A\| + \|B\| \quad (\text{triangle inequality})$$

$$\|A\| \geq 0 \quad (\text{positive-valued})$$

$$\|A\| = 0 \text{ iff } A = 0_{m,n} \quad (\text{definite})$$

Matrix Norms (Review)

Several matrix norms are available for an $m \times n$ matrix $A = [a_{ij}]$.

Matrix Norms (Review)

Several matrix norms are available for an $m \times n$ matrix $A = [a_{ij}]$.

- 1 The *one-norm*,

$$\|A\|_1 \triangleq \max_{1 \leq j \leq n} \sum_{i=1}^m |a_{ij}|.$$

For a (column) vector $v = [v_i] \in \mathbb{R}^\ell$, $\|v\|_1 \triangleq \sum_{i=1}^\ell |v_i|$.

Matrix Norms (Review)

Several matrix norms are available for an $m \times n$ matrix $A = [a_{ij}]$.

- ① The *one-norm*,

$$\|A\|_1 \triangleq \max_{1 \leq j \leq n} \sum_{i=1}^m |a_{ij}|.$$

For a (column) vector $v = [v_i] \in \mathbb{R}^\ell$, $\|v\|_1 \triangleq \sum_{i=1}^\ell |v_i|$.

- ② The *∞ -norm*,

$$\|A\|_\infty \triangleq \max_{1 \leq i \leq m} \sum_{j=1}^n |a_{ij}|.$$

For a (column) vector $v = [v_i] \in \mathbb{R}^\ell$, $\|v\|_\infty \triangleq \max_{1 \leq i \leq \ell} |v_i|$.

Matrix Norms (Review)

- 3 The *two-norm*,

$$\begin{aligned}\|A\|_2 &\triangleq \sigma_{\max}[A], \\ &\triangleq \sqrt{\lambda_{\max}[A'A]}\end{aligned}$$

where $\sigma_{\max}[A]$ denotes the largest singular value, and $\lambda_{\max}[A]$ denotes the largest eigenvalue of A

For a (column) vector $v = [v_i] \in \mathbb{R}^\ell$, $\|v\|_2 \triangleq \sqrt{\sum_{i=1}^{\ell} v_i^2}$.

Matrix Norms (Review)

- 3 The *two-norm*,

$$\begin{aligned}\|A\|_2 &\triangleq \sigma_{\max}[A], \\ &\triangleq \sqrt{\lambda_{\max}[A'A]}\end{aligned}$$

where $\sigma_{\max}[A]$ denotes the largest singular value, and $\lambda_{\max}[A]$ denotes the largest eigenvalue of A

For a (column) vector $v = [v_i] \in \mathbb{R}^\ell$, $\|v\|_2 \triangleq \sqrt{\sum_{i=1}^\ell v_i^2}$.

- 4 The *Frobenius norm*,

$$\|A\|_F \triangleq \sqrt{\sum_{i=1}^m \sum_{j=1}^n a_{ij}^2} = \sqrt{\sum_{i=1}^n \sigma_i[A]^2},$$

where the $\sigma_i[A]$ are the singular values of A .

For (column) vectors, the Frobenius norm coincides with the two-norm, but in general this is not true for matrices.

Matrix Norms (Review)

All matrix norms are *equivalent*

Matrix Norms (Review)

All matrix norms are *equivalent* in the sense that each one of them can be upper and lower bounded by any other times a multiplicative constant:

$$\frac{\|A\|_1}{\sqrt{n}} \leq \|A\|_2 \leq \sqrt{n} \|A\|_1$$

$$\frac{\|A\|_\infty}{\sqrt{n}} \leq \|A\|_2 \leq \sqrt{m} \|A\|_\infty$$

$$\frac{\|A\|_F}{\sqrt{n}} \leq \|A\|_2 \leq \|A\|_F$$

Matrix Norms (Review)

All matrix norms are *equivalent* in the sense that each one of them can be upper and lower bounded by any other times a multiplicative constant:

$$\frac{\|A\|_1}{\sqrt{n}} \leq \|A\|_2 \leq \sqrt{n} \|A\|_1$$

$$\frac{\|A\|_\infty}{\sqrt{n}} \leq \|A\|_2 \leq \sqrt{m} \|A\|_\infty$$

$$\frac{\|A\|_F}{\sqrt{n}} \leq \|A\|_2 \leq \|A\|_F$$

The four matrix norms above are submultiplicative; i.e., given two matrices A and B

$$\|AB\|_p \leq \|A\|_p \|B\|_p, \quad p \in \{1, 2, \infty, F\}$$

Matrix Norms (Review)

All matrix norms are *equivalent* in the sense that each one of them can be upper and lower bounded by any other times a multiplicative constant:

$$\frac{\|A\|_1}{\sqrt{n}} \leq \|A\|_2 \leq \sqrt{n}\|A\|_1$$

$$\frac{\|A\|_\infty}{\sqrt{n}} \leq \|A\|_2 \leq \sqrt{m}\|A\|_\infty$$

$$\frac{\|A\|_F}{\sqrt{n}} \leq \|A\|_2 \leq \|A\|_F$$

The four matrix norms above are submultiplicative; i.e., given two matrices A and B

$$\|AB\|_p \leq \|A\|_p \|B\|_p, \quad p \in \{1, 2, \infty, F\}$$

For any submultiplicative norm $\|\bullet\|_p$, we have

$$\|Ax\|_p \leq \|A\|_p \|x\|_p, \quad \forall x$$

and therefore

$$\|A\|_p \geq \max_{x \neq 0} \frac{\|Ax\|_p}{\|x\|_p}.$$

Positive-Definite Matrices (Review)

A symmetric $n \times n$ matrix Q is *positive-definite* if

$$x'Qx > 0, \quad \forall x \in \mathbb{R}^n \setminus \{0\}. \quad (1)$$

Positive-Definite Matrices (Review)

A symmetric $n \times n$ matrix Q is *positive-definite* if

$$x'Qx > 0, \quad \forall x \in \mathbb{R}^n \setminus \{0\}. \quad (1)$$

When $>$ is replaced by $<$, we obtain the definition of a *negative-definite* matrix.

- Positive-definite matrices are always nonsingular, and their inverses are also positive-definite.
- Negative-definite matrices are also always nonsingular, and their inverses are negative-definite.

Positive-Definite Matrices (Review)

A symmetric $n \times n$ matrix Q is *positive-definite* if

$$x'Qx > 0, \quad \forall x \in \mathbb{R}^n \setminus \{0\}. \quad (1)$$

When $>$ is replaced by $<$, we obtain the definition of a *negative-definite* matrix.

- Positive-definite matrices are always nonsingular, and their inverses are also positive-definite.
- Negative-definite matrices are also always nonsingular, and their inverses are negative-definite.

When (1) holds only for \leq or \geq , the matrix is said to be *negative-semidefinite* or *positive-semidefinite*, respectively.

Positive-Definite Matrices (Review)

The following statements are equivalent for a symmetric $n \times n$ matrix Q .

- 1 Q is positive-definite.
- 2 All eigenvalues of Q are strictly positive.
- 3 The determinants of all upper left submatrices of Q are positive.
- 4 There exists an $n \times n$ nonsingular real matrix H such that

$$Q = H'H$$

Positive-Definite Matrices (Review)

The following statements are equivalent for a symmetric $n \times n$ matrix Q .

- 1 Q is positive-definite.
- 2 All eigenvalues of Q are strictly positive.
- 3 The determinants of all upper left submatrices of Q are positive.
- 4 There exists an $n \times n$ nonsingular real matrix H such that

$$Q = H'H$$

For a positive-definite matrix Q we have

$$0 < \lambda_{\min}[Q]\|x\|^2 \leq x'Qx \leq \lambda_{\max}[Q]\|x\|^2, \quad \forall x \neq 0,$$

where $\lambda_{\min}[Q]$ and $\lambda_{\max}[Q]$ denote the smallest and largest eigenvalues of Q , respectively.

Simple Pendulum

- Equations of motion

$$I\ddot{\theta}(t) + mgl \sin \theta(t) = Q,$$



$$Q = -b\dot{\theta}(t) + u(t)$$

Consider a special case of heavy damping

i.e. $\frac{b}{I} \gg 1$



$$u_0 - mgl \sin \theta = I\ddot{\theta} + b\dot{\theta} \approx b\dot{\theta}$$

$$b\dot{x} = u_0 - mgl \sin x$$




Simple Pendulum

- Two equilibrium position (or steady states):
 - at $\theta = 0$
 - at $\theta = \pi$



Initial angle of 0° , a



Initial angle of 45°



Initial angle of 90°




Initial angle of 135°



Initial angle of 170°





Initial angle of 180° ,



Definitions of stability

In the sense of Lyapunov


A system steady state \mathbf{x}_s is said to be *stable* if for each possible region of radius $\epsilon > 0$ around the steady state, there is an initial state \mathbf{x}_0 at $t = t_0$ falling within a radius $\delta > 0$ around the steady state that causes the dynamic trajectory to stay within the region $|\mathbf{x} - \mathbf{x}_s| < \epsilon$ for all times $t > t_0$.



Definitions of stability

In the sense of Lyapunov

A system steady state \mathbf{x}_s is said to be *asymptotically stable* if it is both stable and in addition, there exists a region of initial conditions of radius $\delta_0 > 0$ around \mathbf{x}_s for which the system approaches \mathbf{x}_s as $t \rightarrow \infty$.



Definition 3

A system steady state is said to be unstable if it is not stable.

Lyapunov Stability

Consider the following continuous-time LTV system

$$\dot{x} = A(t)x + B(t)u, \quad y = C(t)x + D(t)u, \quad x \in \mathbb{R}^n, u \in \mathbb{R}^k, y \in \mathbb{R}^m.$$

Lyapunov Stability

Consider the following continuous-time LTV system

$$\dot{x} = A(t)x + B(t)u, \quad y = C(t)x + D(t)u, \quad x \in \mathbb{R}^n, u \in \mathbb{R}^k, y \in \mathbb{R}^m.$$

Definition (Lyapunov Stability)

The system (CLTV) is said to be

- 1 (marginally) stable in the sense of Lyapunov or internally stable whenever, for every initial condition $x(t_0) = x_0 \in \mathbb{R}^n$, the homogeneous state response

$$x(t) = \phi(t, t_0)x_0, \quad \forall t \geq 0$$

is uniformly bounded,

Lyapunov Stability

Consider the following continuous-time LTV system

$$\dot{x} = A(t)x + B(t)u, \quad y = C(t)x + D(t)u, \quad x \in \mathbb{R}^n, u \in \mathbb{R}^k, y \in \mathbb{R}^m.$$

Definition (Lyapunov Stability)

The system (CLTV) is said to be

- 1 (marginally) stable in the sense of Lyapunov or internally stable whenever, for every initial condition $x(t_0) = x_0 \in \mathbb{R}^n$, the homogeneous state response

$$x(t) = \phi(t, t_0)x_0, \quad \forall t \geq 0$$

is uniformly bounded,

- 2 asymptotically stable (in the sense of Lyapunov) whenever, in addition, for every initial condition $x(t_0) = x_0 \in \mathbb{R}^n$, we have that $x(t) \rightarrow 0$ as $t \rightarrow \infty$,

Lyapunov Stability

Consider the following continuous-time LTV system

$$\dot{x} = A(t)x + B(t)u, \quad y = C(t)x + D(t)u, \quad x \in \mathbb{R}^n, u \in \mathbb{R}^k, y \in \mathbb{R}^m.$$

Definition (Lyapunov Stability)

The system (CLTV) is said to be

- 1 (marginally) stable in the sense of Lyapunov or internally stable whenever, for every initial condition $x(t_0) = x_0 \in \mathbb{R}^n$, the homogeneous state response

$$x(t) = \phi(t, t_0)x_0, \quad \forall t \geq 0$$

is uniformly bounded,

- 2 asymptotically stable (in the sense of Lyapunov) whenever, in addition, for every initial condition $x(t_0) = x_0 \in \mathbb{R}^n$, we have that $x(t) \rightarrow 0$ as $t \rightarrow \infty$,
- 3 exponentially stable whenever, in addition, there exist constants $c, \lambda > 0$ such that, for every initial condition $x(t_0) = x_0 \in \mathbb{R}^n$, we have

$$\|x(t)\| \leq ce^{\lambda(t-t_0)}\|x(t_0)\|, \quad \forall t \geq 0,$$

Lyapunov Stability

Consider the following continuous-time LTV system

$$\dot{x} = A(t)x + B(t)u, \quad y = C(t)x + D(t)u, \quad x \in \mathbb{R}^n, u \in \mathbb{R}^k, y \in \mathbb{R}^m.$$

Definition (Lyapunov Stability)

The system (CLTV) is said to be

- 1 (marginally) stable in the sense of Lyapunov or internally stable whenever, for every initial condition $x(t_0) = x_0 \in \mathbb{R}^n$, the homogeneous state response

$$x(t) = \phi(t, t_0)x_0, \quad \forall t \geq 0$$

is uniformly bounded,

- 2 asymptotically stable (in the sense of Lyapunov) whenever, in addition, for every initial condition $x(t_0) = x_0 \in \mathbb{R}^n$, we have that $x(t) \rightarrow 0$ as $t \rightarrow \infty$,
- 3 exponentially stable whenever, in addition, there exist constants $c, \lambda > 0$ such that, for every initial condition $x(t_0) = x_0 \in \mathbb{R}^n$, we have

$$\|x(t)\| \leq ce^{\lambda(t-t_0)}\|x(t_0)\|, \quad \forall t \geq 0,$$

- 4 unstable whenever it is not marginally stable in the Lyapunov sense.

Lyapunov Stability

- The matrices $B(\bullet)$, $C(\bullet)$, and $D(\bullet)$ play no role in the above definition;

Lyapunov Stability

- The matrices $B(\bullet)$, $C(\bullet)$, and $D(\bullet)$ play no role in the above definition;
- only $A(\bullet)$ matters because this matrix completely defines the state transition matrix.

Therefore one often simply talks about the Lyapunov stability of the homogeneous system

$$\dot{x} = A(t)x, \quad x \in \mathbb{R}^n.$$

Lyapunov Stability

- The matrices $B(\bullet)$, $C(\bullet)$, and $D(\bullet)$ play no role in the above definition;
- only $A(\bullet)$ matters because this matrix completely defines the state transition matrix.

Therefore one often simply talks about the Lyapunov stability of the homogeneous system

$$\dot{x} = A(t)x, \quad x \in \mathbb{R}^n.$$

Attention!

- 1 For marginally stable systems, the effect of initial conditions does not grow unbounded with time (but it may grow temporarily during a transient phase).
- 2 For asymptotically stable systems, the effect of initial conditions eventually disappears with time.
- 3 For unstable systems, the effect of initial conditions (may) grow over time (depending on the specific initial conditions and the value of the matrix C).

Eigenvalue Conditions for Lyapunov Stability

The overall objective is to determine simple conditions to classify the continuous-time homogeneous LTI system

$$\dot{x} = Ax \quad x \in \mathbb{R}^n$$

in terms of its Lyapunov stability, *without explicitly computing the solution to the system.*

Eigenvalue Conditions for Lyapunov Stability

The overall objective is to determine simple conditions to classify the continuous-time homogeneous LTI system

$$\dot{x} = Ax \quad x \in \mathbb{R}^n$$

in terms of its Lyapunov stability, *without explicitly computing the solution to the system.*

Theorem (Eigenvalue conditions)

The system (H-CLTI) is

- 1 *marginally stable if and only if all the eigenvalues of A have negative or zero real parts and all the Jordan blocks corresponding to eigenvalues with zero real parts are 1×1 ,*

Eigenvalue Conditions for Lyapunov Stability

The overall objective is to determine simple conditions to classify the continuous-time homogeneous LTI system

$$\dot{x} = Ax \quad x \in \mathbb{R}^n$$

in terms of its Lyapunov stability, *without explicitly computing the solution to the system.*

Theorem (Eigenvalue conditions)

The system (H-CLTI) is

- 1 *marginally stable if and only if all the eigenvalues of A have negative or zero real parts and all the Jordan blocks corresponding to eigenvalues with zero real parts are 1×1 ,*
- 2 *asymptotically stable if and only if all the eigenvalues of A have strictly negative real parts,*

Eigenvalue Conditions for Lyapunov Stability

The overall objective is to determine simple conditions to classify the continuous-time homogeneous LTI system

$$\dot{x} = Ax \quad x \in \mathbb{R}^n$$

in terms of its Lyapunov stability, *without explicitly computing the solution to the system.*

Theorem (Eigenvalue conditions)

The system (H-CLTI) is

- 1 *marginally stable if and only if all the eigenvalues of A have negative or zero real parts and all the Jordan blocks corresponding to eigenvalues with zero real parts are 1×1 ,*
- 2 *asymptotically stable if and only if all the eigenvalues of A have strictly negative real parts,*
- 3 *unstable if and only if at least one eigenvalue of A has a positive real part or zero real part, but the corresponding Jordan block is larger than 1×1 .*

Eigenvalue Conditions for Lyapunov Stability

Asymptotic and Exponential stability of LTI systems

When all the eigenvalues of A have strictly negative real parts, all entries of e^{At} converge to zero exponentially fast, and therefore $\|e^{At}\|$ converges to zero exponentially fast (for every matrix norm); i.e., there exist constants $c, \lambda > 0$ such that

$$\|e^{At}\| \leq ce^{-\lambda t} \quad \forall t \in \mathbb{R}$$

Eigenvalue Conditions for Lyapunov Stability

Asymptotic and Exponential stability of LTI systems

When all the eigenvalues of A have strictly negative real parts, all entries of e^{At} converge to zero exponentially fast, and therefore $\|e^{At}\|$ converges to zero exponentially fast (for every matrix norm); i.e., there exist constants $c, \lambda > 0$ such that

$$\|e^{At}\| \leq ce^{-\lambda t} \quad \forall t \in \mathbb{R}$$

In this case, for a submultiplicative norm, we have

$$\|x(t)\| = \|e^{A(t-t_0)}x_0\| \leq \|e^{A(t-t_0)}\| \|x_0\| \leq ce^{-\lambda(t-t_0)} \|x_0\|, \quad \forall t \in \mathbb{R}$$

This means that asymptotic stability and exponential stability are *equivalent concepts* for LTI systems

Eigenvalue Conditions for Lyapunov Stability

Asymptotic and Exponential stability of LTI systems

When all the eigenvalues of A have strictly negative real parts, all entries of e^{At} converge to zero exponentially fast, and therefore $\|e^{At}\|$ converges to zero exponentially fast (for every matrix norm); i.e., there exist constants $c, \lambda > 0$ such that

$$\|e^{At}\| \leq ce^{-\lambda t} \quad \forall t \in \mathbb{R}$$

In this case, for a submultiplicative norm, we have

$$\|x(t)\| = \|e^{A(t-t_0)}x_0\| \leq \|e^{A(t-t_0)}\| \|x_0\| \leq ce^{-\lambda(t-t_0)} \|x_0\|, \quad \forall t \in \mathbb{R}$$

This means that asymptotic stability and exponential stability are *equivalent concepts* for LTI systems

Attention!

These conditions do not generalize to time-varying systems. One can find matrix-valued signals $A(t)$ that are stability matrices for every fixed $t \geq 0$, but the time-varying system $\dot{x} = A(t)x$ is not even stable.

Lyapunov Stability Theorem

The Lyapunov stability theorem provides an alternative condition to check whether or not the CT homogeneous LTI system is asymptotically stable.

Lyapunov Stability Theorem

Theorem (Lyapunov stability)

The following conditions are equivalent:

- 1 *The system (H-CLTI) is asymptotically stable.*
- 2 *The system (H-CLTI) is exponentially stable.*
- 3 *All the eigenvalues of A have strictly negative real parts.*
- 4 *For every symmetric positive-definite matrix Q , there exists a unique solution P to the following Lyapunov equation*

$$A'P + PA = -Q. \quad (\text{Lyapunov Eq.})$$

Moreover, P is symmetric and positive-definite.

- 5 *There exists a symmetric positive-definite matrix P for which the following Lyapunov matrix inequality holds:*

$$A'P + PA < 0. \quad (\text{LMI})$$

Lyapunov Stability Theorem

Theorem (Lyapunov stability)

The following conditions are equivalent:

- 1 The system (H-CLTI) is asymptotically stable.
- 2 The system (H-CLTI) is exponentially stable.
- 3 All the eigenvalues of A have strictly negative real parts.
- 4 For every symmetric positive-definite matrix Q , there exists a unique solution P to the following Lyapunov equation


$$A'P + PA = -Q. \quad (\text{Lyapunov Eq.})$$

Moreover, P is symmetric and positive-definite.

- 5 There exists a symmetric positive-definite matrix P for which the following Lyapunov matrix inequality holds:

$$A'P + PA < 0. \quad (\text{LMI})$$

Logical overview of the proof.



Proof: 2 \implies 4

We claim that the unique solution to (Lyapunov Eq.) is given by

$$P = \int_0^{\infty} e^{A't} Q e^{At} dt. \quad (2)$$

Proof: 2 \implies 4

We claim that the unique solution to (Lyapunov Eq.) is given by

$$P = \int_0^{\infty} e^{A't} Q e^{At} dt. \quad (2)$$

To verify that this is so, four steps are needed.

Proof: 2 \implies 4

We claim that the unique solution to (Lyapunov Eq.) is given by

$$P = \int_0^{\infty} e^{A't} Q e^{At} dt. \quad (2)$$

To verify that this is so, four steps are needed.

- 1 The (improper) integral in (2) is well defined (i.e., it is finite)
- 2 The matrix P in (2) solves the equation (Lyapunov Eq.)
- 3 The matrix P in (2) is symmetric and positive-definite
- 4 No other matrix solves this equation

Proof: 2 \implies 4

We claim that the unique solution to (Lyapunov Eq.) is given by

$$P = \int_0^{\infty} e^{A't} Q e^{At} dt. \quad (2)$$

To verify that this is so, four steps are needed.

- 1 Well-defined: This is a consequence of the fact that the system (H-CLTI) is exponentially stable, and therefore $\|e^{A't} Q e^{At}\|$ converges to zero exponentially fast as $t \rightarrow \infty$. Because of this, the (improper) integral is absolutely convergent.

Proof: 2 \implies 4

We claim that the unique solution to (Lyapunov Eq.) is given by

$$P = \int_0^{\infty} e^{A't} Q e^{At} dt. \quad (2)$$

To verify that this is so, four steps are needed.

- 1 Well-defined: This is a consequence of the fact that the system (H-CLTI) is exponentially stable, and therefore $\|e^{A't} Q e^{At}\|$ converges to zero exponentially fast as $t \rightarrow \infty$. Because of this, the (improper) integral is absolutely convergent.
- 2 (2) solves (Lyapunov Eq.): Compute

$$A'P + PA = \int_0^{\infty} (A' e^{A't} Q e^{At} + e^{A't} Q e^{At} A) dt.$$

Proof: 2 \implies 4

We claim that the unique solution to (Lyapunov Eq.) is given by

$$P = \int_0^{\infty} e^{A't} Q e^{At} dt. \quad (2)$$

To verify that this is so, four steps are needed.

① Well-defined: This is a consequence of the fact that the system (H-CLTI) is exponentially stable, and therefore $\|e^{A't} Q e^{At}\|$ converges to zero exponentially fast as $t \rightarrow \infty$. Because of this, the (improper) integral is absolutely convergent.

② (2) solves (Lyapunov Eq.): Compute

$$A'P + PA = \int_0^{\infty} \left(A' e^{A't} Q e^{At} + e^{A't} Q e^{At} A \right) dt.$$

But

$$\frac{d}{dt} \left(e^{A't} Q e^{At} \right) = A' e^{A't} Q e^{At} + e^{A't} Q e^{At} A,$$

Proof: 2 \implies 4

We claim that the unique solution to (Lyapunov Eq.) is given by

$$P = \int_0^{\infty} e^{A't} Q e^{At} dt. \quad (2)$$

To verify that this is so, four steps are needed.

① Well-defined: This is a consequence of the fact that the system (H-CLTI) is exponentially stable, and therefore $\|e^{A't} Q e^{At}\|$ converges to zero exponentially fast as $t \rightarrow \infty$. Because of this, the (improper) integral is absolutely convergent.

② (2) solves (Lyapunov Eq.): Compute

$$A'P + PA = \int_0^{\infty} \left(A' e^{A't} Q e^{At} + e^{A't} Q e^{At} A \right) dt.$$

But

$$\frac{d}{dt} \left(e^{A't} Q e^{At} \right) = A' e^{A't} Q e^{At} + e^{A't} Q e^{At} A,$$

therefore

$$\begin{aligned} A'P + PA &= \int_0^{\infty} \frac{d}{dt} \left(e^{A't} Q e^{At} \right) dt = \left[e^{A't} Q e^{At} \right]_0^{\infty} \\ &= \left(\lim_{t \rightarrow \infty} e^{A't} Q e^{At} \right) - e^{A'0} Q e^{A0}. \end{aligned}$$

Equation (Lyapunov Eq.) follows from this and the facts that $\lim_{t \rightarrow \infty} e^{At} = 0$ because of asymptotic stability and that $e^{A0} = I$.

Proof: $2 \implies 4$

- ③ Symmetric and positive-definite:

③ Symmetric and positive-definite:

$$P' = \int_0^{\infty} (e^{A't} Q e^{At})' dt = \int_0^{\infty} (e^{At})' Q' (e^{A't})' dt = \int_0^{\infty} e^{A't} Q e^{At} dt = P.$$

3 Symmetric and positive-definite:

$$P' = \int_0^\infty (e^{A't} Q e^{At})' dt = \int_0^\infty (e^{At})' Q' (e^{A't})' dt = \int_0^\infty e^{A't} Q e^{At} dt = P.$$

For positive-definiteness, take an arbitrary (constant) vector $z \in \mathbb{R}^n$ and compute

$$z' P z = \int_0^\infty z' e^{A't} Q e^{At} z dt = \int_0^\infty w(t)' Q w(t) dt,$$

where $w(t) = e^{At} z, \forall t \geq 0$.

3 Symmetric and positive-definite:

$$P' = \int_0^\infty (e^{A't} Q e^{At})' dt = \int_0^\infty (e^{At})' Q' (e^{A't})' dt = \int_0^\infty e^{A't} Q e^{At} dt = P.$$

For positive-definiteness, take an arbitrary (constant) vector $z \in \mathbb{R}^n$ and compute

$$z' P z = \int_0^\infty z' e^{A't} Q e^{At} z dt = \int_0^\infty w(t)' Q w(t) dt,$$

where $w(t) = e^{At} z, \forall t \geq 0$. Since Q is positive-definite, we conclude that $z' P z \geq 0$.

3 Symmetric and positive-definite:

$$P' = \int_0^{\infty} (e^{A't} Q e^{At})' dt = \int_0^{\infty} (e^{At})' Q' (e^{A't})' dt = \int_0^{\infty} e^{A't} Q e^{At} dt = P.$$

For positive-definiteness, take an arbitrary (constant) vector $z \in \mathbb{R}^n$ and compute

$$z' P z = \int_0^{\infty} z' e^{A't} Q e^{At} z dt = \int_0^{\infty} w(t)' Q w(t) dt,$$

where $w(t) = e^{At} z, \forall t \geq 0$. Since Q is positive-definite, we conclude that $z' P z \geq 0$. Moreover,

$$z' P z = 0 \implies \int_0^{\infty} w(t)' Q w(t) dt = 0,$$

which can only happen if $w(t) = e^{At} z = 0, \forall t \geq 0$, from which one concludes that $z = 0$, because e^{At} is nonsingular. Therefore P is positive-definite.

Proof: $2 \implies 4$

④ Uniqueness:

Proof: 2 \implies 4

- ④ Uniqueness: Assume there exists another solution \bar{P} to (Lyapunov Eq.), i.e.,

$$A'P + PA = -Q, \quad \text{and} \quad A'\bar{P} + \bar{P}A = -Q$$

Proof: 2 \implies 4

- ④ Uniqueness: Assume there exists another solution \bar{P} to (Lyapunov Eq.), i.e.,

$$A'P + PA = -Q, \quad \text{and} \quad A'\bar{P} + \bar{P}A = -Q$$

Then

$$A'(P - \bar{P}) + (P - \bar{P})A = 0.$$

Proof: 2 \implies 4

- ④ Uniqueness: Assume there exists another solution \bar{P} to (Lyapunov Eq.), i.e.,

$$A'P + PA = -Q, \quad \text{and} \quad A'\bar{P} + \bar{P}A = -Q$$

Then

$$A'(P - \bar{P}) + (P - \bar{P})A = 0.$$

Pre-multiplying and post-multiplying by $e^{A't}$ and e^{At} , respectively, we get

$$e^{A't}A'(P - \bar{P})e^{At} + e^{A't}(P - \bar{P})Ae^{At} = 0, \quad \forall t \geq 0.$$

- ④ Uniqueness: Assume there exists another solution \bar{P} to (Lyapunov Eq.), i.e.,

$$A'P + PA = -Q, \quad \text{and} \quad A'\bar{P} + \bar{P}A = -Q$$

Then

$$A'(P - \bar{P}) + (P - \bar{P})A = 0.$$

Pre-multiplying and post-multiplying by $e^{A't}$ and e^{At} , respectively, we get

$$e^{A't}A'(P - \bar{P})e^{At} + e^{A't}(P - \bar{P})Ae^{At} = 0, \quad \forall t \geq 0.$$

On the other hand,

$$\frac{d}{dt} \left(e^{A't}(P - \bar{P})e^{At} \right) = e^{A't}A'(P - \bar{P})e^{At} + e^{A't}(P - \bar{P})Ae^{At} = 0$$

and therefore $e^{A't}(P - \bar{P})e^{At}$ must remain constant for all times. But, because of stability, this quantity must converge to zero as $t \rightarrow \infty$, so it must be always zero. Since e^{At} is nonsingular, this is only if $P = \bar{P}$.

Lyapunov Stability Theorem

Theorem (Lyapunov stability)

The following conditions are equivalent:

- 1 The system (H-CLTI) is asymptotically stable.
- 2 The system (H-CLTI) is exponentially stable.
- 3 All the eigenvalues of A have strictly negative real parts.
- 4 For every symmetric positive-definite matrix Q , there exists a unique solution P to the following Lyapunov equation


$$A'P + PA = -Q. \quad (\text{Lyapunov Eq.})$$

Moreover, P is symmetric and positive-definite.

- 5 There exists a symmetric positive-definite matrix P for which the following Lyapunov matrix inequality holds:

$$A'P + PA < 0. \quad (\text{LMI})$$

Logical overview of the proof.



Proof: 5 \implies 2

Let P be a symmetric positive-definite matrix for which (LMI) holds and let

$$Q = -(A'P + PA) > 0.$$

Proof: 5 \implies 2

Let P be a symmetric positive-definite matrix for which (LMI) holds and let

$$Q = -(A'P + PA) > 0.$$

Consider an arbitrary solution to H-CLTI system, and define the scalar signal

$$v(t) = x'(t)Px(t) \geq 0, \quad \forall t \geq 0.$$

Proof: 5 \implies 2

Let P be a symmetric positive-definite matrix for which (LMI) holds and let

$$Q = -(A'P + PA) > 0.$$

Consider an arbitrary solution to H-CLTI system, and define the scalar signal

$$v(t) = x'(t)Px(t) \geq 0, \quad \forall t \geq 0.$$

Taking derivatives, we obtain

$$\dot{v} = \dot{x}'Px + x'P\dot{x} = x'(A'P + PA)x = -x'Qx \leq 0, \quad \forall t \geq 0. \quad (3)$$

Therefore, $v(t)$ is a nonincreasing signal

Proof: 5 \implies 2

Let P be a symmetric positive-definite matrix for which (LMI) holds and let

$$Q = -(A'P + PA) > 0.$$

Consider an arbitrary solution to H-CLTI system, and define the scalar signal

$$v(t) = x'(t)Px(t) \geq 0, \quad \forall t \geq 0.$$

Taking derivatives, we obtain

$$\dot{v} = \dot{x}'Px + x'P\dot{x} = x'(A'P + PA)x = -x'Qx \leq 0, \quad \forall t \geq 0. \quad (3)$$

Therefore, $v(t)$ is a nonincreasing signal, and we get

$$v(t) = x'(t)Px(t) \leq v(0) = x'(0)Px(0), \quad \forall t \geq 0$$

Proof: 5 \implies 2

Let P be a symmetric positive-definite matrix for which (LMI) holds and let

$$Q = -(A'P + PA) > 0.$$

Consider an arbitrary solution to H-CLTI system, and define the scalar signal

$$v(t) = x'(t)Px(t) \geq 0, \quad \forall t \geq 0.$$

Taking derivatives, we obtain

$$\dot{v} = \dot{x}'Px + x'P\dot{x} = x'(A'P + PA)x = -x'Qx \leq 0, \quad \forall t \geq 0. \quad (3)$$

Therefore, $v(t)$ is a nonincreasing signal, and we get

$$v(t) = x'(t)Px(t) \leq v(0) = x'(0)Px(0), \quad \forall t \geq 0$$

But since $v = x'Px \geq \lambda_{\min}[P]\|x\|^2$

Proof: 5 \implies 2

Let P be a symmetric positive-definite matrix for which (LMI) holds and let

$$Q = -(A'P + PA) > 0.$$

Consider an arbitrary solution to H-CLTI system, and define the scalar signal

$$v(t) = x'(t)Px(t) \geq 0, \quad \forall t \geq 0.$$

Taking derivatives, we obtain

$$\dot{v} = \dot{x}'Px + x'P\dot{x} = x'(A'P + PA)x = -x'Qx \leq 0, \quad \forall t \geq 0. \quad (3)$$

Therefore, $v(t)$ is a nonincreasing signal, and we get

$$v(t) = x'(t)Px(t) \leq v(0) = x'(0)Px(0), \quad \forall t \geq 0$$

But since $v = x'Px \geq \lambda_{\min}[P]\|x\|^2$, we conclude that

$$\|x\|^2 \leq \frac{x'(t)Px(t)}{\lambda_{\min}[P]} = \frac{v(t)}{\lambda_{\min}[P]} \leq \frac{v(0)}{\lambda_{\min}[P]}, \quad \forall t \geq 0, \quad (4)$$

which means that the H-CLTI system is stable.

Proof: 5 \implies 2

To verify that it is actually exponentially stable, we go back to (3) and, using the facts that $x'Qx \geq \lambda_{\min}[Q]\|x\|^2$ and that $v = x'Px \leq \lambda_{\max}[P]\|x\|^2$

Proof: 5 \implies 2

To verify that it is actually exponentially stable, we go back to (3) and, using the facts that $x'Qx \geq \lambda_{\min}[Q]\|x\|^2$ and that $v = x'Px \leq \lambda_{\max}[P]\|x\|^2$, we conclude that

$$\dot{v} = -x'Qx \leq -\lambda_{\min}[Q]\|x\|^2 \leq -\frac{\lambda_{\min}[Q]}{\lambda_{\max}[P]}v, \quad \forall t \geq 0 \quad (5)$$

Proof: 5 \implies 2

To verify that it is actually exponentially stable, we go back to (3) and, using the facts that $x'Qx \geq \lambda_{\min}[Q]\|x\|^2$ and that $v = x'Px \leq \lambda_{\max}[P]\|x\|^2$, we conclude that

$$\dot{v} = -x'Qx \leq -\lambda_{\min}[Q]\|x\|^2 \leq -\frac{\lambda_{\min}[Q]}{\lambda_{\max}[P]}v, \quad \forall t \geq 0 \quad (5)$$

To proceed, we need the Comparison lemma.

Theorem (Comparison Lemma)

Let $v(t)$ be a differentiable scalar signal for which

$$\dot{v}(t) \leq \mu v(t), \quad \forall t \geq t_0$$

for some constant $\mu \in \mathbb{R}$. Then

$$v(t) \leq e^{\mu(t-t_0)}v(t_0), \quad \forall t \geq t_0.$$

Proof: 5 \implies 2

To verify that it is actually exponentially stable, we go back to (3) and, using the facts that $x'Qx \geq \lambda_{\min}[Q]\|x\|^2$ and that $v = x'Px \leq \lambda_{\max}[P]\|x\|^2$, we conclude that

$$\dot{v} = -x'Qx \leq -\lambda_{\min}[Q]\|x\|^2 \leq -\frac{\lambda_{\min}[Q]}{\lambda_{\max}[P]}v, \quad \forall t \geq 0 \quad (5)$$

To proceed, we need the Comparison lemma.

Theorem (Comparison Lemma)

Let $v(t)$ be a differentiable scalar signal for which

$$\dot{v}(t) \leq \mu v(t), \quad \forall t \geq t_0$$

for some constant $\mu \in \mathbb{R}$. Then

$$v(t) \leq e^{\mu(t-t_0)}v(t_0), \quad \forall t \geq t_0.$$

Applying the Comparison lemma to (5), we conclude that

$$v(t) \leq e^{-\lambda(t-t_0)}v(t_0), \quad \forall t \geq 0, \quad \lambda \triangleq -\frac{\lambda_{\min}[Q]}{\lambda_{\max}[P]},$$

which shows that $v(t)$ converges to zero exponentially fast and so does $\|x(t)\|$ [see (4)].

Comparison Lemma

Theorem (Comparison Lemma)

Let $v(t)$ be a differentiable scalar signal for which

$$\dot{v}(t) \leq \mu v(t), \quad \forall t \geq t_0$$

for some constant $\mu \in \mathbb{R}$. Then

$$v(t) \leq e^{\mu(t-t_0)}v(t_0), \quad \forall t \geq t_0. \quad (6)$$

Proof.

Define a new signal $u(t)$ as follows:

$$u(t) \triangleq e^{-\mu(t-t_0)}v(t), \quad \forall t \geq t_0.$$

Comparison Lemma

Theorem (Comparison Lemma)

Let $v(t)$ be a differentiable scalar signal for which

$$\dot{v}(t) \leq \mu v(t), \quad \forall t \geq t_0$$

for some constant $\mu \in \mathbb{R}$. Then

$$v(t) \leq e^{\mu(t-t_0)} v(t_0), \quad \forall t \geq t_0. \quad (6)$$

Proof.

Define a new signal $u(t)$ as follows:

$$u(t) \triangleq e^{-\mu(t-t_0)} v(t), \quad \forall t \geq t_0.$$

Taking derivative, we conclude that

$$\dot{u} = -\mu e^{-\mu(t-t_0)} v(t) + e^{-\mu(t-t_0)} \dot{v}(t) \leq -\mu e^{-\mu(t-t_0)} v(t) + \mu e^{-\mu(t-t_0)} v(t) = 0$$

Comparison Lemma

Theorem (Comparison Lemma)

Let $v(t)$ be a differentiable scalar signal for which

$$\dot{v}(t) \leq \mu v(t), \quad \forall t \geq t_0$$

for some constant $\mu \in \mathbb{R}$. Then

$$v(t) \leq e^{\mu(t-t_0)} v(t_0), \quad \forall t \geq t_0. \quad (6)$$

Proof.

Define a new signal $u(t)$ as follows:

$$u(t) \triangleq e^{-\mu(t-t_0)} v(t), \quad \forall t \geq t_0.$$

Taking derivative, we conclude that

$$\dot{u} = -\mu e^{-\mu(t-t_0)} v(t) + e^{-\mu(t-t_0)} \dot{v}(t) \leq -\mu e^{-\mu(t-t_0)} v(t) + \mu e^{-\mu(t-t_0)} v(t) = 0$$

Therefore u is nonincreasing, and we conclude that

$$u(t) = e^{-\mu(t-t_0)} v(t) \leq u(t_0) = v(t_0), \quad \forall t \geq t_0$$

which is precisely equivalent to (6). □

Lyapunov Stability Theorem

Theorem (Lyapunov stability)

The following conditions are equivalent:

- 1 The system (H-CLTI) is asymptotically stable.
- 2 The system (H-CLTI) is exponentially stable.
- 3 All the eigenvalues of A have strictly negative real parts.
- 4 For every symmetric positive-definite matrix Q , there exists a unique solution P to the following Lyapunov equation


$$A'P + PA = -Q. \quad (\text{Lyapunov Eq.})$$

Moreover, P is symmetric and positive-definite.

- 5 There exists a symmetric positive-definite matrix P for which the following Lyapunov matrix inequality holds:

$$A'P + PA < 0. \quad (\text{LMI})$$

Logical overview of the proof.



Discrete-time case

Consider now the following discrete-time LTV system

$$x(t+1) = A(t)x(t) + B(t)u(t), \quad y(t) = C(t)x(t) + D(t)u(t). \quad (\text{DLTV})$$

Definition (Lyapunov stability)

The system (DLTV) is said to be

- 1 (marginally) stable in the sense of Lyapunov or internally stable whenever, for every initial condition $x(t_0) = x_0 \in \mathbb{R}^n$, the homogeneous state response

$$x(t) = \phi(t, t_0)x_0, \quad \forall t \geq t_0$$

is uniformly bounded,

- 2 asymptotically stable (in the Lyapunov sense) whenever, in addition, for every initial condition $x(t_0) = x_0 \in \mathbb{R}^n$, we have $x(t) \rightarrow 0$ as $t \rightarrow \infty$,
- 3 exponentially stable whenever, in addition, there exist constants $c > 0, 0 < \lambda < 1$ such that, for every initial condition $x(t_0) = x_0 \in \mathbb{R}^n$,

$$\|x(t)\| \leq c\lambda^{t-t_0}\|x(t_0)\|, \quad \forall t \geq t_0,$$

- 4 unstable whenever it is not marginally stable in the Lyapunov sense.

Discrete-time case

The matrices $B(\bullet)$, $C(\bullet)$, and $D(\bullet)$ play no role in this definition; therefore, one often simply talks about the Lyapunov stability of the homogeneous system

$$x(t+1) = A(t)x, \quad x \in \mathbb{R}^n. \quad (\text{H-DLTV})$$

Theorem (Eigenvalue conditions)

The discrete-time homogeneous LTI system

$$x^+ = Ax, \quad x \in \mathbb{R}^n \quad (\text{H-DLTI})$$

is

- 1 *marginally stable if and only if all the eigenvalues of A have magnitude smaller than or equal to 1 and all the Jordan blocks corresponding to eigenvalues with magnitude equal to 1 are 1×1 ,*
- 2 *asymptotically and exponentially stable if and only if all the eigenvalues of A have magnitude strictly smaller than 1, or*
- 3 *unstable if and only if at least one eigenvalue of A has magnitude larger than 1 or magnitude equal to 1, but the corresponding Jordan block is larger than 1×1 .*

Theorem (Lyapunov stability in discrete time)

The following five conditions are equivalent:

- 1 *The system (H-DLTI) is asymptotically stable.*
- 2 *The system (H-DLTI) is exponentially stable.*
- 3 *All the eigenvalues of A have magnitude strictly smaller than 1.*
- 4 *For every symmetric positive-definite matrix Q , there exists a unique solution P to the following Stein equation (more commonly known as the discrete-time Lyapunov equation)*

$$A'PA - P = -Q. \quad (\text{DT Lyapunov Eq.})$$

Moreover, P is symmetric and positive-definite.

- 5 *There exists a symmetric positive-definite matrix P for which the following Lyapunov matrix inequality holds:*


$$A'PA - P < 0. \quad (\text{DT LMI})$$

Lyapunov Stability Tests for LTI systems

Definition		Continuous time		Discrete time	
		Eigenvalue test	Lyapunov test	Eigenvalue test	Lyapunov test
Unstable	For some $t_0, x(t_0)$, $x(t)$ can be unbounded.	For some $\lambda_i[A]$, $\Re\lambda_i[A] > 0$ or $\Re\lambda_i[A] = 0$ with Jordan block larger than 1×1 .		For some $\lambda_i[A]$, $ \lambda_i[A] > 1$ or $ \lambda_i[A] = 1$ with Jordan block larger than 1×1 .	
Marginally stable	For every $t_0, x(t_0)$, $x(t)$ is uniformly bounded.	For every $\lambda_i[A]$, $\Re\lambda_i[A] < 0$ or $\Re\lambda_i[A] = 0$ with 1×1 Jordan block.		For every $\lambda_i[A]$, $ \lambda_i[A] < 1$ or $ \lambda_i[A] = 1$ with 1×1 Jordan block.	
Asymptotically stable	For every $t_0, x(t_0)$, $\lim_{t \rightarrow \infty} x(t) = 0$.	For every $\lambda_i[A]$, $\Re\lambda_i[A] < 0$.	For every $Q > 0$, $\exists P = P' > 0$: $A'P + PA = -Q$	For every $\lambda_i[A]$, $ \lambda_i[A] < 1$.	For every $Q > 0$, $\exists P = P' > 0$: $A'PA - P = -Q$
Exponentially stable	$\exists c, \lambda > 0$: for every $t_0, x(t_0)$, $\ x(t)\ \leq ce^{-\lambda t} \ x(t_0)\ , \forall t \geq t_0$.		or $\exists P = P' > 0$: $A'P + PA < 0$.		or $\exists P = P' > 0$: $A'PA - P < 0$.

Example: Inverted Pendulum

Consider the inverted pendulum and assume that $u = T$ and $y = \theta$ are its input and output, respectively.



From Newton's law,

$$m\ell^2\ddot{\theta} = mg\ell \sin\theta - b\dot{\theta} + T,$$

where T denotes a torque applied at the base and g is the gravitational acceleration.

Example: Inverted Pendulum

At equilibrium point $\theta = \pi$

$$A = \begin{bmatrix} 0 & 1 \\ -\frac{g}{\ell} & -\frac{b}{m\ell^2} \end{bmatrix}, B = \begin{bmatrix} 0 \\ 1 \end{bmatrix}, C = [1 \quad 0]$$

The eigenvalues of A are given by

$$\det(\lambda I - A) = \lambda \left(\lambda + \frac{b}{m\ell^2} \right) + \frac{g}{\ell} = 0 \Leftrightarrow \lambda = -\frac{b}{2m\ell^2} \pm \sqrt{\left(\frac{b}{2m\ell^2} \right)^2 - \frac{g}{\ell}}$$

Example: Inverted Pendulum

At equilibrium point $\theta = \pi$

$$A = \begin{bmatrix} 0 & 1 \\ -\frac{g}{\ell} & -\frac{b}{m\ell^2} \end{bmatrix}, B = \begin{bmatrix} 0 \\ 1 \end{bmatrix}, C = [1 \quad 0]$$

The eigenvalues of A are given by

$$\det(\lambda I - A) = \lambda \left(\lambda + \frac{b}{m\ell^2} \right) + \frac{g}{\ell} = 0 \Leftrightarrow \lambda = -\frac{b}{2m\ell^2} \pm \sqrt{\left(\frac{b}{2m\ell^2} \right)^2 - \frac{g}{\ell}}$$

and therefore the linearized system is exponentially stable.

This is consistent with the obvious fact that in the absence of u the (nonlinear) pendulum converges to this equilibrium.

Example: Inverted Pendulum

At equilibrium point $\theta = \pi$

$$A = \begin{bmatrix} 0 & 1 \\ -\frac{g}{\ell} & -\frac{b}{m\ell^2} \end{bmatrix}, B = \begin{bmatrix} 0 \\ 1 \end{bmatrix}, C = [1 \quad 0]$$

The eigenvalues of A are given by

$$\det(\lambda I - A) = \lambda \left(\lambda + \frac{b}{m\ell^2} \right) + \frac{g}{\ell} = 0 \Leftrightarrow \lambda = -\frac{b}{2m\ell^2} \pm \sqrt{\left(\frac{b}{2m\ell^2} \right)^2 - \frac{g}{\ell}}$$

and therefore the linearized system is exponentially stable.

This is consistent with the obvious fact that in the absence of u the (nonlinear) pendulum converges to this equilibrium.

$$P = \begin{bmatrix} \frac{b^2 + g^2 \ell^2 m^2 + g \ell^3 m^2}{2bg\ell m} & \frac{\ell}{2g} \\ \frac{\ell}{2g} & \frac{\ell^2 m(g + \ell)}{2bg} \end{bmatrix}$$

Example: Inverted Pendulum

At equilibrium point $\theta = 0$

$$A = \begin{bmatrix} 0 & 1 \\ \frac{g}{\ell} & -\frac{b}{m\ell^2} \end{bmatrix}, B = \begin{bmatrix} 0 \\ 1 \end{bmatrix}, C = [1 \quad 0]$$

The eigenvalues of A are given by

$$\det(\lambda I - A) = \lambda \left(\lambda + \frac{b}{m\ell^2} \right) - \frac{g}{\ell} = 0 \Leftrightarrow \lambda = -\frac{b}{2m\ell^2} \pm \sqrt{\left(\frac{b}{2m\ell^2} \right)^2 + \frac{g}{\ell}}$$

and therefore the linearized system is exponentially unstable, because

$$-\frac{b}{2m\ell^2} + \sqrt{\left(\frac{b}{2m\ell^2} \right)^2 + \frac{g}{\ell}} > 0.$$

This is consistent with the obvious fact that in the absence of u the (nonlinear) pendulum does not naturally move up to the upright position if it starts away from it. However, one can certainly make it move up by applying some torque u .

$$P = \begin{bmatrix} -\frac{b^2 + g^2 \ell^2 m^2 - g \ell^3 m^2}{2bg\ell m} & -\frac{\ell}{2g} \\ -\frac{\ell}{2g} & \frac{\ell^2 m(g - \ell)}{2bg} \end{bmatrix}$$

Bounded-Input, Bounded Output Stability

Internal or Lyapunov stability is concerned only with the effect of the initial conditions on the response of the system.

Bounded-Input, Bounded Output Stability

Internal or Lyapunov stability is concerned only with the effect of the initial conditions on the response of the system.

We now consider a distinct notion of stability that *ignores* initial conditions and is concerned only with the effect of the input on the forced response.

Bounded-Input, Bounded Output Stability

Internal or Lyapunov stability is concerned only with the effect of the initial conditions on the response of the system.

We now consider a distinct notion of stability that *ignores* initial conditions and is concerned only with the effect of the input on the forced response.

We shall see that for LTI systems these two notions of stability are closely related.

Consider the continuous-time LTV system

$$\dot{x} = A(t)x + B(t)u, \quad y = C(t)x + D(t)u, \quad x \in \mathbb{R}^n, u \in \mathbb{R}^k, y \in \mathbb{R}^m$$

The forced response of this system is given by

$$y_f(t) = \int_0^t C(t)\phi(t, \tau)B(\tau)u(\tau)d\tau + D(t)u(t).$$

Bounded-Input, Bounded Output Stability

Internal or Lyapunov stability is concerned only with the effect of the initial conditions on the response of the system.

We now consider a distinct notion of stability that *ignores* initial conditions and is concerned only with the effect of the input on the forced response.

We shall see that for LTI systems these two notions of stability are closely related.

Consider the continuous-time LTV system

$$\dot{x} = A(t)x + B(t)u, \quad y = C(t)x + D(t)u, \quad x \in \mathbb{R}^n, u \in \mathbb{R}^k, y \in \mathbb{R}^m$$

The forced response of this system is given by

$$y_f(t) = \int_0^t C(t)\phi(t, \tau)B(\tau)u(\tau)d\tau + D(t)u(t).$$

Definition (BIBO stability)

The system (CLTV) is said to be (*uniformly*) *BIBO stable* if there exists a finite constant g^1 such that, for every input u , its forced response y_f satisfies

$$\sup_{t \in [0, \infty)} \|y_f(t)\| \leq g \sup_{t \in [0, \infty)} \|u(t)\|$$

¹The factor g can be viewed as a system “gain”.

Theorem (Time domain BIBO stability condition)

The following two statements are equivalent.

- 1 *The system (CLTV) is uniformly BIBO stable.*
- 2 *Every entry of $D(t)$ is uniformly bounded¹ and*

$$\sup_{t \geq 0} \int_0^t |g_{ij}(t, \tau)| d\tau < \infty$$

for every entry $g_{ij}(t, \tau)$ of $C(t)\phi(t, \tau)B(\tau)$.

¹A signal $x(t)$ is uniformly bounded if there exists a finite constant c such that $\|x(t)\| \leq c, \forall t \geq 0$.

Proof: 2 \implies 1

Conditions in (1) implies that the gain g is finite.

Proof: 2 \implies 1

Conditions in (1) implies that the gain g is finite.

$$y_f(t) = \int_0^t C(t)\phi(t, \tau)B(\tau)u(\tau)d\tau + D(t)u(t).$$

Proof: 2 \implies 1

Conditions in (1) implies that the gain g is finite.

$$\|y_f(t)\| \leq \int_0^t \|C(t)\phi(t,\tau)B(\tau)\| \|u(\tau)\| d\tau + \|D(t)\| \|u(t)\|, \forall t \geq 0$$

Proof: 2 \implies 1

Conditions in (1) implies that the gain g is finite.

$$\|y_f(t)\| \leq \int_0^t \|C(t)\phi(t,\tau)B(\tau)\| \|u(\tau)\| d\tau + \|D(t)\| \|u(t)\|, \forall t \geq 0$$

Defining

$$\mu \triangleq \sup_{t \in [0, \infty)} \|u(t)\|, \quad \delta \triangleq \sup_{t \in [0, \infty)} \|D(t)\|,$$

we conclude that

$$\|y_f(t)\| \leq \left(\int_0^t \|C(t)\phi(t,\tau)B(\tau)\| d\tau + \delta \right) \mu, \forall t \geq 0$$

Conditions in (1) implies that the gain g is finite.

$$\|y_f(t)\| \leq \int_0^t \|C(t)\phi(t,\tau)B(\tau)\| \|u(\tau)\| d\tau + \|D(t)\| \|u(t)\|, \forall t \geq 0$$

Defining

$$\mu \triangleq \sup_{t \in [0, \infty)} \|u(t)\|, \quad \delta \triangleq \sup_{t \in [0, \infty)} \|D(t)\|,$$

we conclude that

$$\|y_f(t)\| \leq \left(\int_0^t \|C(t)\phi(t,\tau)B(\tau)\| d\tau + \delta \right) \mu, \forall t \geq 0$$

Defining $g \triangleq \sup_{t \geq 0} \int_0^t \|C(t)\phi(t,\tau)B(\tau)\| d\tau + \delta$, this part is proved if g is finite.

Proof: 2 \implies 1

Conditions in (1) implies that the gain g is finite.

$$\|y_f(t)\| \leq \int_0^t \|C(t)\phi(t,\tau)B(\tau)\| \|u(\tau)\| d\tau + \|D(t)\| \|u(t)\|, \forall t \geq 0$$

Defining
$$\mu \triangleq \sup_{t \in [0, \infty)} \|u(t)\|, \quad \delta \triangleq \sup_{t \in [0, \infty)} \|D(t)\|,$$

we conclude that

$$\|y_f(t)\| \leq \left(\int_0^t \|C(t)\phi(t,\tau)B(\tau)\| d\tau + \delta \right) \mu, \forall t \geq 0$$

Defining $g \triangleq \sup_{t \geq 0} \int_0^t \|C(t)\phi(t,\tau)B(\tau)\| d\tau + \delta$, this part is proved if g is finite.
Note that⁴

$$\|C(t)\phi(t,\tau)B(\tau)\| \leq \sum_{i,j} |g_{i,j}(t,\tau)|,$$

⁴this is a consequence of the triangle inequality

Proof: 2 \implies 1

Conditions in (1) implies that the gain g is finite.

$$\|y_f(t)\| \leq \int_0^t \|C(t)\phi(t,\tau)B(\tau)\| \|u(\tau)\| d\tau + \|D(t)\| \|u(t)\|, \forall t \geq 0$$

Defining
$$\mu \triangleq \sup_{t \in [0, \infty)} \|u(t)\|, \quad \delta \triangleq \sup_{t \in [0, \infty)} \|D(t)\|,$$

we conclude that

$$\|y_f(t)\| \leq \left(\int_0^t \|C(t)\phi(t,\tau)B(\tau)\| d\tau + \delta \right) \mu, \forall t \geq 0$$

Defining $g \triangleq \sup_{t \geq 0} \int_0^t \|C(t)\phi(t,\tau)B(\tau)\| d\tau + \delta$, this part is proved if g is finite. Note that⁴

$$\|C(t)\phi(t,\tau)B(\tau)\| \leq \sum_{i,j} |g_{i,j}(t,\tau)|,$$

and therefore

$$\int_0^t \|C(t)\phi(t,\tau)B(\tau)\| d\tau \leq \sum_{i,j} \int_0^t |g_{i,j}(t,\tau)| d\tau, \quad \forall t \geq 0.$$

⁴this is a consequence of the triangle inequality

Proof: 2 \implies 1

Conditions in (1) implies that the gain g is finite.

$$\|y_f(t)\| \leq \int_0^t \|C(t)\phi(t, \tau)B(\tau)\| \|u(\tau)\| d\tau + \|D(t)\| \|u(t)\|, \forall t \geq 0$$

Defining

$$\mu \triangleq \sup_{t \in [0, \infty)} \|u(t)\|, \quad \delta \triangleq \sup_{t \in [0, \infty)} \|D(t)\|,$$

we conclude that

$$\|y_f(t)\| \leq \left(\int_0^t \|C(t)\phi(t, \tau)B(\tau)\| d\tau + \delta \right) \mu, \forall t \geq 0$$

Defining $g \triangleq \sup_{t \geq 0} \int_0^t \|C(t)\phi(t, \tau)B(\tau)\| d\tau + \delta$, this part is proved if g is finite. Note that⁴

$$\|C(t)\phi(t, \tau)B(\tau)\| \leq \sum_{i,j} |g_{i,j}(t, \tau)|,$$

and therefore

$$\int_0^t \|C(t)\phi(t, \tau)B(\tau)\| d\tau \leq \sum_{i,j} \int_0^t |g_{i,j}(t, \tau)| d\tau, \quad \forall t \geq 0.$$

Finally

$$g = \sup_{t \geq 0} \int_0^t \|C(t)\phi(t, \tau)B(\tau)\| d\tau + \delta \leq \sup_{t \geq 0} \sum_{i,j} \int_0^t |g_{i,j}(t, \tau)| d\tau + \delta < \infty$$

⁴this is a consequence of the triangle inequality

Time-domain condition for BIBO stability

Theorem (Time domain BIBO stability condition)

The following two statements are equivalent.

- 1 The system (CLTV) is uniformly BIBO stable.
- 2 Every entry of $D(t)$ is uniformly bounded¹ and

$$\sup_{t \geq 0} \int_0^t |g_{ij}(t, \tau)| d\tau < \infty$$

for every entry $g_{ij}(t, \tau)$ of $C(t)\phi(t, \tau)B(\tau)$.

$$y_f(t) = \int_0^t C(t)\phi(t, \tau)B(\tau)u(\tau)d\tau + D(t)u(t).$$

$$\sup_{t \in [0, \infty)} \|y_f(t)\| \leq g \sup_{t \in [0, \infty)} \|u(t)\|$$

¹A signal $x(t)$ is uniformly bounded if there exists a finite constant c such that $\|x(t)\| \leq c, \forall t \geq 0$.

Proof: $1 \implies 2$ OR $\neg 1 \iff \neg 2$

Proof: $1 \implies 2$ OR $\neg 1 \iff \neg 2$

Suppose first that 2 is false because the entry $d_{ij}(\bullet)$ of $D(\bullet)$ is unbounded.

Proof: $1 \implies 2$ OR $\neg 1 \iff \neg 2$

Suppose first that 2 is false because the entry $d_{ij}(\bullet)$ of $D(\bullet)$ is unbounded.

We show next that in this case $\sup_{t \in [0, \infty)} \|y_f(t)\| \leq g \sup_{t \in [0, \infty)} \|u(t)\|$ can be violated no matter what we choose for the finite gain g .

Proof: 1 \implies 2 OR $\neg 1 \iff \neg 2$

Suppose first that 2 is false because the entry $d_{ij}(\bullet)$ of $D(\bullet)$ is unbounded.

We show next that in this case $\sup_{t \in [0, \infty)} \|y_f(t)\| \leq g \sup_{t \in [0, \infty)} \|u(t)\|$ can be violated no matter what we choose for the finite gain g .

To do this, pick an arbitrary time T and consider the following step input:

$$u_T(\tau) \triangleq \begin{cases} 0 & 0 \leq \tau < T \\ e_j & \tau \geq T \end{cases} \quad \forall \tau \geq 0,$$

where $e_j \in \mathbb{R}^k$ is the j th vector in the canonical basis of \mathbb{R}^k .

Proof: 1 \implies 2 OR $\neg 1 \iff \neg 2$

Suppose first that 2 is false because the entry $d_{ij}(\bullet)$ of $D(\bullet)$ is unbounded.

We show next that in this case $\sup_{t \in [0, \infty)} \|y_f(t)\| \leq g \sup_{t \in [0, \infty)} \|u(t)\|$ can be violated no matter what we choose for the finite gain g .

To do this, pick an arbitrary time T and consider the following step input:

$$u_T(\tau) \triangleq \begin{cases} 0 & 0 \leq \tau < T \\ e_j & \tau \geq T \end{cases} \quad \forall \tau \geq 0,$$

where $e_j \in \mathbb{R}^k$ is the j th vector in the canonical basis of \mathbb{R}^k . For this input, the second term of the forced response at time T is exactly

$$y_f(T) = D(T)e_j$$

Proof: $1 \implies 2$ OR $\neg 1 \iff \neg 2$

Suppose first that 2 is false because the entry $d_{ij}(\bullet)$ of $D(\bullet)$ is unbounded.

We show next that in this case $\sup_{t \in [0, \infty)} \|y_f(t)\| \leq g \sup_{t \in [0, \infty)} \|u(t)\|$ can be violated no matter what we choose for the finite gain g .

To do this, pick an arbitrary time T and consider the following step input:

$$u_T(\tau) \triangleq \begin{cases} 0 & 0 \leq \tau < T \\ e_j & \tau \geq T \end{cases} \quad \forall \tau \geq 0,$$

where $e_j \in \mathbb{R}^k$ is the j th vector in the canonical basis of \mathbb{R}^k . For this input, the second term of the forced response at time T is exactly

$$y_f(T) = D(T)e_j$$

We thus have found an input for which

$$\sup_{t \in [0, \infty)} \|u_T(t)\| = 1$$

and

$$\sup_{t \in [0, \infty)} \|y_f(t)\| \geq \|y_f(T)\| = \|D(T)e_j\| \geq |d_{ij}(T)|,$$

where the last inequality results from the fact that the norm of the vector $D(T)e_j$ must be larger than the absolute value of its i th entry, which is precisely $d_{ij}(T)$.

Proof: 1 \implies 2 OR $\neg 1 \iff \neg 2$

Suppose first that 2 is false because the entry $d_{ij}(\bullet)$ of $D(\bullet)$ is unbounded.

We show next that in this case $\sup_{t \in [0, \infty)} \|y_f(t)\| \leq g \sup_{t \in [0, \infty)} \|u(t)\|$ can be violated no matter what we choose for the finite gain g .

To do this, pick an arbitrary time T and consider the following step input:

$$u_T(\tau) \triangleq \begin{cases} 0 & 0 \leq \tau < T \\ e_j & \tau \geq T \end{cases} \quad \forall \tau \geq 0,$$

where $e_j \in \mathbb{R}^k$ is the j th vector in the canonical basis of \mathbb{R}^k . For this input, the second term of the forced response at time T is exactly

$$y_f(T) = D(T)e_j$$

We thus have found an input for which

$$\sup_{t \in [0, \infty)} \|u_T(t)\| = 1$$

and

$$\sup_{t \in [0, \infty)} \|y_f(t)\| \geq \|y_f(T)\| = \|D(T)e_j\| \geq |d_{ij}(T)|,$$

where the last inequality results from the fact that the norm of the vector $D(T)e_j$ must be larger than the absolute value of its i th entry, which is precisely $d_{ij}(T)$. Since $d_{ij}(\bullet)$ is unbounded, we conclude that we can make $\sup_{t \in [0, \infty)} \|y_f(t)\|$ arbitrarily large by using inputs $u_T(\bullet)$ for which $\sup_{t \in [0, \infty)} u_T(t) = 1$, which is not compatible with the existence of a finite gain g . This means that $D(\bullet)$ must be uniformly bounded for a system to be BIBO stable.

Proof: $1 \implies 2$ OR $\neg 1 \iff \neg 2$

Suppose first that 2 is false because

$$\int_0^t |g_{ij}(t, \tau)| d\tau \tag{7}$$

is unbounded for some i and j .

Proof: $1 \implies 2$ OR $\neg 1 \iff \neg 2$

Suppose first that 2 is false because

$$\int_0^t |g_{ij}(t, \tau)| d\tau \tag{7}$$

is unbounded for some i and j .

We show next that in this case $\sup_{t \in [0, \infty)} \|y_f(t)\| \leq g \sup_{t \in [0, \infty)} \|u(t)\|$ can be violated no matter what we choose for the finite gain g .

Proof: $1 \implies 2$ OR $\neg 1 \iff \neg 2$

Suppose first that 2 is false because

$$\int_0^t |g_{ij}(t, \tau)| d\tau \tag{7}$$

is unbounded for some i and j .

We show next that in this case $\sup_{t \in [0, \infty)} \|y_f(t)\| \leq g \sup_{t \in [0, \infty)} \|u(t)\|$ can be violated no matter what we choose for the finite gain g .

To do this, pick an arbitrary time T and consider the following “switching” input:

$$u_T(\tau) \triangleq \begin{cases} +e_j & g_{ij}(t, \tau) \geq 0 \\ -e_j & g_{ij}(t, \tau) < 0 \end{cases} \quad \forall \tau \geq 0.$$

Proof: $1 \implies 2$ OR $\neg 1 \iff \neg 2$

Suppose first that 2 is false because

$$\int_0^t |g_{ij}(t, \tau)| d\tau \tag{7}$$

is unbounded for some i and j .

We show next that in this case $\sup_{t \in [0, \infty)} \|y_f(t)\| \leq g \sup_{t \in [0, \infty)} \|u(t)\|$ can be violated no matter what we choose for the finite gain g .

To do this, pick an arbitrary time T and consider the following “switching” input:

$$u_T(\tau) \triangleq \begin{cases} +e_j & g_{ij}(t, \tau) \geq 0 \\ -e_j & g_{ij}(t, \tau) < 0 \end{cases} \quad \forall \tau \geq 0.$$

For this input, the forced response at time T is

$$y_f(T) = \int_0^T C(T)\phi(T, \tau)B(\tau)u(\tau)d\tau + D(T)u(T),$$

and its i th entry is equal to $\int_0^T |g_{ij}(T, \tau)| d\tau \pm d_{ij}(T)$.

Proof: $1 \implies 2$ OR $\neg 1 \iff \neg 2$

Suppose first that 2 is false because

$$\int_0^t |g_{ij}(t, \tau)| d\tau \quad (7)$$

is unbounded for some i and j .

We show next that in this case $\sup_{t \in [0, \infty)} \|y_f(t)\| \leq g \sup_{t \in [0, \infty)} \|u(t)\|$ can be violated no matter what we choose for the finite gain g .

To do this, pick an arbitrary time T and consider the following “switching” input:

$$u_T(\tau) \triangleq \begin{cases} +e_j & g_{ij}(t, \tau) \geq 0 \\ -e_j & g_{ij}(t, \tau) < 0 \end{cases} \quad \forall \tau \geq 0.$$

For this input, the forced response at time T is

$$y_f(T) = \int_0^T C(T)\phi(T, \tau)B(\tau)u(\tau)d\tau + D(T)u(T),$$

and its i th entry is equal to $\int_0^T |g_{ij}(T, \tau)| d\tau \pm d_{ij}(T)$. We thus have found an input for which

$$\sup_{t \in [0, \infty)} \|u_T(t)\| = 1 \quad \text{and} \quad \sup_{t \in [0, \infty)} \|y_f(t)\| \geq \|y_f(T)\| \geq \left| \int_0^T |g_{ij}(t, \tau)| d\tau \pm d_{ij}(t) \right|.$$

Since (7) is unbounded, also now we conclude that we can make $\sup_{t \in [0, \infty)} \|y_f(t)\|$ arbitrarily large by using inputs $u_T(\bullet)$ for which $\sup_{t \in [0, \infty)} u_T(t) = 1$, which is not compatible with the existence of a finite gain g . This means that condition (2) must hold for a system to be BIBO stable.

Theorem (Time domain BIBO stability condition)

The following two statements are equivalent.

- 1 The system (CLTV) is uniformly BIBO stable.
- 2 Every entry of $D(t)$ is uniformly bounded¹ and

$$\sup_{t \geq 0} \int_0^t |g_{ij}(t, \tau)| d\tau < \infty$$

for every entry $g_{ij}(t, \tau)$ of $C(t)\phi(t, \tau)B(\tau)$.

¹A signal $x(t)$ is uniformly bounded if there exists a finite constant c such that $\|x(t)\| \leq c, \forall t \geq 0$.

Time-Invariant Case

For the time-invariant system

$$\dot{x} = Ax + Bu, \quad y = Cx + Du,$$

we have

$$C\phi(t, \tau)B = Ce^{A(t-\tau)}B.$$

Time-Invariant Case

For the time-invariant system

$$\dot{x} = Ax + Bu, \quad y = Cx + Du,$$

we have

$$C\phi(t, \tau)B = Ce^{A(t-\tau)}B.$$

Therefore, rewriting from the previous definition as

$$\sup_{t \geq 0} \int_0^t |\bar{g}_{ij}(t - \tau)| d\tau < \infty,$$

with the understanding that now $\bar{g}_{ij}(t - \tau)$ denotes the ij th entry of $Ce^{A(t-\tau)}B$.

Time-Invariant Case

For the time-invariant system

$$\dot{x} = Ax + Bu, \quad y = Cx + Du,$$

we have

$$C\phi(t, \tau)B = Ce^{A(t-\tau)}B.$$

Therefore, rewriting from the previous definition as

$$\sup_{t \geq 0} \int_0^t |\bar{g}_{ij}(t - \tau)| d\tau < \infty,$$

with the understanding that now $\bar{g}_{ij}(t - \tau)$ denotes the ij th entry of $Ce^{A(t-\tau)}B$. Making the change of variable $\rho \triangleq t - \tau$, we conclude that

$$\sup_{t \geq 0} \int_0^t |\bar{g}_{ij}(t - \tau)| d\tau = \sup_{t \geq 0} \int_0^t |\bar{g}_{ij}(\rho)| d\rho = \int_0^\infty |\bar{g}_{ij}(\rho)| d\rho.$$

Time-Invariant Case

For the time-invariant system

$$\dot{x} = Ax + Bu, \quad y = Cx + Du,$$

we have

$$C\phi(t, \tau)B = Ce^{A(t-\tau)}B.$$

Therefore, rewriting from the previous definition as

$$\sup_{t \geq 0} \int_0^t |\bar{g}_{ij}(t - \tau)| d\tau < \infty,$$

with the understanding that now $\bar{g}_{ij}(t - \tau)$ denotes the ij th entry of $Ce^{A(t-\tau)}B$. Making the change of variable $\rho \triangleq t - \tau$, we conclude that

$$\sup_{t \geq 0} \int_0^t |\bar{g}_{ij}(t - \tau)| d\tau = \sup_{t \geq 0} \int_0^t |\bar{g}_{ij}(\rho)| d\rho = \int_0^\infty |\bar{g}_{ij}(\rho)| d\rho.$$

Theorem (Time domain BIBO LTI condition)

The following two statements are equivalent.

- 1 The system (CLTI) is uniformly BIBO stable.
- 2 For every entry $\bar{g}_{ij}(\rho)$ of $Ce^{A\rho}B$, we have

$$\int_0^\infty |\bar{g}_{ij}(\rho)| d\rho < \infty.$$

Frequency Domain Conditions for BIBO Stability

The Laplace transform provides a very convenient tool for studying BIBO stability.

Frequency Domain Conditions for BIBO Stability

The Laplace transform provides a very convenient tool for studying BIBO stability.

To determine whether a time-invariant system (CLTI) is BIBO stable, we need to compute the entries $g_{ij}(t)$ of $Ce^{At}B$. To do this, we compute its Laplace transform, $\mathcal{L}[Ce^{At}B] = C(sI - A)^{-1}B$.

Frequency Domain Conditions for BIBO Stability

The Laplace transform provides a very convenient tool for studying BIBO stability.

To determine whether a time-invariant system (CLTI) is BIBO stable, we need to compute the entries $g_{ij}(t)$ of $Ce^{At}B$. To do this, we compute its Laplace transform, $\mathcal{L}[Ce^{At}B] = C(sI - A)^{-1}B$.

The ij th entry of this matrix will be a strictly proper rational function of the general form

$$\hat{g}_{ij}(s) = \frac{\alpha_0 s^q + \alpha_1 s^{q-1} + \cdots + \alpha_{q-1} s + \alpha_q}{(s - \lambda_1)^{m_1} (s - \lambda_2)^{m_2} \cdots (s - \lambda_k)^{m_k}},$$

where the λ_ℓ are the (distinct) pole of $\hat{g}_{ij}(s)$ and the m_ℓ are the corresponding multiplicities.

Frequency Domain Conditions for BIBO Stability

The Laplace transform provides a very convenient tool for studying BIBO stability.

To determine whether a time-invariant system (CLTI) is BIBO stable, we need to compute the entries $g_{ij}(t)$ of $Ce^{At}B$. To do this, we compute its Laplace transform, $\mathcal{L}[Ce^{At}B] = C(sI - A)^{-1}B$.

The ij th entry of this matrix will be a strictly proper rational function of the general form

$$\hat{g}_{ij}(s) = \frac{\alpha_0 s^q + \alpha_1 s^{q-1} + \dots + \alpha_{q-1} s + \alpha_q}{(s - \lambda_1)^{m_1} (s - \lambda_2)^{m_2} \dots (s - \lambda_k)^{m_k}},$$

where the λ_ℓ are the (distinct) pole of $\hat{g}_{ij}(s)$ and the m_ℓ are the corresponding multiplicities. Perform the partial fraction as

$$\begin{aligned} \hat{g}_{ij}(s) = & \frac{a_{11}}{(s - \lambda_1)} + \frac{a_{12}}{(s - \lambda_1)^2} + \dots + \frac{a_{1m_1}}{(s - \lambda_1)^{m_1}} + \dots \\ & + \frac{a_{k1}}{(s - \lambda_k)} + \frac{a_{k2}}{(s - \lambda_k)^2} + \dots + \frac{a_{km_k}}{(s - \lambda_k)^{m_k}}. \end{aligned}$$

The inverse Laplace transform is then given by

$$\begin{aligned} g_{ij}(t) &= \mathcal{L}^{-1}[\hat{g}_{ij}(s)] \\ &= a_{11}e^{\lambda_1 t} + a_{12}te^{\lambda_1 t} + \dots + a_{1m_1}t^{m_1-1}e^{\lambda_1 t} + \dots \\ &\quad + a_{k1}e^{\lambda_k t} + a_{k2}te^{\lambda_k t} + \dots + a_{km_k}t^{m_k-1}e^{\lambda_k t}. \end{aligned}$$

Frequency Domain Conditions for BIBO Stability

We therefore conclude the following.

- 1 If for all $\hat{g}_{ij}(s)$, all the poles λ_ℓ have strictly negative real parts, then $g_{ij}(t)$ converges to zero exponentially fast and the system (CLTI) is BIBO stable.

Frequency Domain Conditions for BIBO Stability

We therefore conclude the following.

- 1 If for all $\hat{g}_{ij}(s)$, all the poles λ_ℓ have strictly negative real parts, then $g_{ij}(t)$ converges to zero exponentially fast and the system (CLTI) is BIBO stable.
- 2 If at least one of the $\hat{g}_{ij}(s)$ has a pole λ_ℓ with a zero or positive real part, then $|g_{ij}(t)|$ does not converge to zero and the system (CLTI) is not BIBO stable.

Frequency Domain Conditions for BIBO Stability

We therefore conclude the following.

- 1 If for all $\hat{g}_{ij}(s)$, all the poles λ_ℓ have strictly negative real parts, then $g_{ij}(t)$ converges to zero exponentially fast and the system (CLTI) is BIBO stable.
- 2 If at least one of the $\hat{g}_{ij}(s)$ has a pole λ_ℓ with a zero or positive real part, then $|g_{ij}(t)|$ does not converge to zero and the system (CLTI) is not BIBO stable.

Note that adding a constant D term will not change its poles.

Theorem (Frequency domain BIBO condition)

The following two statements are equivalent:

- 1 *The system (CLTI) is uniformly BIBO stable.*
- 2 *Every pole of every entry of the transfer function of the system (CLTI) has a strictly negative real part.*

BIBO vs Lyapunov stability

We now know that the LTI system

$$\dot{x} = Ax + Bu, \quad y = Cx + Du$$

is uniformly BIBO stable if and only if every entry $\bar{g}_{ij}(t)$ of $Ce^{At}B$ satisfies

$$\int_0^{\infty} |\bar{g}_{ij}(t)| dt < \infty \quad (8)$$

BIBO vs Lyapunov stability

We now know that the LTI system

$$\dot{x} = Ax + Bu, \quad y = Cx + Du$$

is uniformly BIBO stable if and only if every entry $\bar{g}_{ij}(t)$ of $Ce^{At}B$ satisfies

$$\int_0^{\infty} |\bar{g}_{ij}(t)| dt < \infty \quad (8)$$

However, if the system (CLTI) is exponentially stable, then every entry of e^{At} converges to zero exponentially fast and therefore (8) must hold.

BIBO vs Lyapunov stability

We now know that the LTI system

$$\dot{x} = Ax + Bu, \quad y = Cx + Du$$

is uniformly BIBO stable if and only if every entry $\bar{g}_{ij}(t)$ of $Ce^{At}B$ satisfies

$$\int_0^{\infty} |\bar{g}_{ij}(t)| dt < \infty \quad (8)$$

However, if the system (CLTI) is exponentially stable, then every entry of e^{At} converges to zero exponentially fast and therefore (8) must hold.

Theorem

When the system (CLTI) is exponentially stable, then it must also be BIBO stable.

BIBO vs Lyapunov stability

We now know that the LTI system

$$\dot{x} = Ax + Bu, \quad y = Cx + Du$$

is uniformly BIBO stable if and only if every entry $\bar{g}_{ij}(t)$ of $Ce^{At}B$ satisfies

$$\int_0^{\infty} |\bar{g}_{ij}(t)| dt < \infty \quad (8)$$

However, if the system (CLTI) is exponentially stable, then every entry of e^{At} converges to zero exponentially fast and therefore (8) must hold.

Theorem

When the system (CLTI) is exponentially stable, then it must also be BIBO stable.

Attention!

In general, the converse of the above theorem is not true, because there are systems that are BIBO stable but not exponentially stable.

BIBO vs Lyapunov stability

Example¹

Consider the system²

$$\dot{x} = \begin{bmatrix} 1 & 0 \\ 0 & -2 \end{bmatrix} x + \begin{bmatrix} 0 \\ 1 \end{bmatrix} u, \quad y = \begin{bmatrix} 1 & 1 \end{bmatrix} x$$

for which

$$e^{At} = \begin{bmatrix} e^t & 0 \\ 0 & e^{-2t} \end{bmatrix}$$

is unbounded and therefore Lyapunov unstable, but

$$Ce^{At}B = \begin{bmatrix} 1 & 1 \end{bmatrix} \begin{bmatrix} e^t & 0 \\ 0 & e^{-2t} \end{bmatrix} \begin{bmatrix} 0 \\ 1 \end{bmatrix} = e^{-2t}$$

and therefore the system is BIBO stable

¹We shall see in later lectures that this discrepancy between Lyapunov and BIBO stability is always associated with *lack of controllability or observability*, two concepts that will be introduced later.

²The system is not controllable.

Discrete-time case

Consider now the following discrete-time LTV system

$$x(t+1) = A(t)x(t) + B(t)u(t), \quad y(t) = C(t)x(t) + D(t)u(t)$$

The forced response of this system is given by

$$y_f(t) = \sum_{\tau=0}^{t-1} C(t)\phi(t, \tau+1)B(\tau)u(\tau)d\tau + D(t)u(t), \quad \forall t \geq 0,$$

Definition (BIBO stability)

The system (DLTV) is said to be (uniformly) BIBO stable whenever there exists a finite constant g^1 such that, for every input $u(\bullet)$, its forced response $y_f(\bullet)$ satisfies

$$\sup_{t \in \mathbb{N}} \|y_f(t)\| \leq g \sup_{t \in \mathbb{N}} \|u(t)\|.$$

¹The factor g can be viewed as the "gain" of the system.

Discrete-time case

Theorem (Time domain BIBO condition)

The following two statements are equivalent.

- 1 The system *(DLTV)* is uniformly BIBO stable.
- 2 Every entry of $D(\bullet)$ is uniformly bounded and

$$\sup_{t \geq 0} \sum_{\tau=0}^{t-1} |g_{ij}(t, \tau)| < \infty$$

for every entry $g_{ij}(t, \tau)$ of $C(t)\phi(t, \tau)B(\tau)$.

Discrete-time case

Theorem (Time domain BIBO condition)

The following two statements are equivalent.

- 1 The system (DLTV) is uniformly BIBO stable.
- 2 Every entry of $D(\bullet)$ is uniformly bounded and

$$\sup_{t \geq 0} \sum_{\tau=0}^{t-1} |g_{ij}(t, \tau)| < \infty$$

for every entry $g_{ij}(t, \tau)$ of $C(t)\phi(t, \tau)B(\tau)$.

Theorem (BIBO LTI conditions)

The following three statements are equivalent.

- 1 The system (DLTI) is uniformly BIBO stable.
- 2 For every entry $\bar{g}_{ij}(\rho)$ of $CA^{\rho}B$, we have

$$\sum_{\rho=1}^{\infty} |\bar{g}_{ij}(\rho)| < \infty$$


- 3 Every pole of every entry of the transfer function of the system (DLTI) has magnitude strictly smaller than 1.

Interesting facts

Consider the function defined by

$$f(t-n) = \begin{cases} n + (t-n)n^4, & \text{for } n - \frac{1}{n^3} \leq t \leq n \\ n - (t-n)n^4, & \text{for } n < t \leq n + \frac{1}{n^3} \end{cases}$$

for $n = 2, 3, \dots$. The area under each triangle is $1/n^2$. Thus the absolute integration of the function equals $\sum_{n=2}^{\infty} (1/n^2) < \infty$. This function is absolutely integrable but is *not* bounded and does not approach zero as $t \rightarrow \infty$.



Interesting facts

In the discrete-time case, if $g(t)$ is absolutely summable, then it *must* be bounded and approach zero as $t \rightarrow \infty$. However, the converse is not true.

Interesting facts

In the discrete-time case, if $g(t)$ is absolutely summable, then it *must* be bounded and approach zero as $t \rightarrow \infty$. However, the converse is not true.

Example

Consider $g(t) = 1/t$, for $t = 1, 2, \dots$ and $g(0) = 0$. We compute

$$\begin{aligned} S &= \sum_{t=1}^{\infty} |g(t)| = \sum_{t=1}^{\infty} \frac{1}{t} = 1 + \frac{1}{2} + \frac{1}{3} + \frac{1}{4} + \dots \\ &= 1 + \frac{1}{2} + \left(\frac{1}{3} + \frac{1}{4}\right) + \left(\frac{1}{5} + \dots + \frac{1}{8}\right) + \left(\frac{1}{9} + \dots + \frac{1}{16}\right) + \dots \end{aligned}$$

We notice that

$$S > 1 + \frac{1}{2} + \frac{1}{2} + \frac{1}{2} + \dots = \infty$$

This impulse response sequence is bounded and approaches 0 as $t \rightarrow \infty$ but is not absolutely summable.

Theorem

The equation $\dot{x} = Ax$ is marginally stable if and only if all the eigenvalues of A have zero or negative real parts and those with zero real parts are simple roots of the minimal polynomial of A .

Theorem

The equation $\dot{x} = Ax$ is marginally stable if and only if all the eigenvalues of A have zero or negative real parts and those with zero real parts are simple roots of the minimal polynomial of A .

Theorem (Eigenvalue conditions - Slide 20)

The system (H-CLTI) is

- marginally stable if and only if all the eigenvalues of A have negative or zero real parts and all the Jordan blocks corresponding to eigenvalues with zero real parts are 1×1 ,*
- asymptotically stable if and only if all the eigenvalues of A have strictly negative real parts,*
- unstable if and only if at least one eigenvalue of A has a positive real part or zero real part, but the corresponding Jordan block is larger than 1×1 .*

Definition (Minimal polynomial)

Let A be an $n \times n$ matrix. We associate two polynomials to A

Definition (Minimal polynomial)

Let A be an $n \times n$ matrix. We associate two polynomials to A :

- 1 The characteristic polynomial of A is defined as
 $f(s) = \det(s.I - A)$. $f(s)$ is a monic polynomial of degree n .

Definition (Minimal polynomial)

Let A be an $n \times n$ matrix. We associate two polynomials to A :

- 1 The characteristic polynomial of A is defined as $f(s) = \det(s.I - A)$. $f(s)$ is a monic polynomial of degree n .
- 2 The minimal polynomial of A , which we will denote by $\psi(s)$, is defined by the following properties:
 - $\psi(s)$ is monic (i.e., its leading coefficient is 1),
 - $\psi(A) = 0$,
 - $\psi(s)$ is the monic polynomial of the smallest possible degree such that $\psi(A) = 0$,

Definition (Minimal polynomial)

Let A be an $n \times n$ matrix. We associate two polynomials to A :

- 1 The characteristic polynomial of A is defined as $f(s) = \det(s.I - A)$. $f(s)$ is a monic polynomial of degree n .
- 2 The minimal polynomial of A , which we will denote by $\psi(s)$, is defined by the following properties:
 - $\psi(s)$ is monic (i.e., its leading coefficient is 1),
 - $\psi(A) = 0$,
 - $\psi(s)$ is the monic polynomial of the smallest possible degree such that $\psi(A) = 0$,

They also satisfy the following properties:

- If $g(s)$ is another polynomial, then $g(A) = 0$ if and only if $\psi(s)$ divides $g(s)$.
- $f(s)$ is a multiple of $\psi(s)$.

Additional results (Example)

Consider

$$\dot{x} = \begin{bmatrix} 0 & 0 & 0 \\ 0 & 0 & 0 \\ 0 & 0 & -1 \end{bmatrix} x$$

Its characteristic polynomial is $\Delta(\lambda) = \lambda^2(\lambda + 1)$

Additional results (Example)

Consider

$$\dot{x} = \begin{bmatrix} 0 & 0 & 0 \\ 0 & 0 & 0 \\ 0 & 0 & -1 \end{bmatrix} x$$

Its characteristic polynomial is $\Delta(\lambda) = \lambda^2(\lambda + 1)$ and its minimal polynomial is $\psi(\lambda) = \lambda(\lambda + 1)$. The matrix has eigenvalues 0, 0, and -1 . The eigenvalue 0 is a simple root of the minimal polynomial. This the system is marginally stable.

The equation

$$\dot{x} = \begin{bmatrix} 0 & 1 & 0 \\ 0 & 0 & 0 \\ 0 & 0 & -1 \end{bmatrix} x$$

Additional results (Example)

Consider

$$\dot{x} = \begin{bmatrix} 0 & 0 & 0 \\ 0 & 0 & 0 \\ 0 & 0 & -1 \end{bmatrix} x$$

Its characteristic polynomial is $\Delta(\lambda) = \lambda^2(\lambda + 1)$ and its minimal polynomial is $\psi(\lambda) = \lambda(\lambda + 1)$. The matrix has eigenvalues 0, 0, and -1 . The eigenvalue 0 is a simple root of the minimal polynomial. This the system is marginally stable.

The equation

$$\dot{x} = \begin{bmatrix} 0 & 1 & 0 \\ 0 & 0 & 0 \\ 0 & 0 & -1 \end{bmatrix} x$$

is not marginally stable, however, because its minimal polynomial is $\psi(\lambda) = \lambda^2(\lambda + 1)$ and $\lambda = 0$ is not a simple root of the minimal polynomial.

Interesting facts



A time-invariant system is asymptotically stable if all eigenvalues of A have negative real parts. Is this also true for the time-varying case?



A time-invariant system is asymptotically stable if all eigenvalues of A have negative real parts. Is this also true for the time-varying case?

Example

Consider

$$\dot{x} = A(t)x = \begin{bmatrix} -1 & e^{2t} \\ 0 & -1 \end{bmatrix}$$

The characteristic polynomial of $A(t)$ and the eigenvalues are

$$\det(\lambda.I - A(t)) = (\lambda + 1)^2 \implies \lambda = -1, -1$$



A time-invariant system is asymptotically stable if all eigenvalues of A have negative real parts. Is this also true for the time-varying case?

Example

Consider

$$\dot{x} = A(t)x = \begin{bmatrix} -1 & e^{2t} \\ 0 & -1 \end{bmatrix}$$

The characteristic polynomial of $A(t)$ and the eigenvalues are

$$\det(\lambda.I - A(t)) = (\lambda + 1)^2 \implies \lambda = -1, -1$$

It can be verified directly that

$$\phi(t, 0) = \begin{bmatrix} e^{-t} & 0.5(e^t - e^{-t}) \\ 0 & e^{-t} \end{bmatrix}$$

Note that determination of the stability using the eigenvalues of matrix $A(t)$ is not applicable in the time varying case.