

Foundations of R Software

Lecture 19

Basics of Calculations

⋮⋮⋮

Conditional Executions – If and If-Else

Shalabh

Department of Mathematics and Statistics

Indian Institute of Technology Kanpur

Control structures in R :

Control statements,

Functions,

Loops.

1. Conditional execution: if()

Syntax

```
if (condition) {execute commands if condition is TRUE}
```

The code in the `{ }` is evaluated if the logical test contained in the `( )` is **TRUE**.


If the logical test is **FALSE**, R will ignore all of the code in the `{ }`.

`if()` should not be applied when the **condition** being evaluated is a vector. It is best used only when meeting a single element condition.

1. Conditional execution: if()

Syntax

if (condition) {execute commands if condition is TRUE}



1. Conditional execution: if()

Example 1:

Suppose we want to multiply all the values $x > 4$ by 3.


```
> x = 5
```

```
> if (x > 4) x * 3  
[1] 15
```

```
> x = 3
```

```
> if (x > 4) x * 3
```

No response is obtained.



```
R Console  
  
> x = 5  
>  
> if (x > 4) x * 3  
[1] 15  
>  
> x = 3  
>  
> if (x > 4) x * 3  
> |
```

1. Conditional execution: if()

Example 1: Same with using {}

Suppose we want to multiply all the values $x > 4$ by 3.


```
> x = 5
```

```
> if (x > 4) {x * 3}  
[1] 15
```

```
> x = 3
```

```
> if (x > 4) {x * 3}
```

No response is obtained.



```
R Console  
> x = 5  
> x  
[1] 5  
> if (x > 4) {x * 3}  
[1] 15  
>  
> x = 3  
> if (x > 4) {x * 3}  
> |
```

1. Conditional execution: if()


Example 2:

Suppose we want to print if a value is more than 3.

```
x = 6
```

```
if(x > 3){  
  print("The value is more than 3")  
}
```

```
[1] "The value is more than 3"
```



```
R Console  
> x = 6  
> if(x > 3){  
+ print("The value is more than 3")  
+ }  
[1] "The value is more than 3"  
>  
> x = 2  
> if(x > 3){  
+ print("The value is more than 3")  
+ }  
> |
```

1. Conditional execution: if()

Example 3:

Suppose we want to print if a value is more than 3.


```
x = 2
```

```
if(x > 3){
```

```
  print("The value is more than 3")
```

```
}
```

No outcome is obtained.




```
R Console
> x = 6
> if(x > 3){
+ print("The value is more than 3")
+ }
[1] "The value is more than 3"
>
> x = 2
> if(x > 3){
+ print("The value is more than 3")
+ }
> |
```

2. Conditional execution: if else()

Syntax

```
if (condition) {executes commands if condition is TRUE}  
else { executes commands if condition is FALSE }
```



2. Conditional execution: if else()

Please note:

- The condition in this control statement may not be vector valued and if so, only the first element of the vector is used.
- `if else()` should not be applied when the `condition` being evaluated is a vector. It is best used only when meeting a single element condition.
- The condition may be a complex expression where the logical operators "and" (`&&`) and "or" (`||`) can be used.

2. Conditional execution: if else()


Example 4:

```
x = 5  
if ( x==3 ) { x = x-1 } else { x = 2*x }  
x  
[1] 10
```

Interpretation:

- If $x = 3$, then execute $x = x - 1$.
- If $x \neq 3$, then execute $x = 2*x$.

In this case, $x = 5$, so $x \neq 3$. Thus $x = 2*5$



```
R Console  
> x = 5  
>  
> if ( x==3 ) { x = x-1 } else { x = 2*x }  
>  
> x  
[1] 10  
> |
```

2. Conditional execution: if else()


Example 5:

```
x = 3
if ( x==3 ) { x = x-1 } else { x = 2*x }
x
[1] 2
```

Interpretation:

- If $x = 3$, then execute $x = x - 1$.
- If $x \neq 3$, then execute $x = 2*x$.

In this case, $x = 3$. Thus $x = 3 - 1 = 2$



```
R Console
> x = 3
>
> if ( x==3 ) { x = x-1 } else { x = 2*x }
>
> x
[1] 2
> |
```


2. Conditional execution: if else()

Example 6:

Suppose we want to print if a value is more than 3 or less than 3.

```
x = 6
```

```
if(x > 3){  
  print("The value is more than 3")  
} else {  
  print("The value is less than 3")  
}  
[1] "The value is more than 3"
```



```
R Console  
> x = 6  
> if(x > 3){  
+ print("The value is more than 3")  
+ } else {  
+ print("The value is less than 3")  
+ }  
[1] "The value is more than 3"  
>  
> x = 2  
> if(x > 3){  
+ print("The value is more than 3")  
+ } else {  
+ print("The value is less than 3")  
+ }  
[1] "The value is less than 3"  
> |
```

2. Conditional execution: if else()

Example 7:

Suppose we want to print if a value is more than 3 or less than 3.

```
x = 2
```

```
if(x > 3){  
    print("The value is more than 3")  
} else {  
    print("The value is less than 3")  
}
```

```
[1] "The value is less than 3"
```

2. Conditional execution: if else()

Example 6:

R Console

```
> x = 6
> if(x > 3){
+ print("The value is more than 3")
+ } else {
+ print("The value is less than 3")
+ }
[1] "The value is more than 3"
>
> x = 2
> if(x > 3){
+ print("The value is more than 3")
+ } else {
+ print("The value is less than 3")
+ }
[1] "The value is less than 3"
> |
```