

Foundations of R Software

Lecture 23

Basics of Calculations

⋮

Loops – while and repeat

Shalabh

Department of Mathematics and Statistics

Indian Institute of Technology Kanpur

Control structures in R :

Control statements,

Functions,

Loops.


Loops

Repetitive commands are executed by loops

- **for loop**
- **while loop**
- **repeat loop**

1. The for loop

If the number of repetitions is known in advance (e.g. if all commands have to be executed for all cases $i = 1, 2, \dots, n$ in the data), a **for()** loop can be used.



1. The for loop

Syntax


```
for (name in vector) {commands to be executed}
```

A variable with name **name** is sequentially set to all values, which contained in the vector **vector**.

All operations/commands are executed for all these values.

2. The `while` loop

If the number of loops is not known in before, e.g. when an iterative algorithm to maximize a likelihood function is used, one can use a `while()` loop.



2. The `while` loop

Syntax

```
while(condition){ commands to be executed as  
long as condition is TRUE }
```

If the condition is not true *before entering* the loop, no commands within the loop are executed.

2. The while loop

Example 1:

```
i = 1
```

```
while (i < 10) {
```

```
  print(i^2)
```

```
  i = i+2
```

```
}
```

```
[1] 1
```

```
[1] 9
```

```
[1] 25
```

```
[1] 49
```

```
[1] 81
```

R Console

```
> i = 1
> while (i < 10) {
+   print(i^2)
+   i = i+2
+ }
[1] 1
[1] 9
[1] 25
[1] 49
[1] 81
> |
```

2. The while loop

Example 2:

```
sumfunction = function(){  
  sum = 0  
  
  number = as.integer(readline(prompt="Please  
select any number less than 25:  "))  
  
  while (number <= 25)  {  
    sum = sum + number  
    number = number + 1  }  
  
  print(paste("The sum of numbers received from  
the While Loop:  ", sum))  
}
```

2. The while loop

Example 2:

```
> sumfunction()
```

```
Please select any number less than 25 : 22
```

```
[1] "The sum of numbers received from the  
While Loop: 94"
```

```
> 22+23+24+25
```

```
[1] 94
```

```
R Console  
  
> sumfunction = function(){  
+ sum = 0  
+ number = as.integer(readline(prompt="Please select any number less than 25: "))  
+ while (number <= 25) {  
+   sum = sum + number  
+   number = number + 1 }  
+ print(paste("The sum of numbers received from the While Loop: ", sum))  
+ }  
>  
> sumfunction()  
Please select any number less than 25: 22  
[1] "The sum of numbers received from the While Loop: 94"  
> |
```

3. The repeat loop

The repeat loop doesn't test any condition — in contrast to the `while()` loop — *before entering* the loop and also not during the execution of the loop.

Again, the programmer is responsible that the loop terminates after the appropriate number of iterations. For this the `break` command can be used.

Syntax

```
repeat{ commands to be executed }
```

Example 3:

```
i = 1
repeat{
  print( i^2 )
  i = i+2
  if ( i > 10 )
    break
}
[1] 1
[1] 9
[1] 25
[1] 49
[1] 81
```


R Console

```
> i = 1
> repeat{
+ print( i^2 )
+ i = i+2
+ if ( i > 10 )
+ break
+ }
[1] 1
[1] 9
[1] 25
[1] 49
[1] 81
> |
```

Example 4:

Additionally, the command **next** is available, to return to the beginning of the loop (to return to the first command in the loop).

```
i = 1
repeat{
  i = i+1
  if (i < 10) next
  print(i^2)
  if (i >= 13) break
}
[1] 100
[1] 121
[1] 144
[1] 169
```

A screenshot of an R console window with a light blue header bar that says "R Console". The console shows the execution of the R code from the previous block. The commands are in red text, and the output is in blue text. The output shows the squares of 10, 11, 12, and 13, each on a new line, preceded by "[1]". The prompt "> |" is at the bottom.

```
> i = 1
> repeat{
+ i = i+1
+ if (i < 10) next
+ print(i^2)
+ if (i >= 13) break
+ }
[1] 100
[1] 121
[1] 144
[1] 169
> |
```