

Foundations of R Software

Lecture 37

Strings – Display and Formatting

⋮

Paste Function

Shalabh

Department of Mathematics and Statistics

Indian Institute of Technology Kanpur

Formatting and Display of Strings: `paste`

- The `paste()` function concatenates several strings together.
- It creates a new string by joining the given strings end to end.
- The result of `paste()` can be assigned to a variable (in contrast to the function `cat()`).

Formatting and Display of Strings

Usage

```
paste (... , sep = " ", collapse = NULL).
```

collapse is an optional character string to separate the results.

- The parameter **sep** is a string that serves as a separation between the strings that are given as input.
- **paste** inserts a single space between pairs of strings.
- A desired line break can be achieved with **"\n"** (newline).

Formatting and Display of Strings: **paste**

- **paste** converts its arguments to character strings (via **as.character**) , and concatenates them (separating them by the string given by **sep**).
- If the arguments are vectors, they are concatenated term-by-term to give a character vector result.
- If a value is specified for **collapse**, the values in the result are then concatenated into a single string, with the elements being separated by the value of **collapse**.

Formatting and Display of Strings: `paste`

- The `paste()` function concatenates several strings together.
- It creates a new string by joining the given strings end to end.
- The result of `paste()` can be assigned to a variable (in contrast to the function `cat()`).

`paste0(..., collapse)`


is equivalent to `paste(..., sep = "", collapse)`,
slightly more efficiently.

Formatting and Display of Strings

Example: `paste` converts its arguments to character strings (via `as.character`), and concatenates them

```
> paste(1:12)
[1] "1" "2" "3" "4" "5" "6" "7" "8"
"9" "10" "11" "12"
```

```
> as.character(1:12) #Alternative to paste
[1] "1" "2" "3" "4" "5" "6" "7" "8"
"9" "10" "11" "12"
```



```
R Console
> paste(1:12)
[1] "1" "2" "3" "4" "5" "6" "7" "8" "9" "10" "11" "12"
>
> as.character(1:12)
[1] "1" "2" "3" "4" "5" "6" "7" "8" "9" "10" "11" "12"
> |
```

Formatting and Display of Strings

```
> paste("Everybody", "loves", "R Programming.")
```

```
[1] "Everybody loves R Programming."
```

```
> paste("Everybody", "loves", "R Programming.",  
sep="*")
```

```
[1] "Everybody*loves*R Programming."
```

```
> paste("Everybody", "loves", "R Programming.",  
sep==="")
```

```
[1] "Everybody===loves===R Programming."
```

Formatting and Display of Strings

R Console

```
> paste("Everybody", "loves", "R Programming.")  
[1] "Everybody loves R Programming."  
>  
> paste("Everybody", "loves", "R Programming.", sep="*")  
[1] "Everybody*loves*R Programming."  
>  
> paste("Everybody", "loves", "R Programming.", sep==="")  
[1] "Everybody===loves===R Programming."
```


Formatting and Display of Strings

If one or more arguments are vectors of strings, **paste** will generate all combinations of the arguments:

```
> names = c("Prof. Singh", "Mr. Venkat", "Dr. Jha")
```

```
> names  
[1] "Prof. Singh" "Mr. Venkat" "Dr. Jha"
```

```
> paste(names, "is", "a good", "person.")  
[1] "Prof. Singh is a good person." "Mr. Venkat is a  
good person." "Dr. Jha is a good person."
```

A screenshot of an R console window showing the execution of the same R code as the previous blocks. The console output matches the text shown above.

```
R Console  
> names = c("Prof. Singh", "Mr. Venkat", "Dr. Jha")  
> names  
[1] "Prof. Singh" "Mr. Venkat" "Dr. Jha"  
> paste(names, "is", "a good", "person.")  
[1] "Prof. Singh is a good person." "Mr. Venkat is a good person." "Dr. Jha is a good person."  
> |
```

Formatting and Display of Strings

When we want to join even those combinations into one, big string.

The **collapse** parameter defines a top-level separator and instructs **paste** to concatenate the generated strings using that separator:

```
> names = c("Prof. Singh", "Mr. Venkat", "Dr. Jha")
```

```
> paste(names, "is", "a good", "person.",  
collapse=", and ")  
[1] "Prof. Singh is a good person., and Mr.  
Venkat is a good person., and Dr. Jha is a good  
person."
```

Formatting and Display of Strings

R Console

```
> names = c("Prof. Singh", "Mr. Venkat", "Dr. Jha")
>
> paste(names, "is", "a good", "person.", collapse=" and ")
[1] "Prof. Singh is a good person., and Mr. Venkat is a good person., and Dr. Jha is a good person."
> |
```

Operations with Strings

Example:

```
> paste(1, " is first", 2, " is second", 3, " is third",  
sep = "#")
```

```
[1] "1# is first#2# is second#3# is third"
```

Observe the role of blank space inside double quotes

```
> paste(1, " is first    ", 2, " is second    ", 3, " is  
third    ", sep = "#")
```

```
[1] "1# is first    #2# is second    #3# is third    "
```

R Console

```
> paste(1, " is first", 2, " is second", 3, " is third", sep = "#")  
[1] "1# is first#2# is second#3# is third"  
>  
> paste(1, " is first    ", 2, " is second    ", 3, " is third    ", sep = "#")  
[1] "1# is first    #2# is second    #3# is third    "  
> |
```

Operations with Strings

Example:

```
> x = paste("Ex", 1:5, sep="_")
```

```
> x
```

```
[1] "Ex_1" "Ex_2" "Ex_3" "Ex_4" "Ex_5"
```

```
> x[1]
```

```
[1] "Ex_1"
```

```
> x[2]
```


```
[1] "Ex_2"
```

```
> x[3]
```

```
[1] "Ex_3"
```

```
> x[5]
```

```
[1] "Ex_5"
```



```
R Console
> x = paste("Ex", 1:5, sep="_")
> x
[1] "Ex_1" "Ex_2" "Ex_3" "Ex_4" "Ex_5"
> x[1]
[1] "Ex_1"
> x[2]
[1] "Ex_2"
> x[3]
[1] "Ex_3"
> x[4]
[1] "Ex_4"
> x[5]
[1] "Ex_5"
> |
```

Operations with Strings


x is a vector of strings.

If we use the parameter **collapse**, a single string, instead of a vector of strings, is created:

```
> x = paste("Ex", 1:5, sep="_", collapse="")
```

```
> x[1]
```

```
[1] "Ex_1Ex_2Ex_3Ex_4Ex_5"
```

A screenshot of an R console window. The title bar says "R Console". The console shows the following commands and output:

```
> x = paste("Ex", 1:5, sep="_", collapse="")  
> x  
[1] "Ex_1Ex_2Ex_3Ex_4Ex_5"  
> |
```

Operations with Strings

Note the difference between

```
x = paste("Ex", 1:5, sep="_")
```

```
> x
```


```
[1] "Ex_1" "Ex_2" "Ex_3" "Ex_4" "Ex_5"
```

and

```
x = paste("Ex", 1:5, sep="_", collapse="")
```

```
> x
```

```
[1] "Ex_1Ex_2Ex_3Ex_4Ex_5"
```



```
R Console
> x = paste("Ex", 1:5, sep="_")
> x
[1] "Ex_1" "Ex_2" "Ex_3" "Ex_4" "Ex_5"
>
> x = paste("Ex", 1:5, sep="_", collapse="")
> x
[1] "Ex_1Ex_2Ex_3Ex_4Ex_5"
> |
```

Operations with Strings

When using a single vector, `paste0` and `paste` have the same outcome and they work the same `as.character`.

```
> paste0(1:10)
[1] "1"  "2"  "3"  "4"  "5"  "6"  "7"  "8"
"9"  "10"
```

```
> paste(1:10)
[1] "1"  "2"  "3"  "4"  "5"  "6"  "7"  "8"
"9"  "10"
```

R Console

```
> paste0(1:10)
[1] "1"  "2"  "3"  "4"  "5"  "6"  "7"  "8"  "9"  "10"
> paste(1:10)
[1] "1"  "2"  "3"  "4"  "5"  "6"  "7"  "8"  "9"  "10"
> |
```


Operations with Strings

When we use more than one vectors to `paste0` then they concatenate in a vectorized way.

```
> paste0(1:10, c("st", "nd", "rd", rep("th", 7)))  
[1] "1st" "2nd" "3rd" "4th" "5th" "6th" "7th"  
"8th" "9th" "10th"
```

Observe the role of blank space

```
> paste(1:10, c("st", "nd", "rd", rep("th", 7)))  
[1] "1 st" "2 nd" "3 rd" "4 th" "5 th" "6 th"  
"7 th" "8 th" "9 th" "10 th"
```



```
R Console  
> paste0(1:10, c("st", "nd", "rd", rep("th", 7)))  
[1] "1st" "2nd" "3rd" "4th" "5th" "6th" "7th" "8th" "9th" "10th"  
>  
> paste(1:10, c("st", "nd", "rd", rep("th", 7)))  
[1] "1 st" "2 nd" "3 rd" "4 th" "5 th" "6 th" "7 th" "8 th" "9 th" "10 th"  
>
```