

Foundations of R Software

Lecture 38

Strings – Display and Formatting

⋮

String Splitting

Shalabh

Department of Mathematics and Statistics

Indian Institute of Technology Kanpur

Operations with Strings

Command **strsplit**, split the elements of a character vector.

"Split" can be a single character, or a character string:

Usage

```
strsplit(x, split, fixed = FALSE, ...)
```

Arguments

x character vector, each element of which is to be split.

split character vector containing regular expression(s)
(unless **fixed** = TRUE) to use for splitting.

fixed logical. If **TRUE** match split exactly, otherwise use regular expressions.

Operations with Strings

❑ With a command `strsplit`, we can split a string in pieces.

```
> x = "The&!syntax&!of&!paste&!is!&available!  
&inthe online-help"
```

```
> x  
[1] "The&!syntax&!of&!paste&!is!&available!  
&inthe online-help"
```

```
> strsplit(x, split="!")  
[[1]]  
[1] "The&"          "syntax&"      "of&"  
[4] "paste&"        "is"           "&available"  
[7] " &inthe online-help"
```

Operations with Strings

R Console

```
> x = "The&!syntax&!of&!paste&!is!&available! &inthe online-help"
> x
[1] "The&!syntax&!of&!paste&!is!&available! &inthe online-help"
> strsplit(x, split="!")
[[1]]
[1] "The&"          "syntax&"          "of&"
[4] "paste&"        "is"               "&available"
[7] " &inthe online-help"
```

Operations with Strings

```
> x = "The&!syntax&!of&!paste&!is!&available!  
&inthe online-help"
```

```
> x
```

```
[1] "The&!syntax&!of&!paste&!is!&available!  
&inthe online-help"
```

```
> strsplit(x, split = "&!")
```

```
[[1]]
```

```
[1] "The"
```

```
[2] "syntax"
```

```
[3] "of"
```

```
[4] "paste"
```

```
[5] "is!&available! &inthe online-help"
```

Operations with Strings

R Console

```
> x = "The&!syntax&!of&!paste&!is!&available! &inthe online-help"
> x
[1] "The&!syntax&!of&!paste&!is!&available! &inthe online-help"
> strsplit(x, split = "&!")
[[1]]
[1] "The"
[2] "syntax"
[3] "of"
[4] "paste"
[5] "is!&available! &inthe online-help"
```

Operations with Strings

```
> x = "The&!syntax&!of&!paste&!is!&available!  
&inthe online-help"
```

```
> x
```

```
[1] "The&!syntax&!of&!paste&!is!&available!  
&inthe online-help"
```

```
> y = strsplit(x, split = "!&")
```

```
> y
```

```
[[1]]  
[1] "The&!syntax&!of&!paste&!is"      "available!  
&inthe online-help"
```

Operations with Strings

Notice the access to single components:

```
> y[[1]][1]
```

```
[1] "The&!syntax&!of&!paste&!is"
```

```
> y[[1]][2]
```

```
[1] "available! &inthe online-help"
```

```
> y[[1]][3]
```

```
[1] NA
```

Operations with Strings

```
R Console
> x = "The&!syntax&!of&!paste&!is!&available! &inthe online-help"
> x
[1] "The&!syntax&!of&!paste&!is!&available! &inthe online-help"
> y = strsplit(x, split = "!&")
> y
[[1]]
[1] "The&!syntax&!of&!paste&!is"      "available! &inthe online-help"

> y[[1]][1]
[1] "The&!syntax&!of&!paste&!is"
> y[[1]][2]
[1] "available! &inthe online-help"
> y[[1]][3]
[1] NA
> |
```

Operations with Strings

Example: Convert to matrix

```
> dates = c("2020-07-24", "2021-08-25", "2022-09-26", "2023-10-27")
```

Split the dates

```
> datesplt = strsplit(dates, "-")
```

```
> datesplt
```

```
[[1]]
```

```
[1] "2020" "07"   "24"
```

```
[[2]]
```

```
[1] "2021" "08"   "25"
```

```
[[3]]
```

```
[1] "2022" "09"   "26"
```

```
[[4]]
```

```
[1] "2023" "10"   "27"
```

Operations with Strings

Example: Convert to matrix

Create matrix of dates and outcome is that the elements are character

```
> datemat = matrix(unlist(datesplt), nrow = 4,  
ncol=3, byrow=TRUE)
```

```
> datemat
```

	[, 1]	[, 2]	[, 3]
[1,]	"2020"	"07"	"24"
[2,]	"2021"	"08"	"25"
[3,]	"2022"	"09"	"26"
[4,]	"2023"	"10"	"27"

Operations with Strings

Example: Convert to matrix

Create matrix of dates and outcome is that the elements are numbers

```
> datematrix =
```

```
matrix(as.numeric(unlist(datesplt)), nrow = 4,  
ncol=3, byrow=TRUE)
```

```
> datematrix
```

	[,1]	[,2]	[,3]
[1,]	2020	7	24
[2,]	2021	8	25
[3,]	2022	9	26
[4,]	2023	10	27

Operations with Strings

Example: Convert to matrix

```
R Console

> dates = c("2020-07-24", "2021-08-25", "2022-09-26", "2023-10-27")
> dates
[1] "2020-07-24" "2021-08-25" "2022-09-26" "2023-10-27"
> datesplt = strsplit(dates, "-")
> datesplt
[[1]]
[1] "2020" "07" "24"

[[2]]
[1] "2021" "08" "25"

[[3]]
[1] "2022" "09" "26"

[[4]]
[1] "2023" "10" "27"

> datemat = matrix(unlist(datesplt), nrow = 4, ncol=3, byrow=TRUE)
> datemat
      [,1] [,2] [,3]
[1,] "2020" "07" "24"
[2,] "2021" "08" "25"
[3,] "2022" "09" "26"
[4,] "2023" "10" "27"


> datematrix = matrix(as.numeric(unlist(datesplt)), nrow = 4, ncol=3, byrow=TRUE)
> datematrix
      [,1] [,2] [,3]
[1,] 2020    7   24
[2,] 2021    8   25
[3,] 2022    9   26
[4,] 2023   10   27
> |
```

Operations with Strings

```
> strsplit("Shalabh",split="")
```

```
[[1]]
```

```
[1] "S" "h" "a" "l" "a" "b" "h"
```

A screenshot of an R console window. The title bar says "R Console". The console shows the command `> strsplit("Shalabh",split="")` and its output: `[[1]]` followed by `[1] "S" "h" "a" "l" "a" "b" "h"` on the next line.

```
> strsplit("Shalabh",split="")  
[[1]]  
[1] "S" "h" "a" "l" "a" "b" "h"
```