

## Module 1:Preliminary Concepts and Basics Equations

### Lecture 3: A Generalized Approach

#### The Lecture Contains:

 Generalized approach for Energy Equation

 Important Dimensionless Numbers

 **Previous**    **Next** 



### Generalized approach for Energy Equation

Let us apply Reynolds transport theorem to an arbitrary control volume (**Figure 1.2**) for the conservation of energy. We can write


Rate of change of energy for the system,

(A) = Rate of change of energy in the CV,

(B) + Rate of efflux of energy through the control surface of the CV,

(C) Applying first law of thermodynamics, we can also write Rate of change of energy for the system

(A) = rate of energy production within the





**system + rate of work done on the system.**

We evaluate the quantities B & C in the following manner

$$(B) + (C) = \int \int \int \left[ \frac{\partial}{\partial t}(\rho E) + \nabla \cdot (\rho \mathbf{V} E) - \nabla \cdot (k \nabla T) \right] dV$$

Here **E** is defined as  $e + V^2/2$ . Now, (B) + (C) can be equated with the rate of energy production within the system and the rate of work done on the system :

$$\begin{aligned} \int \int \int \left[ \frac{\partial}{\partial t}(\rho E) + \nabla \cdot \{\rho \mathbf{V} E\} - \nabla \cdot (k \nabla T) \right] dV \\ = \int \int \int \left[ \rho \mathbf{f} \cdot \mathbf{V} + \nabla \cdot (\sigma \cdot \mathbf{V}) + \dot{S}_{th} \right] dV \end{aligned} \quad (1.51)$$

For the homogeneous and isotropic medium :

$$\underbrace{\frac{\partial}{\partial t}(\rho E) + \nabla \cdot \{\rho \mathbf{V} E\}}_I - \underbrace{k \nabla^2 T}_{II} = \underbrace{\rho \mathbf{f} \cdot \mathbf{V}}_{III} + \underbrace{\nabla \cdot (\sigma \cdot \mathbf{V})}_{IV} + \underbrace{\dot{S}_{th}}_V \quad (1.52)$$

We obtain the following from term I :

$$\begin{aligned} \frac{\partial}{\partial t}(\rho E) + \nabla \cdot \{\rho \mathbf{V} E\} &= E \frac{\partial \rho}{\partial t} + \rho \frac{\partial E}{\partial t} + \rho \mathbf{V} \cdot \nabla E + E (\nabla \cdot \rho \mathbf{V}) \\ &= \rho \left[ \frac{\partial E}{\partial t} + (\mathbf{V} \cdot \nabla) E \right] + E \left[ \frac{\partial \rho}{\partial t} + \nabla \cdot (\rho \mathbf{V}) \right] \\ &= \rho \left[ \frac{\partial E}{\partial t} + (\mathbf{V} \cdot \nabla) E \right] = \rho \frac{DE}{Dt} \end{aligned} \quad (1.53)$$



## Module 1:Preliminary Concepts and Basics Equations

## Lecture 3: A Generalized Approach

Term IV produces :

$$\begin{aligned}
 \nabla \cdot (\sigma \cdot \mathbf{V}) &= \frac{\partial}{\partial x_i} (\sigma \cdot \mathbf{V})_i \\
 &= \frac{\partial}{\partial x_i} (\sigma_{ij} \cdot \mathbf{V}_j) \\
 &= \left( \frac{\partial}{\partial x_i} \sigma_{ij} \right) \mathbf{V}_j + \sigma_{ij} \frac{\partial \mathbf{V}_j}{\partial x_i} \\
 &= (\nabla \cdot \sigma)_j \mathbf{V}_j + \sigma_{ij} (\nabla \mathbf{V})_{ij} \\
 &= (\nabla \cdot \sigma) \cdot \mathbf{V} + \sigma : \nabla \mathbf{V}
 \end{aligned} \tag{1.54}$$

Energy equation becomes :

$$\rho \frac{DE}{Dt} = k \nabla^2 T + \rho \mathbf{f} \cdot \mathbf{V} + (\nabla \cdot \sigma) \cdot \mathbf{V} + \sigma : \nabla \mathbf{V} + \dot{S}_{th} \tag{1.55}$$

N-S equation is given by :

$$\rho \frac{D\mathbf{V}}{Dt} = \rho \mathbf{f} + \nabla \cdot \sigma \tag{1.56}$$

or, taking dot product of both side with  $\mathbf{V}$  :

$$\rho \left( \mathbf{V} \cdot \frac{D\mathbf{V}}{Dt} \right) = \rho \mathbf{f} \cdot \mathbf{V} + (\nabla \cdot \sigma) \cdot \mathbf{V} \tag{1.57}$$



## Module 1:Preliminary Concepts and Basics Equations

## Lecture 3: A Generalized Approach

Or ,

$$\rho \frac{D}{Dt} \left( \frac{\mathbf{V}^2}{2} \right) = \rho \mathbf{f} \cdot \mathbf{V} + (\nabla \cdot \sigma) \cdot \mathbf{V} \quad (1.58)$$

Subtracting **Eqn. (1.58) from Eqn. (1.55)** one gets :

$$\rho \frac{De}{Dt} = k \nabla^2 T + \sigma : \nabla \mathbf{V} + \dot{S}_{th} \quad (1.59)$$

Here,

$$\sigma : \nabla \mathbf{V} = \left[ - \left\{ p + \frac{2}{3} \mu \nabla \cdot \mathbf{V} \right\} I + \tau \right] : \nabla \mathbf{V} \quad (1.60)$$

Again,

$$\tau = 2\mu \text{ Def } \mathbf{V} \quad (1.61)$$

And

$$\text{Def } \mathbf{V} = \frac{1}{2} \left[ \frac{\partial V_j}{\partial x_i} + \frac{\partial V_i}{\partial x_j} \right] \quad (1.62)$$



## Module 1:Preliminary Concepts and Basics Equations

## Lecture 3: A Generalized Approach

So

$$\sigma : \nabla \mathbf{V} = -p \mathbf{I} : \nabla \mathbf{V} - \frac{2}{3} \mu (\nabla \cdot \mathbf{V}) \mathbf{I} : \nabla \mathbf{V} + \tau : \nabla \mathbf{V} \quad (1.63)$$

$$\begin{aligned} &= -p (\nabla \cdot \mathbf{V}) - \frac{2}{3} \mu (\nabla \cdot \mathbf{V})^2 + \tau : \nabla \mathbf{V} \\ &= -p (\nabla \cdot \mathbf{V}) + \mu \phi \end{aligned} \quad (1.64)$$

Where

$$\Phi = \left[ \left\{ \frac{\partial V_i}{\partial x_j} + \frac{\partial V_j}{\partial x_i} \right\} \left( \frac{\partial V_i}{\partial x_j} \right) - \frac{2}{3} \left( \frac{\partial V_i}{\partial x_i} \right)^2 \right] \quad (1.65)$$

From continuity,

$$\begin{aligned} \frac{\partial \rho}{\partial t} + \nabla \cdot (\rho \mathbf{V}) &= 0 \\ \frac{\partial \rho}{\partial t} + (\mathbf{V} \cdot \nabla) \rho + \rho (\nabla \cdot \mathbf{V}) &= 0 \end{aligned} \quad (1.66)$$

Or ,

$$\begin{aligned} -\nabla \cdot \mathbf{V} &= \frac{1}{\rho} \left[ \frac{\partial \rho}{\partial t} + (\mathbf{V} \cdot \nabla) \rho \right] = \frac{1}{\rho} \frac{D\rho}{Dt} \\ -p (\nabla \cdot \mathbf{V}) &= \frac{p}{\rho} \left[ \frac{\partial \rho}{\partial t} + (\mathbf{V} \cdot \nabla) \rho \right] = \frac{p}{\rho} \frac{D\rho}{Dt} \end{aligned} \quad (1.67)$$

◀ Previous    Next ▶



## Module 1:Preliminary Concepts and Basics Equations

## Lecture 3: A Generalized Approach

Energy **Equation (1.59)** can be written as :

$$\rho \frac{De}{Dt} = k \nabla^2 T + \frac{p}{\rho} \frac{D\rho}{Dt} + \mu \Phi + \dot{S}_{th} \quad (1.68)$$

$$i = e + \frac{p}{\rho} \quad (1.69)$$

$$\rho \frac{De}{Dt} = \rho \left[ \frac{Di}{Dt} - \frac{D}{Dt} \left( \frac{p}{\rho} \right) \right] = \rho \left[ \frac{Di}{Dt} + \frac{p}{\rho^2} \frac{D\rho}{Dt} - \frac{1}{\rho} \frac{Dp}{Dt} \right] \quad (1.70)$$

Now, the energy equation becomes :

$$\rho \frac{Di}{Dt} = -\frac{p}{\rho} \frac{D\rho}{Dt} + \frac{Dp}{Dt} + k \nabla^2 T + \frac{p}{\rho} \frac{D\rho}{Dt} + \mu \Phi + \dot{S}_{th} \quad (1.71)$$

Or ,

$$\rho \frac{Di}{Dt} = \frac{Dp}{Dt} + k \nabla^2 T + \mu \Phi + \dot{S}_{th} \quad (\text{General}) \quad (1.72)$$



## Module 1:Preliminary Concepts and Basics Equations

## Lecture 3: A Generalized Approach

For liquids, one can write **(from Eqn. (1.59) and Eqn. (1.64))**,

$$\rho \frac{De}{Dt} = k\nabla^2 T + \mu\Phi + \dot{S}_{th} \quad (1.73)$$

where, the general viscous dissipation function is :

$$\begin{aligned} \Phi = & \left[ \left\{ \frac{\partial V_i}{\partial x_j} + \frac{\partial V_j}{\partial x_i} \right\} \left( \frac{\partial V_i}{\partial x_j} \right) - \frac{2}{3} \left( \frac{\partial V_i}{\partial x_i} \right)^2 \right] = \left[ 2 \frac{\partial u}{\partial x} \frac{\partial u}{\partial x} + \left( \frac{\partial u}{\partial y} + \frac{\partial v}{\partial x} \right) \frac{\partial u}{\partial y} \right. \\ & + \left( \frac{\partial u}{\partial z} + \frac{\partial w}{\partial x} \right) \frac{\partial u}{\partial z} + \left( \frac{\partial v}{\partial x} + \frac{\partial u}{\partial y} \right) \frac{\partial v}{\partial x} + 2 \frac{\partial v}{\partial y} \frac{\partial v}{\partial y} + \left( \frac{\partial v}{\partial z} + \frac{\partial w}{\partial y} \right) \frac{\partial v}{\partial z} \\ & \left. + \left( \frac{\partial w}{\partial x} + \frac{\partial u}{\partial z} \right) \frac{\partial w}{\partial x} + \left( \frac{\partial w}{\partial y} + \frac{\partial v}{\partial z} \right) \frac{\partial w}{\partial y} + 2 \frac{\partial w}{\partial z} \frac{\partial w}{\partial z} - \frac{2}{3} \left( \frac{\partial u}{\partial x} + \frac{\partial v}{\partial y} + \frac{\partial w}{\partial z} \right)^2 \right] \quad (1.74) \end{aligned}$$

However, in absence of heat sources ( $\dot{S}_{th} = 0$ ) and negligible viscous dissipation ( $\mu\Phi = 0$ , **which is often true for liquids**), the energy equation for the liquids can be written as : **(from Eqn. (1.73))**

$$\rho c \left( \frac{\partial T}{\partial t} + u \frac{\partial T}{\partial x} + v \frac{\partial T}{\partial y} + w \frac{\partial T}{\partial z} \right) = k \left( \frac{\partial^2 T}{\partial x^2} + \frac{\partial^2 T}{\partial y^2} + \frac{\partial^2 T}{\partial z^2} \right) \quad (1.75)$$

For gases, in general the energy equation can be written as **(from Equation (1.72))** ,

$$\rho c_p \frac{DT}{Dt} = \frac{Dp}{Dt} + k\nabla^2 T + \mu\Phi + \dot{S}_{th}$$

◀ Previous   Next ▶



**Important Dimensionless Numbers**

In order to nondimensionalize, we define :

$$u^* = \frac{u}{U_\infty}, \quad v^* = \frac{v}{U_\infty}, \quad w^* = \frac{w}{U_\infty}, \quad \theta = \frac{T - T_\infty}{T_w - T_\infty},$$

$$x^* = \frac{x}{L}, \quad y^* = \frac{y}{L}, \quad z^* = \frac{z}{L}, \quad p^* = \frac{p}{\rho U_\infty^2}, \quad t^* = t \frac{U_\infty}{L}$$

Assumption of  $\dot{S}_{th}=0$  produces,

$$\rho c_p \left( \frac{\partial T}{\partial t} + u \frac{\partial T}{\partial x} + v \frac{\partial T}{\partial y} + w \frac{\partial T}{\partial z} \right) = \left( \frac{\partial p}{\partial t} + u \frac{\partial p}{\partial x} + v \frac{\partial p}{\partial y} + w \frac{\partial p}{\partial z} \right) + k \left( \frac{\partial^2 T}{\partial x^2} + \frac{\partial^2 T}{\partial y^2} + \frac{\partial^2 T}{\partial z^2} \right) + \mu \Phi \quad (1.76)$$

The time derivatives will vanish for the steady state situation. In any case,

$$\frac{\partial \theta}{\partial t^*} + u^* \frac{\partial \theta}{\partial x^*} + v^* \frac{\partial \theta}{\partial y^*} + w^* \frac{\partial \theta}{\partial z^*} = \frac{U_\infty^2}{c_p(T_w - T_\infty)} \left( \frac{\partial p^*}{\partial t^*} + u^* \frac{\partial p^*}{\partial x^*} + v^* \frac{\partial p^*}{\partial y^*} + w^* \frac{\partial p^*}{\partial z^*} \right) + \frac{k}{\rho c_p U_\infty L} \left( \frac{\partial^2 \theta}{\partial x^{*2}} + \frac{\partial^2 \theta}{\partial y^{*2}} + \frac{\partial^2 \theta}{\partial z^{*2}} \right) + \frac{\mu U_\infty^2}{L \rho c_p (T_w - T_\infty) U_\infty} \bar{\Phi} \quad (1.77)$$

$$\frac{\partial \theta}{\partial t^*} + u^* \frac{\partial \theta}{\partial x^*} + v^* \frac{\partial \theta}{\partial y^*} + w^* \frac{\partial \theta}{\partial z^*} = Ec \left( \frac{\partial p^*}{\partial t^*} + u^* \frac{\partial p^*}{\partial x^*} + v^* \frac{\partial p^*}{\partial y^*} + w^* \frac{\partial p^*}{\partial z^*} \right) + \frac{1}{Re.Pr} \left( \frac{\partial^2 \theta}{\partial x^{*2}} + \frac{\partial^2 \theta}{\partial y^{*2}} + \frac{\partial^2 \theta}{\partial z^{*2}} \right) + \frac{Ec}{Re} \bar{\Phi} \quad (1.78)$$

$$Ec = \frac{U_\infty^2}{c_p(T_w - T_\infty)}, \quad Pr = \frac{\mu c_p}{k}, \quad Re = \rho \frac{U_\infty L}{\mu} \quad (1.79)$$



## Module 1:Preliminary Concepts and Basics Equations

## Lecture 3: A Generalized Approach

Let us look at the **term Ec (Eckert number)** :

$$Ec = \frac{U_{\infty}^2}{c_p(T_w - T_{\infty})} = \frac{\text{Kinetic energy of the flow}}{\text{Boundary layer enthalpy difference}} \quad (1.80)$$

$$\begin{aligned} \frac{1}{Ec} &= \frac{c_p(T_w - T_{\infty})}{U_{\infty}^2} = \frac{c_p T_{\infty}}{U_{\infty}^2} \left( \frac{T_w}{T_{\infty}} - 1 \right) \\ &= \frac{c_p}{\gamma(c_p - c_v)} \frac{a^2}{U_{\infty}^2} \left( \frac{T_w}{T_{\infty}} - 1 \right) = \frac{1}{(\gamma - 1)} \frac{1}{M^2} \left( \frac{T_w}{T_{\infty}} - 1 \right) \end{aligned} \quad (1.81)$$

$$Ec = \frac{(\gamma - 1)M^2}{[(T_w/T_{\infty}) - 1]} \quad (1.82)$$

where **M = (fluid velocity) / (local sound speed)** and a is the **local sound speed**, and M is known as **Mach Number**.

or low Mach number situation, energy equation in nondimensional form is :

$$\frac{\partial \theta}{\partial t^*} + u^* \frac{\partial \theta}{\partial x^*} + v^* \frac{\partial \theta}{\partial y^*} + w^* \frac{\partial \theta}{\partial z^*} = \frac{1}{Re.Pr} \left[ \frac{\partial^2 \theta}{\partial x^{*2}} + \frac{\partial^2 \theta}{\partial y^{*2}} + \frac{\partial^2 \theta}{\partial z^{*2}} \right] \quad (1.83)$$

◀ Previous   Next ▶



## Module 1:Preliminary Concepts and Basics Equations

## Lecture 3: A Generalized Approach

Dimensional form will be :

$$\rho c_p \left( u \frac{\partial T}{\partial x} + v \frac{\partial T}{\partial y} + w \frac{\partial T}{\partial z} \right) = k \left[ \frac{\partial^2 T}{\partial x^2} + \frac{\partial^2 T}{\partial y^2} + \frac{\partial^2 T}{\partial z^2} \right] \quad (1.84)$$

For forced convection, the variables can be presented as :

$$\theta = \theta(u, v, x, y, Re, Pr, Ec) \quad (1.85)$$

$$q_w = -k_f \frac{\partial T}{\partial n} = h(T_w - T_\infty)$$

Where, n is the dimension in the direction normal to the surface.or,

$$h = \frac{-k_f \frac{\partial T}{\partial n}}{(T_w - T_\infty)} = \frac{-k_f \frac{(T_w - T_\infty)}{L} \frac{\partial \theta}{\partial \bar{n}}}{T_w - T_\infty} \quad (1.86)$$

where  $\bar{n} = \frac{n}{L}$

Or

$$\left( \frac{hL}{k} \right) = Nu = - \left( \frac{\partial \theta}{\partial \bar{n}} \right) \quad (1.87)$$

Therefore, **Nusselt number, Nu is the nondimensional temperature gradient at the surface** on which heat transfer takes place.

◀ Previous   Next ▶